

MACX-MR-V-600-R-PT - Monitoring relay



1487460
<https://www.phoenixcontact.com/us/products/1487460>

Please be informed that the data shown in this PDF document is generated from our online catalog. Please find the complete data in the user documentation. Our general terms of use for downloads are valid.



1-phase voltage monitoring relay with RS-485 interface (0 V ... 600 V AC/DC), with adjustable threshold values, response delay, undervoltage, overvoltage, window monitoring functions. 24 V ... 240 V AC/DC wide-range power supply. Supports failure record storage, supports NFC communication and Modbus/RTU communication, with two configuration possibilities. 1 PDT dry contact output, plug-in connection.

Commercial data

Item number	1487460
Packing unit	1 pc
Minimum order quantity	1 pc
Sales key	C443
Product key	DK6611
GTIN	4063151931421
Weight per piece (including packing)	185.4 g
Weight per piece (excluding packing)	185.4 g
Customs tariff number	85371098
Country of origin	CN

MACX-MR-V-600-R-PT - Monitoring relay



1487460

<https://www.phoenixcontact.com/us/products/1487460>

Technical data

Product properties

Product type	Voltage monitoring relay
Operating mode	Closed circuit or wire break
Mechanical service life	Approx. 1×10^7 cycles

Insulation characteristics: Railway standard

Overvoltage category	III
Pollution degree	3

Electrical properties

Rated impulse withstand voltage	6 kV
Service life electrical	approx. 1×10^5 cycles, resistive load 2000 V A
Maximum power dissipation for nominal condition	15 W
Mains type	Single-phase AC, DC

Railway standard

Rated insulation voltage	600 V
--------------------------	-------

Electrical isolation

Electrical isolation	300 V
----------------------	-------

Supply

Supply voltage range	24 V AC ... 240 V AC -15 % ... +10 %
	24 V DC ... 240 V DC -25 % ... +30 %
	24 V ... 240 V AC -10 % ... +10 % (Railway application)
	48 V ... 110 V DC (Railway application)
Nominal power consumption	15 VA (1.5 W)
Frequency range	48 Hz ... 400 Hz

Input data

Input name	Measuring input
Measured value	DC, AC sine (15 Hz ... 500 Hz)
Input voltage range	0 V AC/DC ... 600 V AC/DC
Input resistance of voltage input	0.75 M Ω
Frequency range	48 Hz ... 400 Hz
Maximum temperature coefficient	0.05 %/K
Setting range for response delay	0 s ... 99.9 s
Min setting range of the voltage threshold value	0 V AC/DC ... 600 V AC/DC
Max. setting range of the voltage threshold value	600 V AC/DC
Function	Undervoltage
	Overvoltage
	Window
Basic accuracy	1 % (>50 V) , ± 0.5 V (0...50 V)

MACX-MR-V-600-R-PT - Monitoring relay



1487460

<https://www.phoenixcontact.com/us/products/1487460>

Repeat accuracy	0.5 %
Recovery time	200 ms

Output data

Switching

Contact switching type	1 floating changeover contact
Contact material	AgSnO ₂
Maximum switching voltage	250 V AC
Interrupting rating (ohmic load) max.	2000 VA (8 A/250 V AC)
Output fuse	10 A (fast-blow)

Connection data

Connection method	Push-in connection
Stripping length	10 mm
Conductor cross-section rigid	0.2 mm ² ... 2.5 mm ²
Conductor cross-section flexible	0.2 mm ² ... 2.5 mm ²
Conductor cross-section AWG	24 ... 14

Interfaces

Data: Network interface

Communication protocol	Modbus/RTU
Communication standard	RS-485
Connection method	Plug-in connection
Transmission speed range	2.4 kbps ... 115.2 kbps

Signaling

Status display	LED
----------------	-----

Dimensions

Width	22.5 mm
Height	109 mm
Depth	114 mm

Material specifications

Flammability rating according to UL 94	V0
Housing insulation material	PBT

Environmental and real-life conditions

Ambient conditions

Degree of protection	IP20
	IP20
Ambient temperature (operation)	-40 °C ... 70 °C
Ambient temperature (storage/transport)	-40 °C ... 85 °C

MACX-MR-V-600-R-PT - Monitoring relay



1487460

<https://www.phoenixcontact.com/us/products/1487460>

Altitude	2000 m
Permissible humidity (operation)	10 % ... 95 %

Approvals

CE/UKCA

Identification	EN 62311, EN 300 330, EN 301 489-1, EN 301 489-3, EN/IEC 63000
----------------	--

UL, USA/Canada

Identification	UL/C-UL Listed UL 508
----------------	-----------------------

CCC

Identification	GB/T 14048.5
----------------	--------------

TÜV

Identification	EN 60947-5-1
	EN 60255-27

Electronic devices in rail vehicles

Operating temperature class	OT4
Class of extended operating temperature upon activation	ST2
Temperature change class	H1
Interruption of the power supply/supply changeover	S2
	S3/C1
	C2
Hazard levels	HL1
	HL2
	HL3
Protective coating	PC2
Shock (operation)	Category 1
Vibration (operation)	Class B

EMC data

Electromagnetic compatibility	Conformance with EMC directive
Low Voltage Directive	Conformance with Low Voltage Directive
Noise immunity	EN 61000-6-2

Noise emission

Standards/regulations	EN 61000-6-4
-----------------------	--------------

Standards and regulations

Railway standard

Standard designation	EN 50155, GB/T 25119
----------------------	----------------------

Mounting

Mounting type	DIN rail mounting
---------------	-------------------

MACX-MR-V-600-R-PT - Monitoring relay




1487460

<https://www.phoenixcontact.com/us/products/1487460>

Assembly note	on standard DIN rail NS 35 in accordance with EN 60715
Mounting position	any

Drawings

Diagram



Interrupting rating

MACX-MR-V-600-R-PT - Monitoring relay



1487460

<https://www.phoenixcontact.com/us/products/1487460>

Approvals

🔗 To download certificates, visit the product detail page: <https://www.phoenixcontact.com/us/products/1487460>



CCC

Approval ID: 2024010303656845

MACX-MR-V-600-R-PT - Monitoring relay



1487460

<https://www.phoenixcontact.com/us/products/1487460>

Classifications

ECLASS

ECLASS-13.0	27371801
ECLASS-15.0	27371801

ETIM

ETIM 10.0	EC001438
-----------	----------

UNSPSC

UNSPSC 21.0	41113600
-------------	----------

MACX-MR-V-600-R-PT - Monitoring relay



1487460

<https://www.phoenixcontact.com/us/products/1487460>

Environmental product compliance

EU RoHS

Fulfills EU RoHS substance requirements	Yes
Exemption	7(a), 7(c)-I

China RoHS

Environment friendly use period (EFUP)	EFUP-50
	An article-related China RoHS declaration table can be found in the download area for the respective article under "Manufacturer declaration". For all articles with EFUP-E, no China RoHS declaration table issued and required.

EU REACH SVHC

REACH candidate substance (CAS No.)	Lead(CAS: 7439-92-1)
SCIP	435d172f-a35f-4515-b3e2-36c28241a05f

EF3.1 Climate Change

CO2e kg	8.453 kg CO2e
---------	---------------

Phoenix Contact 2026 © - all rights reserved
<https://www.phoenixcontact.com>

Phoenix Contact USA
586 Fulling Mill Road
Middletown, PA 17057, United States
(+717) 944-1300
info@phoenixcon.com