# SACC-P12MSX-8CT-CL SH - Data connector

1489580

https://www.phoenixcontact.com/us/products/1489580

Please be informed that the data shown in this PDF document is generated from our online catalog. Please find the complete data in the user documentation. Our general terms of use for downloads are valid.



Data connector, Ethernet CAT6$_A$ (10 Gbps), PROFINET CAT6$_A$ (10 Gbps), 8-position, shielded, Plug straight M12 Push-Pull, coding: X, Crimp connection, knurl material: Zinc die-cast, tin-plated, external cable diameter 6.5 mm ... 10 mm, without crimp contacts

## Your advantages

- Extremely compact, thanks to the small wiring space and high contact density
- Safe use in the field, thanks to a high degree of protection
- Safely shielded: reliable shield connection even under extreme mechanical strain
- Robust connection: suitable for railway applications with high shock and vibration loads

## Commercial data

| | |
|---|---|
| Item number | 1489580 |
| Packing unit | 1 pc |
| Minimum order quantity | 1 pc |
| Sales key | BF33 |
| Product key | AF2CJJ |
| GTIN | 4063151936723 |
| Weight per piece (including packing) | 24.3 g |
| Weight per piece (excluding packing) | 24.3 g |
| Customs tariff number | 85366990 |
| Country of origin | PL |

# Technical data

## Notes

| | |
|---|---|
| General | This product corresponds to the PROFINET Cabling and Interconnection Technology Guideline for PROFINET regulations, version 2.00, order no: 2.252, Chapter 8.2 Connectors for Outside Environment (Balanced cabling) |
| Assembly note | NOTE: Observe the permissible bending radii when routing cables, since the degree of protection may be at risk if the bending forces are too high. Reduce mechanical loads upstream of the connector, e.g., by using cable ties. |

## Mounting

| | |
|---|---|
| Assembly note | Contacts can be clipped in place and unclipped without tools |


## Product properties

| | |
|---|---|
| Product type | Circular connector (cable-side) |
| Application | Data |
| Number of positions | 8 |
| No. of cable outlets | 1 |
| Shielded | yes |
| Coding | X |
| Cable outlet | straight |

### Insulation characteristics

| | |
|---|---|
| Overvoltage category | II |
| Degree of pollution | 3 |

## Dimensions

| | |
|---|---|
| Dimensional drawing |   |
| Length | 43 mm |
| Wrench size, union nut | 15 mm |
| Wrench size, counter nut | 14 mm |

### External dimensions

| | |
|---|---|
| Outside diameter | 6.5 mm ... 10 mm |

### Housing

| | |
|---|---|
| Diameter housing | 19 mm |

## Material specifications

| | |
|---|---|
| Flammability rating according to UL 94 | V0 |
| Material of grip body | Zinc die-cast, nickel-plated |

| | |
|---|---|
| Contact carrier material | PA 6.6 |
| Material for screw connection | Zinc die-cast, tin-plated |

## Connection data

### Conductor connection

| | |
|---|---|
| Connection method | Crimp connection |
| Connection cross section | 0.14 mm² ... 0.34 mm² (flexible) |
| Connection cross section AWG | 26 ... 22 (flexible) |
| Stripping length of the individual wire | 4 mm +0,5 mm |
| Tightening torque | 1.5 Nm (Screw plug insert with sleeve housing as far it will go) |
| | 4 Nm (Pressure nut with coupling sleeve) |

### Connection assignment

| | |
|---|---|
| Contact \| Color (signal designation) \| Contact (optional) | 1 = WHOG (D1+) |
| | 2 = OG (D1-) |
| | 3 = WHGN (D2+) |
| | 4 = GN (D2-) |
| | 5 = WHBN (D4+) |
| | 6 = BN (D4-) |
| | 7 = WHBU (D3-) |
| | 8 = BU (D3+) |

## Electrical properties

| | |
|---|---|
| Rated surge voltage | 0.8 kV |
| Insulation resistance | ≥ 100 MΩ |
| Nominal voltage $U_N$ | 48 V AC |
| | 60 V DC |
| Nominal current $I_N$ | 0.5 A |
| Transmission speed | 10 Gbps |

## Mechanical properties

### Mechanical data

| | |
|---|---|
| Insertion/withdrawal cycles | ≥ 100 |

## Connector

### Connection 1

| | |
|---|---|
| Head design | Plug |
| Head cable outlet | straight |
| Head thread type | M12 |
| Head locking type | Push-Pull |
| Coding | X |

## Interfaces

| | |
|---|---|
| Signal type/category | Ethernet $CAT6_A$ (IEC 11801), 10 Gbps |

| | |
|---|---|
| | PROFINET CAT6$_A$ (IEC 11801), 10 Gbps |

## Environmental and real-life conditions

### Ambient conditions


| | |
|---|---|
| Degree of protection | IP65 |
| | IP67 |
| Ambient temperature (operation) (male connector/female connector) | -40 °C ... 85 °C (Plug) |

## Standards and regulations

| | |
|---|---|
| Standard designation | M12-Push-Pull |
| Standards/specifications | IEC 61076-2-010 |
| Standard designation | Shock, vibration |
| Standards/specifications | EN 50155:2001 |


## Drawings

Dimensional drawing





Dimensional drawing

Functional drawing




Functional drawing

Schematic diagram




Pin assignment M12 plug, 8-pos., view plug side

## Approvals

To download certificates, visit the product detail page: https://www.phoenixcontact.com/us/products/1489580

**UL Listed**
Approval ID: E335024

**cUL Listed**
Approval ID: E335024

## Classifications

### ECLASS

| | |
|---|---|
| ECLASS-13.0 | 27440116 |
| ECLASS-15.0 | 27440116 |

### ETIM

| | |
|---|---|
| ETIM 10.0 | EC002635 |

### UNSPSC

| | |
|---|---|
| UNSPSC 21.0 | 39121400 |

## Environmental product compliance

EU RoHS

| | |
|---|---|
| Fulfills EU RoHS substance requirements | Yes, No exemptions |

China RoHS

| | |
|---|---|
| Environment friendly use period (EFUP) | EFUP-E |
| | No hazardous substances above the limits |

EU REACH SVHC

| | |
|---|---|
| REACH candidate substance (CAS No.) | No substance above 0.1 wt% |

Phoenix Contact 2026 © - all rights reserved
https://www.phoenixcontact.com

Phoenix Contact USA
586 Fulling Mill Road
Middletown, PA 17057, United States
(+717) 944-1300
info@phoenixcon.com