

# PTCB TM1 3A F2 NO P - Thermal-magnetic device circuit breaker



1509522

<https://www.phoenixcontact.com/us/products/1509522>

Please be informed that the data shown in this PDF document is generated from our online catalog. Please find the complete data in the user documentation. Our general terms of use for downloads are valid.



Thermal-magnetic device circuit breaker, 1-position, tripping characteristic: F2, mounting type: With base element on 35 mm DIN rail in accordance with EN 60715, rated current: 3 A

## Your advantages

- More space in the control cabinet: protection and signaling in an overall width of just 8 mm
- Easy to set up applications thanks to flexible use of connectors with fixed nominal currents
- Transparency of load and switching status thanks to integrated remote signaling
- Easy handling from commissioning right through to maintenance due to clear functionality and switching state at all times

## Commercial data

|                                      |               |
|--------------------------------------|---------------|
| Item number                          | 1509522       |
| Packing unit                         | 4 pc          |
| Minimum order quantity               | 4 pc          |
| Sales key                            | CL10          |
| Product key                          | CLA127        |
| GTIN                                 | 4063151971243 |
| Weight per piece (including packing) | 26.3 g        |
| Weight per piece (excluding packing) | 21.205 g      |
| Customs tariff number                | 85362010      |
| Country of origin                    | DE            |

# PTCB TM1 3A F2 NO P - Thermal-magnetic device circuit breaker



1509522

<https://www.phoenixcontact.com/us/products/1509522>

## Technical data

### Product properties

|                         |  |
|-------------------------|--|
| Product type            | Thermomagnetic device circuit breakers |
| Product family          | PTCB TM                                |
| Number of positions     | 1                                      |
| No. of channels         | 1                                      |
| Mechanical service life | 25 insertion cycles                    |

### Insulation characteristics

|                      |   |
|----------------------|---|
| Protection class     | II (according to EN 61140 for the actuation area) |
| Overvoltage category | II (250 V AC / IEC 60934)                         |
|                      | III (UL 1077)                                     |
|                      | III (80 V DC / IEC 60934)                         |
| Pollution degree     | 2 (250 V AC / IEC 60934)                          |
|                      | 3 (UL 1077)                                       |
|                      | 2 (80 V DC / IEC 60934)                           |

### Electrical properties

#### General

|   |  |
|---|--|
| Operating voltage                               | 10 V AC ... 277 V AC (UL 1077)   |
|   | 10 V AC ... 240 V AC (IEC 60934)   |
|   | 10 V DC ... 56 V DC  |
| Rated voltage                                   | 240 V AC (IEC 60934)   |
|   | 277 V AC (UL 1077)   |
|   | 56 V DC (IEC 60934)  |
|   | 56 V DC (UL 1077)  |
| Rated insulation voltage $U_i$                  | 250 V AC (IEC 60934)   |
|   | 80 V DC (IEC 60934)  |
|   | 277 V AC (UL 1077)   |
| Rated current $I_N$                             | 3 A  |
| Rated surge voltage                             | 2.5 kV (IEC 60934, reinforced insulation between load/auxiliary circuit and in the actuation area) |
| Insulation resistance $R_{iso}$                 | > 100 M $\Omega$ (500 V DC)  |
| Type of actuation                               | S type   |
| Tripping method                                 | TM (thermal-magnetic)  |
| Tripping level                                  | Trip-free mechanism (positive)   |
| Device resistance                               | 121 m $\Omega$   |
| Required backup fuse                            | 16 A ( $I > I_{cn}$ , RK5 (UL 1077), type gG (IEC 60934))  |
| Rated short-circuit switching capacity $I_{cn}$ | 300 A (240 V AC / IEC 60934)   |
|   | 600 A (56 V DC/IEC 60934)  |
| Short-circuit switching capacity                | 1000 A (277 V AC C1 / UL 1077)   |

# PTCB TM1 3A F2 NO P - Thermal-magnetic device circuit breaker



1509522

<https://www.phoenixcontact.com/us/products/1509522>

|                        |  |
|------------------------|--|
|                        | 1000 A (56 V DC C1 / UL 1077)  |
| Dielectric strength    | 3000 V AC (Actuation area)   |
|                        | 3000 V AC (between load and auxiliary circuits in accordance with IEC 60934) |
|                        | 1554 V AC (between open contacts in accordance with UL 1077)                 |
| Switching cycles, max. | 6000 (low-induction, UL 1077)  |
|                        | 3000 (IEC 60934, 240 V AC/56 V DC, inductive, -5°C ... +60°C)                |
|                        | 1000 (IEC 60934, 240 V AC/56 V DC, inductive, -30°C ... +60°C)               |
| Fuse                   | F2   |
| Power dissipation      | 0 W (No-load operation)  |
|                        | 1.1 W (Nominal operation)  |
| Voltage drop           | 0.36 V (at 1 x I <sub>n</sub> )  |

## Indicator/remote signaling

|                    |                        |
|--------------------|------------------------|
| Connection name    | Connection 3 / 4       |
| Switching function | N/O contact            |
| Operating voltage  | 10 V AC ... 277 V AC   |
|                    | 10 V DC ... 56 V DC    |
| Operating current  | 10 mA AC ... 200 mA AC |
|                    | 10 mA DC ... 200 mA DC |

## Dimensions

|                     |         |
|---------------------|---------|
| Dimensional drawing |         |
| Width               | 8.2 mm  |
| Height              | 52.3 mm |
| Depth               | 63.7 mm |

## Material specifications

|  |                       |
|--|-----------------------|
| Color  | light gray (RAL 7035) |
| Material   | PA                    |
| Flammability rating according to UL 94                 | V-0                   |
| Insulating material group                              | I                     |
| Fire protection for rail vehicles (DIN EN 45545-2) R22 | HL 1 - HL 3           |
| Fire protection for rail vehicles (DIN EN 45545-2) R23 | HL 1 - HL 3           |

## Mechanical properties

### Mechanical data

# PTCB TM1 3A F2 NO P - Thermal-magnetic device circuit breaker



1509522

<https://www.phoenixcontact.com/us/products/1509522>

|                 |    |
|-----------------|----|
| Open side panel | No |
|-----------------|----|

## Environmental and real-life conditions

### Ambient conditions

|   |  |
|---|--|
| Degree of protection                    | IP20 (Connection area)<br>IP30 (Actuation area)  |
| Ambient temperature (operation)         | -30 °C ... 60 °C   |
| Ambient temperature (storage/transport) | -40 °C ... 80 °C   |
| Altitude                                | ≤ 2000 m (250 V AC / IEC 60934)  |
| Humidity test                           | 96 h, 95 % RH, 40 °C   |
| Shock (operation)                       | 30g (IEC 60068-2-27, Test Ea)<br>Category 1, Class B (DIN EN 61373)  |
| Vibration (operation)                   | 10 Hz ... 150 Hz, 20 cycles (IEC 60068-2-6, Test Fc)<br>10 Hz ... 75 Hz (Amplitude ±0.35 mm; in accordance with IEC 60068-2-6, Test Fc)<br>75 Hz ... 150 Hz (8g)<br>Category 1, Class B (DIN EN 61373) |

## Approvals

### UL approval

|                |                       |
|----------------|-----------------------|
| Identification | UL Recognized UL 1077 |
|----------------|-----------------------|

### CSA, Canada

|                |                      |
|----------------|----------------------|
| Identification | CSA C22.2 No. 235-04 |
|----------------|----------------------|

## Standards and regulations

|                          |   |
|--------------------------|---|
| Standards/specifications | IEC 60934   |
| Note                     | 2019  |
| Standards/specifications | UL 1077   |
| Note                     | Additional protective devices for use in electrical equipment       |
| Standards/specifications | CSA C22.2 No. 235-04  |
| Note                     | 2017  |
| Standards/specifications | IEC 60068-2-6   |
| Note                     | Environmental influences – Vibrations (sinusoidal)                  |
| Standards/specifications | IEC 60068-2-11  |
| Note                     | Environmental influences - corrosion resistance/salt spray, test Ka |
| Standards/specifications | EN 60068-2-27   |
| Note                     | Environmental influences – Shocks                                   |
| Standards/specifications | EN 60068-2-78   |
| Note                     | Environmental influences – Moisture and heat, constant              |
| Standards/specifications | DIN EN 50274  |
| Note                     | Touch protection and back-of-hand safety                            |

# PTCB TM1 3A F2 NO P - Thermal-magnetic device circuit breaker



1509522

<https://www.phoenixcontact.com/us/products/1509522>

|                          |   |
|--------------------------|---|
| Standards/specifications | IEC 60529   |
| Note                     | 2019  |
| Standards/specifications | EN 61373  |
| Note                     | Railway applications - Rolling stock equipment - Shock and vibration tests  |
| Standards/specifications | EN 45545-2  |
| Note                     | Railway applications - Fire protection on railway vehicles - Part 2: Requirements for fire behavior of materials and components |

## Mounting


|               |   |
|---------------|---|
| Mounting type | With base element on 35 mm DIN rail in accordance with EN 60715 |
|---------------|---|

# PTCB TM1 3A F2 NO P - Thermal-magnetic device circuit breaker

1509522

<https://www.phoenixcontact.com/us/products/1509522>

## Drawings




# PTCB TM1 3A F2 NO P - Thermal-magnetic device circuit breaker



1509522


<https://www.phoenixcontact.com/us/products/1509522>

Dimensional drawing



The figure shows the complete module consisting of a base element and connector

Application drawing



# PTCB TM1 3A F2 NO P - Thermal-magnetic device circuit breaker

1509522

<https://www.phoenixcontact.com/us/products/1509522>

Connection diagram



# PTCB TM1 3A F2 NO P - Thermal-magnetic device circuit breaker

1509522

<https://www.phoenixcontact.com/us/products/1509522>

Schematic diagram



Actuation area A


# PTCB TM1 3A F2 NO P - Thermal-magnetic device circuit breaker



1509522

<https://www.phoenixcontact.com/us/products/1509522>

Diagram



Tripping characteristic in the AC range


# PTCB TM1 3A F2 NO P - Thermal-magnetic device circuit breaker



1509522

<https://www.phoenixcontact.com/us/products/1509522>

Diagram



Trigger characteristic in the DC range

# PTCB TM1 3A F2 NO P - Thermal-magnetic device circuit breaker



1509522

<https://www.phoenixcontact.com/us/products/1509522>

Diagram



Operating current correction factor

# PTCB TM1 3A F2 NO P - Thermal-magnetic device circuit breaker



1509522

<https://www.phoenixcontact.com/us/products/1509522>

Circuit diagram



Graphic symbol

# PTCB TM1 3A F2 NO P - Thermal-magnetic device circuit breaker



1509522

<https://www.phoenixcontact.com/us/products/1509522>

Circuit diagram



Graphic symbol

# PTCB TM1 3A F2 NO P - Thermal-magnetic device circuit breaker



1509522

<https://www.phoenixcontact.com/us/products/1509522>



# PTCB TM1 3A F2 NO P - Thermal-magnetic device circuit breaker



1509522

<https://www.phoenixcontact.com/us/products/1509522>

## Approvals

To download certificates, visit the product detail page: <https://www.phoenixcontact.com/us/products/1509522>



**IECEE CB Scheme**  
Approval ID: DE1-69241



**cULus Recognized**  
Approval ID: E140459



**CSA**  
Approval ID: 80247832



**VDE Zeichengenehmigung**  
Approval ID: 40060968

**CCA**

Approval ID: CCA/DE1 35015

# PTCB TM1 3A F2 NO P - Thermal-magnetic device circuit breaker



1509522

<https://www.phoenixcontact.com/us/products/1509522>

## Classifications

### ECLASS

|             |          |
|-------------|----------|
| ECLASS-13.0 | 27140401 |
| ECLASS-15.0 | 27140401 |

### ETIM

|           |          |
|-----------|----------|
| ETIM 10.0 | EC003538 |
|-----------|----------|

### UNSPSC

|             |          |
|-------------|----------|
| UNSPSC 21.0 | 39121410 |
|-------------|----------|

# PTCB TM1 3A F2 NO P - Thermal-magnetic device circuit breaker



1509522

<https://www.phoenixcontact.com/us/products/1509522>

## Environmental product compliance

### EU RoHS

|   |                    |
|---|--------------------|
| Fulfills EU RoHS substance requirements | Yes, No exemptions |
|---|--------------------|

### China RoHS

|  |  |
|--|--|
| Environment friendly use period (EFUP) | EFUP-E                                   |
|  | No hazardous substances above the limits |

### EU REACH SVHC

|                                     |                            |
|-------------------------------------|----------------------------|
| REACH candidate substance (CAS No.) | No substance above 0.1 wt% |
|-------------------------------------|----------------------------|

Phoenix Contact 2026 © - all rights reserved  
<https://www.phoenixcontact.com>

Phoenix Contact USA  
586 Fulling Mill Road  
Middletown, PA 17057, United States  
(+717) 944-1300  
[info@phoenixcon.com](mailto:info@phoenixcon.com)