

RC-09S1N12E100 - Device connector rear mounting



1596076

<https://www.phoenixcontact.com/us/products/1596076>

Please be informed that the data shown in this PDF document is generated from our online catalog. Please find the complete data in the user documentation. Our general terms of use for downloads are valid.



M23, Device connector rear mounting, application: Signal, series: RC, straight, shielded: yes, Screw locking mechanism, No. of pos.: 8+1, Direction of rotation: Standard, contact connection type: Socket, Solder cup, Flat gasket, Panel thickness min.: 3 mm, Panel thickness max.: 10.5 mm, coding: N

The figure shows the 17-pos.
product version with O-ring seal

Commercial data

Item number	1596076
Packing unit	40 pc
Minimum order quantity	1 pc
Note	Made to order (non-returnable)
Product key	ABRAFL
GTIN	4046356209700
Weight per piece (including packing)	48.44 g
Weight per piece (excluding packing)	40.44 g
Country of origin	DE

1596076

<https://www.phoenixcontact.com/us/products/1596076>

Technical data

Product properties

Product type	Circular connectors (device side)
--------------	-----------------------------------

Connector

Insulating body

Coding	N
Material (Insulating body)	PBT
Material (Contact)	CuZn
Material (Contact surface)	Ni/Au
Insertion/withdrawal cycles	50
Connection method	Solder cup
Contact switching type	Socket
Application	Signal
Number of positions	9
Direction of rotation	Standard
Connection profile	8+1
Number (Contact group 1)	1
Contact diameter (Contact group 1)	2 mm
Litz wires Min. cross section (Contact group 1)	0.08 mm ²
Litz wires Max. cross section (Contact group 1)	2.5 mm ²
Rated current Contact (Contact group 1)	20 A (for max. connection cross section)
Rated voltage Contact (Contact group 1)	48 V AC 74 V DC
Rated surge voltage	1.5 kV
Overvoltage category	III
Degree of pollution	3
Number (Contact group 2)	8
Contact diameter (Contact group 2)	1 mm
Litz wires Max. cross section (Contact group 2)	1 mm ²
Rated current Contact (Contact group 2)	8 A (for max. connection cross section)
Rated voltage Contact (Contact group 2)	48 V AC 48 V AC

Housing

Order information:	Order contact inserts separately
Type	Flange housing
Thread type	M23
Design	straight
Type of locking	Screw locking mechanism
Pg screw connection	none
Mounting type	Rear mounting/square flange (4x M3)

RC-09S1N12E100 - Device connector rear mounting



1596076

<https://www.phoenixcontact.com/us/products/1596076>

Housing material	Metal
Degree of protection (plugged in)	IP67
Seal for the device	Flat gasket

RC-09S1N12E100 - Device connector rear mounting




1596076

<https://www.phoenixcontact.com/us/products/1596076>

Drawings

Schematic diagram



Connector pin assignment

1596076

<https://www.phoenixcontact.com/us/products/1596076>

Schematic diagram



Connector pin assignment


RC-09S1N12E100 - Device connector rear mounting



1596076

<https://www.phoenixcontact.com/us/products/1596076>

Schematic diagram



Dimensional drawing

Phoenix Contact 2026 © - all rights reserved
<https://www.phoenixcontact.com>

Phoenix Contact USA
586 Fulling Mill Road
Middletown, PA 17057, United States
(+717) 944-1300
info@phoenixcon.com