

RC-12P1N8AC3K5 - Rear panel feed-through



1597579

<https://www.phoenixcontact.com/us/products/1597579>

Please be informed that the data shown in this PDF document is generated from our online catalog. Please find the complete data in the user documentation. Our general terms of use for downloads are valid.



M23, Rear panel feed-through, application: Signal, series: RC, straight, shielded: yes, Screw locking mechanism, No. of pos.: 12, Direction of rotation: Standard, contact connection type: Pin, Crimp connection, Radial O-ring, Panel thickness max. : 2.5 mm, coding: N. This product is in the process of being discontinued. This product must no longer be considered for new projects. Please contact your sales representative for alternatives.

The figure shows the product with assembled crimp contacts. Please order crimp contacts separately.

Commercial data

| | |
|--------------------------------------|---------------|
| Item number | 1597579 |
| Packing unit | 20 pc |
| Minimum order quantity | 1 pc |
| Product key | ABRAFJ |
| GTIN | 4046356216937 |
| Weight per piece (including packing) | 82.894 g |
| Weight per piece (excluding packing) | 78.163 g |
| Country of origin | DE |

RC-12P1N8AC3K5 - Rear panel feed-through



1597579

<https://www.phoenixcontact.com/us/products/1597579>

Technical data

Notes

| | |
|--------------------|--|
| Order information: | Order crimp contacts Ø 1 mm separately |
|--------------------|--|

Product properties

| | |
|--------------|-----------------------------------|
| Product type | Circular connectors (device side) |
|--------------|-----------------------------------|

Connector

Insulating body

| | |
|---|---|
| Note | Order information: Order crimp contacts Ø 1 mm separately |
| Coding | N |
| Material (Insulating body) | PA 6.6 |
| Connection method | Crimp connection |
| Contact switching type | Pin |
| Application | Signal |
| Number of positions | 12 |
| Direction of rotation | Standard |
| Connection profile | 12 |
| Number (Contact group 1) | 12 |
| Contact diameter (Contact group 1) | 1 mm |
| Rated current Contact (Contact group 1) | 8 A (for max. connection cross section) |
| Rated voltage Contact (Contact group 1) | 48 V AC 74 V DC |
| Rated surge voltage | 1.5 kV |
| Overvoltage category | III |
| Degree of pollution | 3 |

Housing

| | |
|-----------------------------------|--|
| Order information: | Order contact inserts and cable clamping/shield accessories separately |
| Type | Feed-through header |
| Thread type | M23 |
| Design | straight |
| Type of locking | Screw locking mechanism |
| Pg screw connection | none |
| Mounting type | Rear mounting/square flange (4x M3) |
| Housing material | Metal |
| Degree of protection (plugged in) | IP67 |
| Seal for the device | Radial O-ring |

Environmental and real-life conditions

Ambient conditions

RC-12P1N8AC3K5 - Rear panel feed-through



1597579

<https://www.phoenixcontact.com/us/products/1597579>

| |
|--|
| Permissible humidity (storage/transport) |
|--|

| |
|---------------|
| 50 % ... 65 % |
|---------------|

RC-12P1N8AC3K5 - Rear panel feed-through



1597579

<https://www.phoenixcontact.com/us/products/1597579>

Drawings

Schematic diagram



Connector pin assignment

RC-12P1N8AC3K5 - Rear panel feed-through



1597579

<https://www.phoenixcontact.com/us/products/1597579>

Classifications

ECLASS

| | |
|-------------|----------|
| ECLASS-13.0 | 27440109 |
| ECLASS-15.0 | 27440109 |

ETIM

| | |
|-----------|----------|
| ETIM 10.0 | EC003569 |
|-----------|----------|

UNSPSC

| | |
|-------------|----------|
| UNSPSC 21.0 | 39121400 |
|-------------|----------|

RC-12P1N8AC3K5 - Rear panel feed-through



1597579

<https://www.phoenixcontact.com/us/products/1597579>

Environmental product compliance

EU RoHS

| | |
|---|------|
| Fulfills EU RoHS substance requirements | Yes |
| Exemption | 6(c) |

China RoHS

| | |
|--|---|
| Environment friendly use period (EFUP) | EFUP-50 |
| | An article-related China RoHS declaration table can be found in the download area for the respective article under "Manufacturer declaration". For all articles with EFUP-E, no China RoHS declaration table issued and required. |

EU REACH SVHC

| | |
|-------------------------------------|--------------------------------------|
| REACH candidate substance (CAS No.) | Lead(CAS: 7439-92-1) |
| SCIP | d3d14217-64d4-4203-b9d3-f72657eb3828 |

Phoenix Contact 2026 © - all rights reserved

<https://www.phoenixcontact.com>

Phoenix Contact USA
586 Fulling Mill Road
Middletown, PA 17057, United States
(+717) 944-1300
info@phoenixcon.com