PV-FT-CF-C-4-130-BU-12 - Device connector front mounting

1627092

https://www.phoenixcontact.com/us/products/1627092

Please be informed that the data shown in this PDF document is generated from our online catalog. Please find the complete data in the user documentation. Our general terms of use for downloads are valid.

Device connector front mounting, Range of articles: SUNCLIX, housing material: PPE

Commercial data

Item number	1627092
Packing unit	100 pc
Minimum order quantity	100 pc
Product key	ABLBAA
GTIN	4055626289342
Weight per piece (including packing)	13.46 g
Weight per piece (excluding packing)	13.46 g
Country of origin	DE

Technical data

Product properties

Product type	Panel feed-through
Product family	SUNCLIX

Insulation characteristics

Degree of pollution	3

Dimensions

Width	18.6 mm
Height	18.6 mm
Length	43.2 mm

Electrical properties

Rated voltage (III/2)	1500 V
Rated surge voltage (III/3)	16 kV

Material specifications

Color of the housing part	black
Flammability rating according to UL 94	V0
Insulating material group	I / CTI 600
Seal material	EPDM
Housing material	PPE
Cable seal material	Elastosil LR 3065/50
Contact material	Cu
Contact surface material	Ag
O-ring material	Silopren LSR 2660

Cable/line

Halogen-free	yes

Classifications

ECLASS

ECLASS-13.0	27440107
ECLASS-15.0	27440107

Environmental product compliance

EU RoHS

Fulfills EU RoHS substance requirements	Yes, No exemptions

China RoHS

Environment friendly use period (EFUP)	EFUP-E
	No hazardous substances above the limits

EU REACH SVHC

REACH candidate substance (CAS No.)	No substance above 0.1 wt%

Phoenix Contact 2026 © - all rights reserved
https://www.phoenixcontact.com

Phoenix Contact USA
586 Fulling Mill Road
Middletown, PA 17057, United States
(+717) 944-1300
info@phoenixcon.com