

# EV-T2G3PC-3AC32A-7,0M6,0ESBK01 - AC charging cable



1628199

<https://www.phoenixcontact.com/us/products/1628199>

Please be informed that the data shown in this PDF document is generated from our online catalog. Please find the complete data in the user documentation. Our general terms of use for downloads are valid.



CHARX connect comfort, Type 2, Mobile AC charging cable, 32 A permanent, 480 V AC, with vehicle charging connector and infrastructure charging plug, cable: 7 m, black, straight, with protective cap, housing: black, gray, PHOENIX CONTACT logo, IEC 62196-2, for charging electric vehicles (EV) with alternating current (AC) via type 2 vehicle charging inlets

## Product description

Mobile AC charging cable with vehicle charging connector and infrastructure charging plug for charging electric vehicles (EV) with alternating current (AC) via type 2 vehicle charging inlets, compatible with type 2 infrastructure charging sockets at charging stations for e-mobility (EVSE)

## Your advantages

- Complete product range
- Convenient handling due to the ergonomic, triple award-winning design
- Available with your logo on request - for consistent branding of your charging station
- Longitudinal water tightness reliably prevents water ingress
- Developed and produced in accordance with the IATF 16949 automotive standard and ISO 9001
- Tested in accordance with automotive standards LV124, LV214, and LV215-2
- Tested in accordance with EV Ready 37 requirements
- Laser-marked mating face in accordance with DIN EN 17186

## Commercial data

Item number	1628199
Packing unit	1 pc
Minimum order quantity	1 pc
Product key	XWBEBD
GTIN	4055626395623
Weight per piece (including packing)	3,655 g
Weight per piece (excluding packing)	3,655 g
Country of origin	PL

# EV-T2G3PC-3AC32A-7,0M6,0ESBK01 - AC charging cable



1628199

<https://www.phoenixcontact.com/us/products/1628199>

## Technical data

### Product properties

Product type	AC charging cable
Product family	CHARX connect comfort
Type	Mobile AC charging cable with vehicle charging connector and infrastructure charging plug
Design	with protective cap
Charging standard	Type 2
Charging mode	Mode 3, Case B
Affixed logo	PHOENIX CONTACT logo
Customer variations	On request

### Electrical properties

#### Charging power and current (AC charging, 3-phase)

Type of charging current	AC 3-phase
Charging current	32 A AC (3-phase)
Charging power	26.6 kW (3-phase)
Operating voltage	typ. 400 V AC

#### Pin assignment (Power contacts)

Note on the connection method	Crimp connection, cannot be disconnected
Number	5 (L1, L2, L3, N, PE)
Rated voltage	480 V AC
Rated current	32 A

#### Pin assignment (Signal contacts)

Note on the connection method	Crimp connection, cannot be disconnected
Type of signal transmission	Pulse width modulation
Number	2 (CP, PP)
Rated voltage	30 V AC
Rated current	2 A
Coding	220 $\Omega$ (between PE and PP)

## Dimensions

### Infrastructure charging plug

#### Dimensional drawing



Infrastructure plug

# EV-T2G3PC-3AC32A-7,0M6,0ESBK01 - AC charging cable



1628199

<https://www.phoenixcontact.com/us/products/1628199>

Width	58 mm
Height	131.8 mm
Depth	233.4 mm

## Vehicle charging connector

Dimensional drawing	<p>Vehicle connector</p>
Width	70 mm
Height	137 mm
Depth	215.9 mm

## Material specifications

Color (Housing)	black (9005)
Color (Handle area)	gray (7042)
Color (Mating face)	black (9005)
Color (Protective cap)	black (9005)
Color (Cable)	black (9005)
Material (Vehicle charging connector)	Plastic
Material (Cable outer sheath)	TPE-U
Material (Infrastructure charging plug)	Plastic
Material (Contact surface)	Silver
Note	The color appearance and gloss level of the charging cable may vary.

## Cable/line

Cable length	7 m
Wiring standards/regulations	prEN 50620/DIN EN 50620
Wiring certifications	VDE
Cable weight	max. 505.00 kg/km
Cable type	Class 5
Cable type	straight
Cable structure	5 x 4.0 mm <sup>2</sup> + 1 x 0.5 mm <sup>2</sup>
External cable diameter	14.20 mm ±0.3 mm
Outer sheath, material	TPE-U
Cable resistance	≤ 0.0033 Ω/m (based on a power core, at an ambient temperature of 20°C)
Bending radius	min. 127.5 mm (7.5x diameter)

## Mechanical properties

### Mechanical data

# EV-T2G3PC-3AC32A-7,0M6,0ESBK01 - AC charging cable



1628199

<https://www.phoenixcontact.com/us/products/1628199>

Insertion/withdrawal cycles	> 10000
Insertion force	< 100 N
Withdrawal force	< 100 N

## Environmental and real-life conditions

### Ambient conditions

Degree of protection (Vehicle charging connector)	IP44 (plugged in; when plugged in and ready to operate, the degree of protection is only ensued if both plug-in components are original products from Phoenix Contact or suitable standard-compliant products)
Degree of protection (Infrastructure charging plug)	IP44 (plugged in; when plugged in and ready to operate, the degree of protection is only ensued if both plug-in components are original products from Phoenix Contact or suitable standard-compliant products)
Degree of protection (Protective cap)	IP54
Ambient temperature (operation)	-40 °C ... 50 °C
Ambient temperature (storage/transport)	-40 °C ... 80 °C
Altitude	5000 m (above sea level)

## Standards and regulations

Standards/specifications	IEC 62196-2
Note	Compliant with AFIR - EU 2025/656

# EV-T2G3PC-3AC32A-7,0M6,0ESBK01 - AC charging cable



1628199

<https://www.phoenixcontact.com/us/products/1628199>

## Drawings

Dimensional drawing



## Vehicle connector

Dimensional drawing



## Infrastructure plug

# EV-T2G3PC-3AC32A-7,0M6,0ESBK01 - AC charging cable

1628199

<https://www.phoenixcontact.com/us/products/1628199>

Connection diagram



Pin assignment of Infrastructure Plug

# EV-T2G3PC-3AC32A-7,0M6,0ESBK01 - AC charging cable

1628199

<https://www.phoenixcontact.com/us/products/1628199>

Schematic diagram



Operating instructions

# EV-T2G3PC-3AC32A-7,0M6,0ESBK01 - AC charging cable

1628199

<https://www.phoenixcontact.com/us/products/1628199>

Schematic diagram



Pin assignment of the Vehicle Connector

Schematic diagram



Terminology definition

# EV-T2G3PC-3AC32A-7,0M6,0ESBK01 - AC charging cable




1628199

<https://www.phoenixcontact.com/us/products/1628199>

## Approvals

To download certificates, visit the product detail page: <https://www.phoenixcontact.com/us/products/1628199>

 <b>IECEE CB Scheme</b> Approval ID: DE1-65890/M1		Nominal voltage $U_N$	Nominal current $I_N$	Cross section AWG	Cross section $\text{mm}^2$
keine		480 V	32 A	-	-

# EV-T2G3PC-3AC32A-7,0M6,0ESBK01 - AC charging cable



1628199

<https://www.phoenixcontact.com/us/products/1628199>

## Classifications

### ECLASS

ECLASS-13.0	27144705
ECLASS-15.0	27144705

### ETIM

ETIM 10.0	EC002897
-----------	----------

### UNSPSC

UNSPSC 21.0	39121500
-------------	----------

# EV-T2G3PC-3AC32A-7,0M6,0ESBK01 - AC charging cable



1628199

<https://www.phoenixcontact.com/us/products/1628199>

## Environmental product compliance

### EU RoHS

Fulfills EU RoHS substance requirements	Yes
Exemption	6(c)

### China RoHS

Environment friendly use period (EFUP)	EFUP-50
	An article-related China RoHS declaration table can be found in the download area for the respective article under "Manufacturer declaration". For all articles with EFUP-E, no China RoHS declaration table issued and required.

### EU REACH SVHC

REACH candidate substance (CAS No.)	Lead(CAS: 7439-92-1)
SCIP	a7be104a-6643-4e8b-b9aa-31ec4722ee6b

### EF3.1 Climate Change

CO2e kg	47.18 kg CO2e
---------	---------------

Phoenix Contact 2026 © - all rights reserved  
<https://www.phoenixcontact.com>

Phoenix Contact USA  
586 Fulling Mill Road  
Middletown, PA 17057, United States  
(+717) 944-1300  
[info@phoenixcon.com](mailto:info@phoenixcon.com)