


VS-CAT5-F-4X2X26 AWG - Installation cable



1652101

<https://www.phoenixcontact.com/us/products/1652101>

Please be informed that the data shown in this PDF document is generated from our online catalog. Please find the complete data in the user documentation. Our general terms of use for downloads are valid.



CAT5e-S/UTP cable, 4 x 2 x 26 AWG, stranded (7-wire), shielded, outer sheath: Halogen-free PUR, outside diameter 6.1 mm, RAL 5021 (water blue), by the meter

Commercial data

Item number	1652101
Packing unit	1 pc
Note	Made to order (non-returnable)
Sales key	BF11
Product key	AF1LEA
Customs tariff number	85369010
Country of origin	DE

VS-CAT5-F-4X2X26 AWG - Installation cable



1652101

<https://www.phoenixcontact.com/us/products/1652101>

Technical data

Product properties

Product type	Cable by the meter
Number of positions	8
Shielded	yes

Electrical properties

Transmission characteristics (category)	CAT5 (IEC 11801:2002)
---	-----------------------

Cable/line

Ethernet [94B]

Number of positions	8
Shielded	yes
Cable type	Ethernet [94B]
Conductor structure	4x2xAWG26/7; S-UTP
Conductor structure signal line	7x 0.16 mm
AWG signal line	26
Conductor cross-section	0.14 mm ²
Wire diameter incl. insulation	1 mm
External cable diameter	6.1 mm
Outer sheath, material	PUR
External sheath, color	water blue RAL 5021
Conductor material	Bare Cu litz wires
Single wire, color	white/blue-blue, white/orange-orange, white/green-green, white/brown-brown
Twisted pairs	2 cores to the pair
Overall twist	4 pairs for core
Optical shield covering	85 %
Max. conductor resistance	≤ 284 Ω/km
Insulation resistance	≥ 5 GΩ*km
Wave impedance	100 Ω ±15 % (at 1 ... 100 MHz)
Working capacitance	48 nF (At 800 Hz)
Nominal voltage, cable	125 V
Test voltage Core/Core	1000 V
Test voltage Core/Shield	500.00 V
Smallest bending radius, fixed installation	50 mm (cable, fixed installation)
Smallest bending radius, movable installation	95 mm (Cable, flexible installation)
Ambient temperature (operation)	-20 °C ... 70 °C (cable, fixed installation) -5 °C ... 60 °C (Cable, flexible installation)

Environmental and real-life conditions

Ambient conditions

VS-CAT5-F-4X2X26 AWG - Installation cable



1652101

<https://www.phoenixcontact.com/us/products/1652101>

Ambient temperature (operation) (Cable, fixed installation)	-30 °C ... 80 °C (cable, fixed installation)
Ambient temperature (operation) (Cable, flexible installation)	-5 °C ... 60 °C (Cable, flexible installation)

VS-CAT5-F-4X2X26 AWG - Installation cable



1652101

<https://www.phoenixcontact.com/us/products/1652101>

Classifications

ECLASS

ECLASS-13.0	27061801
ECLASS-15.0	27061801

VS-CAT5-F-4X2X26 AWG - Installation cable



1652101

<https://www.phoenixcontact.com/us/products/1652101>

Environmental product compliance

China RoHS

Environment friendly use period (EFUP)	EFUP-50
	An article-related China RoHS declaration table can be found in the download area for the respective article under "Manufacturer declaration". For all articles with EFUP-E, no China RoHS declaration table issued and required.

EU REACH SVHC

REACH candidate substance (CAS No.)	No substance above 0.1 wt%
-------------------------------------	----------------------------

Phoenix Contact 2026 © - all rights reserved
<https://www.phoenixcontact.com>

Phoenix Contact USA
586 Fulling Mill Road
Middletown, PA 17057, United States
(+717) 944-1300
info@phoenixcon.com