

# PST 1,0/ 6-H-3,5 - Pin strip

1737051

<https://www.phoenixcontact.com/us/products/1737051>

Please be informed that the data shown in this PDF document is generated from our online catalog. Please find the complete data in the user documentation. Our general terms of use for downloads are valid.



The figure shows a 10-position version of the product

Pin strip, nominal cross section: 1.5 mm<sup>2</sup>, color: black, nominal current: 8 A (depends on the plug used), rated voltage (III/2): 250 V, contact surface: Sn, contact connection type: Pin, number of potentials: 6, number of rows: 1, number of positions: 6, number of connections: 6, product range: PST 1,0/..-H, pitch: 3.5 mm, mounting: THR soldering / wave soldering, pin layout: Linear pinning, solder pin [P]: 6.6 mm, number of solder pins per potential: 1, plug-in system: COMBICON PST 1,0, locking: without, mounting method: without, type of packaging: packed in cardboard, The maximum current depends on the plug used. The lower of the two current values apply for plug and pin strip. The pin strip is made of highly temperature resistant plastic and is thus suitable for the reflow process.

## Your advantages

- Suitable for wave and reflow soldering processes
- Optimum pin geometry for all COMBICON pin strip connectors

## Commercial data

|                                      |               |
|--------------------------------------|---------------|
| Item number                          | 1737051       |
| Packing unit                         | 50 pc         |
| Minimum order quantity               | 50 pc         |
| Sales key                            | AA02          |
| Product key                          | AABTKB        |
| GTIN                                 | 4046356183468 |
| Weight per piece (including packing) | 0.86 g        |
| Weight per piece (excluding packing) | 0.68 g        |
| Customs tariff number                | 85366930      |
| Country of origin                    | SK            |

# PST 1,0/ 6-H-3,5 - Pin strip



1737051

<https://www.phoenixcontact.com/us/products/1737051>

## Technical data

### Product properties

|                           |                       |
|---------------------------|-----------------------|
| Product type              | Pin strip             |
| Product family            | PST 1,0/..-H          |
| Product line              | COMBICON Connectors S |
| Type                      | Pin strip             |
| Number of positions       | 6                     |
| Pitch                     | 3.5 mm                |
| Number of connections     | 6                     |
| Number of rows            | 1                     |
| Number of potentials      | 6                     |
| Mounting type             | without               |
| Pin layout                | Linear pinning        |
| Solder pins per potential | 1                     |

### Electrical properties

#### Properties

|                             |                                |
|-----------------------------|--------------------------------|
| Nominal current $I_N$       | 8 A (depends on the plug used) |
| Nominal voltage $U_N$       | 250 V                          |
| Rated voltage (III/3)       | 160 V                          |
| Rated surge voltage (III/3) | 2.5 kV                         |
| Rated voltage (III/2)       | 250 V                          |
| Rated surge voltage (III/2) | 2.5 kV                         |
| Rated voltage (II/2)        | 250 V                          |
| Rated surge voltage (II/2)  | 2.5 kV                         |

### Mounting

|               |                                |
|---------------|--------------------------------|
| Mounting type | THR soldering / wave soldering |
| Pin layout    | Linear pinning                 |

### Material specifications

#### Material data - contact

|   |  |
|---|--|
| Note  | WEEE/RoHS-compliant, free of whiskers according to IEC 60068-2-82/JEDEC JESD 201 |
| Contact material                            | Cu alloy   |
| Surface characteristics                     | Tin-plated   |
| Metal surface contact area (top layer)      | Tin (3 $\mu\text{m}$ - 5 $\mu\text{m}$ Sn)                                       |
| Metal surface contact area (middle layer)   | Nickel (1 $\mu\text{m}$ - 3 $\mu\text{m}$ Ni)                                    |
| Metal surface soldering area (top layer)    | Tin (3 $\mu\text{m}$ - 5 $\mu\text{m}$ Sn)                                       |
| Metal surface soldering area (middle layer) | Nickel (1 $\mu\text{m}$ - 3 $\mu\text{m}$ Ni)                                    |

#### Material data - housing


# PST 1,0/ 6-H-3,5 - Pin strip

1737051

<https://www.phoenixcontact.com/us/products/1737051>

|   |              |
|---|--------------|
| Color (Housing)   | black (9005) |
| Insulating material   | PA           |
| Insulating material group   | IIIa         |
| CTI according to IEC 60112  | 250          |
| Flammability rating according to UL 94                            | V0           |
| Glow wire flammability index GWFI according to EN 60695-2-12      | 850          |
| Glow wire ignition temperature GWIT according to EN 60695-2-13    | 775          |
| Temperature for the ball pressure test according to EN 60695-10-2 | 125 °C       |

## Dimensions

|                       |  |
|-----------------------|--|
| Dimensional drawing   |  |
| Pitch                 | 3.5 mm   |
| Width [w]             | 21 mm  |
| Height [h]            | 9.4 mm   |
| Length [l]            | 10.5 mm  |
| Installed height      | 2.8 mm   |
| Solder pin length [P] | 6.6 mm   |
| Pin dimensions        | ø 1 mm   |

## PCB design

|               |        |
|---------------|--------|
| Hole diameter | 1.2 mm |
|---------------|--------|

## Electrical tests

### Air clearances and creepage distances |

|  |                     |
|--|---------------------|
| Specification  | IEC 60664-1:2007-04 |
| Insulating material group                              | IIIa                |
| Comparative tracking index (IEC 60112)                 | CTI 250             |
| Rated insulation voltage (III/3)                       | 160 V               |
| Rated surge voltage (III/3)                            | 2.5 kV              |
| minimum clearance value - non-homogenous field (III/3) | 1.5 mm              |
| minimum creepage distance (III/3)                      | 2.5 mm              |
| Rated insulation voltage (III/2)                       | 250 V               |
| Rated surge voltage (III/2)                            | 2.5 kV              |
| minimum clearance value - non-homogenous field (III/2) | 1.5 mm              |
| minimum creepage distance (III/2)                      | 2.5 mm              |
| Rated insulation voltage (II/2)                        | 250 V               |
| Rated surge voltage (II/2)                             | 2.5 kV              |
| minimum clearance value - non-homogenous field (II/2)  | 1.5 mm              |

# PST 1,0/ 6-H-3,5 - Pin strip

1737051

<https://www.phoenixcontact.com/us/products/1737051>



|                                  |        |
|----------------------------------|--------|
| minimum creepage distance (II/2) | 2.5 mm |
|----------------------------------|--------|

## Environmental and real-life conditions

### Ambient conditions

|   |   |
|---|---|
| Ambient temperature (storage/transport) | -40 °C ... 70 °C                                    |
| Relative humidity (storage/transport)   | 30 % ... 70 %                                       |
| Ambient temperature (assembly)          | -5 °C ... 100 °C                                    |
| Ambient temperature (operation)         | -40 °C ... 100 °C (dependent on the derating curve) |

### Ambient conditions

|   |   |
|---|---|
| Ambient temperature (operation)         | -40 °C ... 100 °C (dependent on the derating curve) |
| Ambient temperature (storage/transport) | -40 °C ... 70 °C                                    |
| Relative humidity (storage/transport)   | 30 % ... 70 %                                       |
| Ambient temperature (assembly)          | -5 °C ... 100 °C                                    |

## Packaging specifications

|                   |                     |
|-------------------|---------------------|
| Type of packaging | packed in cardboard |
|-------------------|---------------------|


# PST 1,0/ 6-H-3,5 - Pin strip

1737051

<https://www.phoenixcontact.com/us/products/1737051>

## Drawings

Dimensional drawing



Drilling plan/solder pad geometry



# PST 1,0/ 6-H-3,5 - Pin strip

1737051

<https://www.phoenixcontact.com/us/products/1737051>



## Approvals

To download certificates, visit the product detail page: <https://www.phoenixcontact.com/us/products/1737051>

|  <b>cULus Recognized</b><br>Approval ID: E60425-20030211 |                       |                       |                   |                             |
|---|-----------------------|-----------------------|-------------------|-----------------------------|
|   | Nominal voltage $U_N$ | Nominal current $I_N$ | Cross section AWG | Cross section $\text{mm}^2$ |
| B   |                       |                       |                   |                             |
|   | 300 V                 | 10 A                  | -                 | -                           |

# PST 1,0/ 6-H-3,5 - Pin strip

1737051

<https://www.phoenixcontact.com/us/products/1737051>



## Classifications

### ECLASS

|             |          |
|-------------|----------|
| ECLASS-13.0 | 27460201 |
| ECLASS-15.0 | 27460201 |

### ETIM

|           |          |
|-----------|----------|
| ETIM 10.0 | EC002637 |
|-----------|----------|

### UNSPSC

|             |          |
|-------------|----------|
| UNSPSC 21.0 | 39121400 |
|-------------|----------|

# PST 1,0/ 6-H-3,5 - Pin strip



1737051

<https://www.phoenixcontact.com/us/products/1737051>

## Environmental product compliance

### EU RoHS

|   |                    |
|---|--------------------|
| Fulfills EU RoHS substance requirements | Yes, No exemptions |
|---|--------------------|

### China RoHS

|  |  |
|--|--|
| Environment friendly use period (EFUP) | EFUP-E                                   |
|  | No hazardous substances above the limits |

### EU REACH SVHC

|                                     |                            |
|-------------------------------------|----------------------------|
| REACH candidate substance (CAS No.) | No substance above 0.1 wt% |
|-------------------------------------|----------------------------|

Phoenix Contact 2026 © - all rights reserved  
<https://www.phoenixcontact.com>

Phoenix Contact USA  
586 Fulling Mill Road  
Middletown, PA 17057, United States  
(+717) 944-1300  
[info@phoenixcon.com](mailto:info@phoenixcon.com)