


OCS BAT PANEL SET 1412-150-195 - Holder



1768078

<https://www.phoenixcontact.com/us/products/1768078>

Please be informed that the data shown in this PDF document is generated from our online catalog. Please find the complete data in the user documentation. Our general terms of use for downloads are valid.



Battery holder set, suitable for OCS and POS housings of size 1412, for easy integration of batteries up to size 195 x 135 x 170 mm, consisting of battery fastening set and mounting panel with base, material: galvanized steel

Your advantages

- Secure attachment even in harsh environments
- Flexible holder thanks to compatibility with standard batteries in the 72 Wh ... 720 Wh range
- Easy mounting with just one tool (wrench size 13 mm)
- Space-saving solution provides enough space for the installation of additional electronics

Commercial data

| | |
|--------------------------------------|---------------|
| Item number | 1768078 |
| Packing unit | 1 pc |
| Minimum order quantity | 1 pc |
| Sales key | AC04 |
| Product key | ACFDBZ |
| GTIN | 4067923377929 |
| Weight per piece (including packing) | 2,080 g |
| Weight per piece (excluding packing) | 1.839 g |
| Customs tariff number | 73269098 |
| Country of origin | CN |

OCS BAT PANEL SET 1412-150-195 - Holder



1768078

<https://www.phoenixcontact.com/us/products/1768078>

Technical data

Notes

| | |
|----------------|---|
| Recommendation | Further information and detailed dimensions are available in the download area. |
|----------------|---|

Product properties

| | |
|----------------|-------------------|
| Product type | Mounting material |
| Housing type | Outdoor housing |
| Housing type | Outdoor housings |
| Housing series | OCS |
| Product family | OCS..1412.. |

Dimensions

| | |
|------------|--|
| Width | 272 mm |
| Height | 333 mm |
| Depth | 157 mm |
| Dimensions | 140 mm x 40 mm x 80 mm (Minimum battery size) 195 mm x 135 mm x 170 mm (Maximum battery size) |

Material specifications

| | |
|-----------------|-------------------|
| Color | silver-colored |
| Material Holder | Steel, galvanized |

Environmental and real-life conditions

Vibration test

| | |
|------------------------|-----------------------------|
| Specification | IEC 60068-2-6:2007-12 |
| Frequency | 10 - 150 - 10 Hz |
| Sweep speed | 1 octave/min |
| Amplitude | 0.15 mm (10 Hz ... 58.1 Hz) |
| Acceleration | 2g (58.1 Hz ... 150 Hz) |
| Test duration per axis | 2.5 h |
| Test directions | X-, Y- and Z-axis |

Shocks

| | |
|--------------------------------|-----------------------------------|
| Specification | IEC 60068-2-27:2008-02 |
| Pulse shape | Half-sine |
| Acceleration | 5g |
| Shock duration | 11 ms |
| Number of shocks per direction | 3 |
| Test directions | X-, Y- and Z-axis (pos. and neg.) |

Ambient conditions

| | |
|---------------------------------|------------------|
| Ambient temperature (operation) | -40 °C ... 80 °C |
|---------------------------------|------------------|

OCS BAT PANEL SET 1412-150-195 - Holder



1768078

<https://www.phoenixcontact.com/us/products/1768078>

Mounting

| | |
|---------------|----------------|
| Mounting type | Screw mounting |
| Mounting | 4 Nm |

Packaging specifications

| | |
|-------------------|---------------|
| Type of packaging | Box packaging |
|-------------------|---------------|

OCS BAT PANEL SET 1412-150-195 - Holder



1768078

<https://www.phoenixcontact.com/us/products/1768078>

Classifications

ECLASS

| | |
|-------------|----------|
| ECLASS-13.0 | 27190605 |
| ECLASS-15.0 | 27190605 |

ETIM

| | |
|-----------|----------|
| ETIM 10.0 | EC002779 |
|-----------|----------|

OCS BAT PANEL SET 1412-150-195 - Holder



1768078

<https://www.phoenixcontact.com/us/products/1768078>

Environmental product compliance

EU RoHS

| | |
|---|--------------------|
| Fulfills EU RoHS substance requirements | Yes, No exemptions |
|---|--------------------|

China RoHS

| | |
|--|--|
| Environment friendly use period (EFUP) | EFUP-E |
| | No hazardous substances above the limits |

EU REACH SVHC

| | |
|-------------------------------------|----------------------------|
| REACH candidate substance (CAS No.) | No substance above 0.1 wt% |
|-------------------------------------|----------------------------|

Phoenix Contact 2026 © - all rights reserved
<https://www.phoenixcontact.com>

Phoenix Contact USA
586 Fulling Mill Road
Middletown, PA 17057, United States
(+717) 944-1300
info@phoenixcon.com