

TBUS8-20,0-PPPPPPP-7035 - DIN rail bus connector



2202889

<https://www.phoenixcontact.com/us/products/2202889>

Please be informed that the data shown in this PDF document is generated from our online catalog. Please find the complete data in the user documentation. Our general terms of use for downloads are valid.



DIN rail bus connector, color: light gray, nominal current: 6 A (parallel contacts), rated voltage (III/2): 32 V, number of positions: 8, product range: TBUS8-20..., pitch: 2.54 mm, mounting: DIN rail mounting, locking: without, mounting method: without, type of packaging: packed in cardboard, Item with gold-plated contacts, bus connectors for connecting with electronics housings, 8 parallel contacts

Your advantages

- Space-saving installation under the housing in the DIN rail
- Contact design enables electronics modules to be easily snapped on
- Power supply and communication without additional wiring
- Parallel and serial contacts for efficient signal and data transmission

Commercial data

| | |
|--------------------------------------|---------------|
| Item number | 2202889 |
| Packing unit | 10 pc |
| Minimum order quantity | 10 pc |
| Sales key | AC09 |
| Product key | ACHAGA |
| GTIN | 4055626382135 |
| Weight per piece (including packing) | 5.9 g |
| Weight per piece (excluding packing) | 4.53 g |
| Customs tariff number | 85366990 |
| Country of origin | PL |

TBUS8-20,0-PPPPPPP-7035 - DIN rail bus connector



2202889

<https://www.phoenixcontact.com/us/products/2202889>

Technical data

Notes

| | |
|----------------|---|
| Recommendation | Material of contact pads for bus connector, galvanic gold (hard gold) |
|----------------|---|

Product properties

| | |
|---------------------|------------------------|
| Product type | DIN rail bus connector |
| Product family | TBUS8-20.. |
| Number of positions | 8 |
| Pitch | 2.54 mm |

Electrical properties

Properties

| | |
|-----------------------------|-------------------------|
| Nominal current I_N | 6 A (parallel contacts) |
| Nominal voltage U_N | 32 V |
| Rated voltage (III/3) | 32 V |
| Rated surge voltage (III/3) | 1.5 kV |
| Rated voltage (III/2) | 32 V |
| Rated surge voltage (III/2) | 1.5 kV |
| Rated voltage (II/2) | 32 V |
| Rated surge voltage (II/2) | 1.5 kV |

Connection data

| | |
|----------------------|-----|
| Maximum load current | 6 A |
|----------------------|-----|

Material specifications

Material data - contact

| | |
|-------------------------|-------------|
| Contact material | Cu alloy |
| Surface characteristics | gold-plated |

Material data - housing

| | |
|--|-------------------|
| Color (Housing) | light gray (7035) |
| Insulating material | PA |
| Insulating material group | I |
| CTI according to IEC 60112 | 600 |
| Flammability rating according to UL 94 | V0 |

material specifications - connector

| | |
|----------|----|
| Color () | () |
|----------|----|

Dimensions

| | |
|-----------|---------|
| Pitch | 2.54 mm |
| Width [w] | 24.3 mm |

TBUS8-20,0-PPPPPPP-7035 - DIN rail bus connector



2202889

<https://www.phoenixcontact.com/us/products/2202889>

| | |
|------------|----------|
| Height [h] | 37.15 mm |
| Length [l] | 16.3 mm |

Mounting

| | |
|---------------|-------------------|
| Mounting type | DIN rail mounting |
|---------------|-------------------|

Environmental and real-life conditions

Ambient conditions

| | |
|---|---|
| Ambient temperature (storage/transport) | -40 °C ... 55 °C |
| Relative humidity (storage/transport) | 30 % ... 70 % |
| Ambient temperature (assembly) | -5 °C ... 100 °C |
| Ambient temperature (operation) | -40 °C ... 105 °C (dependent on the derating curve) |

Ambient conditions

| | |
|---|---|
| Ambient temperature (operation) | -40 °C ... 105 °C (dependent on the derating curve) |
| Ambient temperature (storage/transport) | -40 °C ... 55 °C |
| Relative humidity (storage/transport) | 30 % ... 70 % |
| Ambient temperature (assembly) | -5 °C ... 100 °C |

Electrical tests

Air clearances and creepage distances |

| | |
|--|---------------------|
| Specification | IEC 60664-1:2007-04 |
| Insulating material group | I |
| Comparative tracking index (IEC 60112) | CTI 600 |
| Rated insulation voltage (III/3) | 32 V |
| Rated surge voltage (III/3) | 1.5 kV |
| minimum clearance value - non-homogenous field (III/3) | 0.8 mm |
| minimum creepage distance (III/3) | 1.3 mm |
| Rated insulation voltage (III/2) | 32 V |
| Rated surge voltage (III/2) | 1.5 kV |
| minimum clearance value - non-homogenous field (III/2) | 0.5 mm |
| minimum creepage distance (III/2) | 0.53 mm |
| Rated insulation voltage (II/2) | 32 V |
| Rated surge voltage (II/2) | 1.5 kV |
| minimum clearance value - non-homogenous field (II/2) | 0.5 mm |
| minimum creepage distance (II/2) | 0.53 mm |

Packaging specifications

| | |
|----------------------|---------------------|
| Type of packaging | packed in cardboard |
| Outer packaging type | Carton |

TBUS8-20,0-PPPPPPP-7035 - DIN rail bus connector





2202889


<https://www.phoenixcontact.com/us/products/2202889>

Approvals

To download certificates, visit the product detail page: <https://www.phoenixcontact.com/us/products/2202889>

|  cUL Recognized Approval ID: E118976-20151204 | | | | |
|--|-----------------------|-----------------------|-------------------|-----------------------------|
| | Nominal voltage U_N | Nominal current I_N | Cross section AWG | Cross section mm^2 |
| keine | | | | |
| Power | 29.9 V | 4 A | - | - |
| Signal | 29.9 V | 4 A | - | - |

|  UL Recognized Approval ID: E118976-20151204 | | | | |
|---|-----------------------|-----------------------|-------------------|-----------------------------|
| | Nominal voltage U_N | Nominal current I_N | Cross section AWG | Cross section mm^2 |
| keine | | | | |
| Power | 29.9 V | 6 A | - | - |
| Signal | 29.9 V | 4 A | - | - |

|  VDE approval of drawings Approval ID: 40050612 | | | | |
|--|-----------------------|-----------------------|-------------------|-----------------------------|
| | Nominal voltage U_N | Nominal current I_N | Cross section AWG | Cross section mm^2 |
| keine | | | | |
| Power | 32 V | 6 A | - | - |
| Signal | 32 V | 4 A | - | - |

2202889

<https://www.phoenixcontact.com/us/products/2202889>

Classifications

ECLASS

| | |
|-------------|----------|
| ECLASS-13.0 | 27460201 |
| ECLASS-15.0 | 27460201 |

ETIM

| | |
|-----------|----------|
| ETIM 10.0 | EC002637 |
|-----------|----------|

UNSPSC

| | |
|-------------|----------|
| UNSPSC 21.0 | 39121400 |
|-------------|----------|

2202889

<https://www.phoenixcontact.com/us/products/2202889>

Environmental product compliance

EU RoHS

| | |
|---|--------------------|
| Fulfills EU RoHS substance requirements | Yes, No exemptions |
|---|--------------------|

China RoHS

| | |
|--|--|
| Environment friendly use period (EFUP) | EFUP-E |
| | No hazardous substances above the limits |

EU REACH SVHC

| | |
|-------------------------------------|----------------------------|
| REACH candidate substance (CAS No.) | No substance above 0.1 wt% |
|-------------------------------------|----------------------------|

Phoenix Contact 2026 © - all rights reserved
<https://www.phoenixcontact.com>

Phoenix Contact USA
586 Fulling Mill Road
Middletown, PA 17057, United States
(+717) 944-1300
info@phoenixcon.com