

# ELR 1-230AC/600AC-20 - Solid-state contactor



2297141

<https://www.phoenixcontact.com/us/products/2297141>

Please be informed that the data shown in this PDF document is generated from our online catalog. Please find the complete data in the user documentation. Our general terms of use for downloads are valid.



Single-phase solid-state contactor, input voltage: 230 V AC, output current: 20 A, zero voltage switch

## Your advantages

- Wear and bounce-free
- High switching frequency
- 24 V DC and 230 V AC input voltage versions

## Commercial data

Item number	2297141
Packing unit	1 pc
Note	Made to order (non-returnable)
Sales key	C471
Product key	DK7122
GTIN	4046356132015
Weight per piece (including packing)	258.8 g
Weight per piece (excluding packing)	254.7 g
Customs tariff number	85362010
Country of origin	MT

2297141

<https://www.phoenixcontact.com/us/products/2297141>

## Technical data

### Product properties

Product type	Solid-state contactor
--------------	-----------------------

### Electrical properties

Number of phases	1
Mains type	1-phase
Test voltage (Input/output)	4 kV <sub>rms</sub> (50 Hz, 60 s)

### Input data

#### Control

Input name	Control input
Rated actuating voltage $U_C$	230 V AC
Triggering voltage range	24 V AC ... 275 V AC
Rated actuating current $I_C$	approx. 17 mA
Switching threshold	$\leq 6$ V AC ("0" signal) $\geq 22$ V AC ("1" signal)
Operating voltage display	Green LED
Transmission frequency	6 Hz

### Output data

#### Load output

Operating voltage range	42 V AC ... 660 V AC
Rated operating current at AC-51	20 A
Rated operating current at AC-53a	5 A
Peak offstate voltage	1200 V
Mains frequency	45 Hz 65 Hz
Load current range	350 mA ... 20 A (see to derating)
Leakage current	< 3 mA (In off state)
Residual voltage	< 1.6 V
Surge current	250 A (t = 10 ms)
Max. load value	525 A <sup>2</sup> s
Protective circuit	RCV circuit
Phase angle $\cos \phi$ min	0.5

### Connection data

#### Control circuits

Connection method	Screw connection
Stripping length	8 mm
Screw thread	M4

# ELR 1-230AC/600AC-20 - Solid-state contactor



2297141

<https://www.phoenixcontact.com/us/products/2297141>

Conductor cross-section rigid	0.5 mm <sup>2</sup> ... 2.5 mm <sup>2</sup>
Conductor cross-section flexible	0.5 mm <sup>2</sup> ... 2.5 mm <sup>2</sup>
Conductor cross-section AWG	20 ... 14

## Load circuit

Connection method	Screw connection
Stripping length	8 mm
Screw thread	M4
Conductor cross-section rigid	0.5 mm <sup>2</sup> ... 4 mm <sup>2</sup>
Conductor cross-section flexible	0.5 mm <sup>2</sup> ... 4 mm <sup>2</sup>
Conductor cross-section AWG	20 ... 12

## Signaling

Operating voltage display	Green LED
---------------------------	-----------

## Dimensions

Width	22.5 mm
Height	103 mm
Depth	103 mm

## Material specifications

Color	green (RAL 6021)
-------	------------------

## Environmental and real-life conditions

### Ambient conditions

Ambient temperature (operation)	-30 °C ... 70 °C
Ambient temperature (storage/transport)	-40 °C ... 80 °C

## Standards and regulations

### Standards/regulations


Standards/regulations	EN 61000-4-2
	EN 61000-4-3
	EN 61000-4-4
	EN 61000-4-5
	EN 61000-4-6
	EN 55011

## Mounting


Mounting type	DIN rail mounting
Assembly note	can be aligned with $\geq 22.5$ mm spacing
Mounting position	Vertical (horizontal DIN rail)

## Drawings

Diagram



Block diagram



# ELR 1-230AC/600AC-20 - Solid-state contactor



2297141

<https://www.phoenixcontact.com/us/products/2297141>

## Classifications

### ETIM

ETIM 9.0

EC002055

Phoenix Contact 2026 © - all rights reserved

<https://www.phoenixcontact.com>

Phoenix Contact USA

586 Fulling Mill Road

Middletown, PA 17057, United States

(+717) 944-1300

[info@phoenixcon.com](mailto:info@phoenixcon.com)