


SUBCON-PLUS-IBS/F - D-SUB bus connector



2310675

<https://www.phoenixcontact.com/us/products/2310675>

Please be informed that the data shown in this PDF document is generated from our online catalog. Please find the complete data in the user documentation. Our general terms of use for downloads are valid.



D-SUB connector, 9-pos. female connector, two cable entries < 35°, bus system: INTERBUS, pin assignment: 3, 5, 6, 8; screw connection terminal blocks

Commercial data

Item number	2310675
Packing unit	1 pc
Note	Made to order (non-returnable)
Sales key	NULL
Product key	DNC512
GTIN	4046356104357
Weight per piece (including packing)	29.5 g
Weight per piece (excluding packing)	29.5 g
Customs tariff number	85369010
Country of origin	DE

SUBCON-PLUS-IBS/F - D-SUB bus connector



2310675

<https://www.phoenixcontact.com/us/products/2310675>

Technical data

Product properties

Product type	Data plug
Pin assignment	3, 5, 6, 8

Electrical properties

Nominal voltage U_N	60 V AC/DC
Nominal current I_N	1 A

Connection data

D-SUB connection

Connection method	D-SUB connector
-------------------	-----------------

PCB connection

Connection method	Screw connection
Stripping length	5 mm
Conductor cross-section, rigid min.	0.14 mm ²
Conductor cross-section, rigid max.	1.5 mm ²
Conductor cross-section flexible min.	0.14 mm ²
Conductor cross-section flexible max.	1 mm ²
Conductor cross-section AWG min.	26
Conductor cross-section AWG max.	16

Interfaces

Bus system	INTERBUS
Signal	INTERBUS

Material specifications

Material (Housing)	ABS (metal-plated)
--------------------	--------------------

Cable/line

External cable diameter	7.6 mm ... 8.4 mm (Incoming bus line)
-------------------------	---------------------------------------

Mechanical properties

Mechanical data

Insertion/withdrawal cycles	> 200
Fixing screws	4-40 UNC
Tightening torque	0.4 Nm

Environmental and real-life conditions

Ambient conditions

Degree of protection	IP40
----------------------	------

SUBCON-PLUS-IBS/F - D-SUB bus connector



2310675

<https://www.phoenixcontact.com/us/products/2310675>

Ambient temperature (operation)

-20 °C ... 55 °C

SUBCON-PLUS-IBS/F - D-SUB bus connector



2310675

<https://www.phoenixcontact.com/us/products/2310675>

Environmental product compliance

EU REACH SVHC

REACH candidate substance (CAS No.)	
-------------------------------------	--

	No substance above 0.1 wt%
--	----------------------------

Phoenix Contact 2026 © - all rights reserved

<https://www.phoenixcontact.com>

Phoenix Contact USA
586 Fulling Mill Road
Middletown, PA 17057, United States
(+717) 944-1300
info@phoenixcon.com