

# FL SFP FE WDM20-A - Media module



2702437

<https://www.phoenixcontact.com/us/products/2702437>

Please be informed that the data shown in this PDF document is generated from our online catalog. Please find the complete data in the user documentation. Our general terms of use for downloads are valid.



Fast Ethernet SFP WDM module for transmission up to a maximum of 20 km on a single fiber with a wavelength of 1310/1550 nm.

## Product description

SFP WDM module with a data transmission speed of 100 Mbps, a wavelength of 1310/1550 nm, and a maximum transmission length of 20 km.

## Your advantages

- MSA compliant

## Commercial data

|                                      |               |
|--------------------------------------|---------------|
| Item number                          | 2702437       |
| Packing unit                         | 1 pc          |
| Minimum order quantity               | 1 pc          |
| Sales key                            | DN22          |
| Product key                          | DNN1ZS        |
| GTIN                                 | 4055626189031 |
| Weight per piece (including packing) | 33 g          |
| Weight per piece (excluding packing) | 33 g          |
| Customs tariff number                | 85176200      |
| Country of origin                    | TW            |

# FL SFP FE WDM20-A - Media module



2702437

<https://www.phoenixcontact.com/us/products/2702437>

## Technical data

### Dimensions

|        |         |
|--------|---------|
| Width  | 13.7 mm |
| Height | 8.95 mm |
| Length | 56.5 mm |

### Notes

Note on application

|                     |                         |
|---------------------|-------------------------|
| Note on application | Only for industrial use |
|---------------------|-------------------------|

### Material specifications

|                  |       |
|------------------|-------|
| Housing material | Metal |
|------------------|-------|

### Mounting

|               |                    |
|---------------|--------------------|
| Mounting type | Plug-in mounting   |
| Mounting type | Insert in SFP slot |

### Interfaces

Ethernet FO

|                              |                                     |
|------------------------------|-------------------------------------|
| Connection method            | LC                                  |
| Transmission speed           | 100 Mbps                            |
| Transmit capacity, minimum   | -14 dBm                             |
| Transmit capacity, maximum   | -8 dBm                              |
| Minimum receiver sensitivity | -32 dBm                             |
| Maximum receiver sensitivity | -3 dBm                              |
| Transmission physics         | Single-mode fiberglass              |
| Transmission length          | 20 km (Fiberglass 9/125)            |
| Wavelength                   | 1310 nm (TX)<br>1550 nm (RX)        |
| Signal LEDs                  | depending on the Factoryline device |
| No. of channels              | 1 (LC single mode)                  |

### Product properties

|              |  |
|--------------|--|
| Product type | SFP module   |
| Type         | Factoryline devices with SFP slot  |
| MTTF         | 201 Years (Telcordia SR-332, temperature factor at 40°C = 1, stress factor at 50% = 1, environmental factor = 1) |
| Format       | SFP (Small Form-factor Pluggable)  |

### Signaling

|                |                          |
|----------------|--------------------------|
| Status display | via a Factoryline device |
|----------------|--------------------------|

2702437

<https://www.phoenixcontact.com/us/products/2702437>

## Electrical properties

|   |        |
|---|--------|
| Current consumption                             | 300 mA |
| Maximum power dissipation for nominal condition | 1 W    |
| Transmission medium                             | FO     |

## Supply

|                          |                                |
|--------------------------|--------------------------------|
| Supply voltage           | 3.3 V (via Factoryline switch) |
| Power supply connection  | via SFP slot                   |
| Max. current consumption | 300 mA                         |
| Current consumption      | 300 mA                         |

## Environmental and real-life conditions

### Ambient conditions

|   |                                   |
|---|-----------------------------------|
| Degree of protection                    | IP20                              |
| Ambient temperature (operation)         | -40 °C ... 75 °C                  |
| Ambient temperature (storage/transport) | -40 °C ... 85 °C (non-condensing) |
| Case temperature                        | max. 85 °C (Operation)            |

## Standards and regulations

|                          |                        |
|--------------------------|------------------------|
| Standard designation     | Laser equipment safety |
| Standards/specifications | IEC 60825              |

# FL SFP FE WDM20-A - Media module



2702437

<https://www.phoenixcontact.com/us/products/2702437>

## Approvals

To download certificates, visit the product detail page: <https://www.phoenixcontact.com/us/products/2702437>



**DNV GL**

Approval ID: TAA00000YV



**LR**

Approval ID: LR22250919TA



**NK**

Approval ID: TA24215M



**BV**

Approval ID: 48146\_B1 BV

**BSH**

Approval ID: Nr. 966



**RINA**

Approval ID: ELE014724XG001

**ABS**

Approval ID: 21\_2066186\_1\_PDA

# FL SFP FE WDM20-A - Media module



2702437

<https://www.phoenixcontact.com/us/products/2702437>

## Classifications

### ECLASS

ECLASS-13.0

19179090

### ETIM

ETIM 9.0

EC000310

### UNSPSC

UNSPSC 21.0

43222600

# FL SFP FE WDM20-A - Media module



2702437

<https://www.phoenixcontact.com/us/products/2702437>

## Environmental product compliance

### EU RoHS

|   |                    |
|---|--------------------|
| Fulfills EU RoHS substance requirements | Yes, No exemptions |
|---|--------------------|

### China RoHS

|  |  |
|--|--|
| Environment friendly use period (EFUP) | EFUP-E                                   |
|  | No hazardous substances above the limits |

### EU REACH SVHC

|                                     |                            |
|-------------------------------------|----------------------------|
| REACH candidate substance (CAS No.) | No substance above 0.1 wt% |
|-------------------------------------|----------------------------|

Phoenix Contact 2026 © - all rights reserved  
<https://www.phoenixcontact.com>

Phoenix Contact USA  
586 Fulling Mill Road  
Middletown, PA 17057, United States  
(+717) 944-1300  
[info@phoenixcon.com](mailto:info@phoenixcon.com)