

# IB ST 24 DO32/2-WT - I/O module

2752482

<https://www.phoenixcontact.com/us/products/2752482>

Please be informed that the data shown in this PDF document is generated from our online catalog. Please find the complete data in the user documentation. Our general terms of use for downloads are valid.



INTERBUS-ST digital output module, 32 outputs, 24 V DC, 500 mA, 2-conductor connection technology, IP20 degree of protection, consisting of: terminal part with screw connection and module electronics, extended temperature range

The figure shows version IB ST  
24 BDO 32/2

## Commercial data

Item number	2752482
Packing unit	1 pc
Note	Made to order (non-returnable)
Sales key	NULL
Product key	DRI332
GTIN	4017918272449
Weight per piece (including packing)	759.3 g
Weight per piece (excluding packing)	741 g
Customs tariff number	85389091
Country of origin	DE

## Technical data

### Dimensions

Width	118 mm
Height	117 mm
Length	116 mm

### Interfaces

#### ST local bus

Connection method	INTERBUS-ST local bus
Transmission speed	500 kbps

### Output data

#### Digital

Number of outputs	32
Output voltage	$U_S - 1\text{ V}$
Protective circuit	Short-circuit protection of outputs; Electronic per channel

### Product properties

Product type	I/O component
Product family	Smart Terminal ST
Type	modular

### Electrical properties

Test section	Bus/Output groups 500 V AC 50 Hz 1 min
	Output groups/Ground conductor 500 V AC 50 Hz 1 min
	Output group/Output group 500 V AC 50 Hz 1 min

#### Supply

Communications power $U_L$	9 V DC (from the ST local bus)
I/O voltage	24 V DC
I/O voltage range	20 V DC ... 30 V DC
Residual ripple	$\pm 1.2\text{ V}_{PP}$
Typical current consumption	100 mA (from the ST local bus)

### Connection data

Connection method	Screw connection
Conductor cross-section, rigid	0.2 mm <sup>2</sup> ... 2.5 mm <sup>2</sup>
Conductor cross-section, flexible	0.2 mm <sup>2</sup> ... 2.5 mm <sup>2</sup>
Conductor cross-section AWG	24 ... 12
Stripping length	8 mm

### Environmental and real-life conditions

# IB ST 24 DO32/2-WT - I/O module



2752482

<https://www.phoenixcontact.com/us/products/2752482>

## Ambient conditions

Degree of protection	IP20
Ambient temperature (operation)	-25 °C ... 55 °C
Ambient temperature (storage/transport)	-25 °C ... 70 °C

## Mounting

Mounting type	DIN rail mounting
---------------	-------------------

# IB ST 24 DO32/2-WT - I/O module

2752482

<https://www.phoenixcontact.com/us/products/2752482>



## Classifications

### UNSPSC

UNSPSC 21.0	32151602
-------------	----------

# IB ST 24 DO32/2-WT - I/O module



2752482

<https://www.phoenixcontact.com/us/products/2752482>

## Environmental product compliance

### China RoHS

Environment friendly use period (EFUP)	EFUP-E
	No hazardous substances above the limits

### EU REACH SVHC

REACH candidate substance (CAS No.)	No substance above 0.1 wt%
-------------------------------------	----------------------------

Phoenix Contact 2026 © - all rights reserved  
<https://www.phoenixcontact.com>

Phoenix Contact USA  
586 Fulling Mill Road  
Middletown, PA 17057, United States  
(+717) 944-1300  
[info@phoenixcon.com](mailto:info@phoenixcon.com)