

# MACX MCR-UI-UI-NC - Input signal conditioner



2811446

<https://www.phoenixcontact.com/us/products/2811446>

Please be informed that the data shown in this PDF document is generated from our online catalog. Please find the complete data in the user documentation. Our general terms of use for downloads are valid.



Configurable 3-way isolating amplifier with safe electrical isolation, 24 V, power bridging. DIP switches on the front, over 1600 signal conversions can be set. Standard configuration (IN 0 ... 10 V/OUT 0 ... 20 mA), screw connection, SIL.

## Your advantages

- Power supply possible via DIN rail connector
- Over 1600 signal conversions can be set via DIP switches on the front
- Installation in zone 2 permitted
- Up to SIL 2 in accordance with EN 61508
- 3-way electrical isolation
- Analog signal conditioner for isolating, filtering, amplifying, and converting standard analog signals
- Configurable input and output signals, including bipolar current and voltage signals
- 10 kHz limit frequency for time-critical applications
- Status indicator for supply voltage
- Active or passive output
- Plug-in screw or spring-cage connection technology (Push-in technology)

## Commercial data

|                                      |               |
|--------------------------------------|---------------|
| Item number                          | 2811446       |
| Packing unit                         | 1 pc          |
| Minimum order quantity               | 1 pc          |
| Sales key                            | C402          |
| Product key                          | DK1111        |
| GTIN                                 | 4046356288927 |
| Weight per piece (including packing) | 178.05 g      |
| Weight per piece (excluding packing) | 150 g         |
| Customs tariff number                | 85437090      |
| Country of origin                    | DE            |

# MACX MCR-UI-UI-NC - Input signal conditioner



2811446

<https://www.phoenixcontact.com/us/products/2811446>

## Technical data

### Product properties

|                 |                          |
|-----------------|--------------------------|
| Product type    | Input signal conditioner |
| Product family  | MACX Analog              |
| No. of channels | 1                        |
| Configuration   | DIP switches             |

### System properties

#### Functionality

|               |              |
|---------------|--------------|
| Configuration | DIP switches |
|---------------|--------------|

### Electrical properties

|   |   |
|---|---|
| Alignment span                                  | $\pm 4 \%$                                  |
| Alignment zero                                  | $\pm 4 \%$                                  |
| Electrical isolation between input and output   | yes   |
| Limit frequency (3 dB)                          | 10 kHz (Can be switched to 30 Hz)           |
| Maximum power dissipation for nominal condition | $< 0.7 \text{ W}$ (20 mA)                   |
| Protective circuit                              | Transient protection                        |
| Step response (10-90%)                          | 35 $\mu\text{s}$ (10 kHz)                   |
|   | 11 ms (30 Hz)                               |
| Maximum temperature coefficient                 | 0.0075 %/K                                  |
| Maximum transmission error                      | $\leq 0.1 \%$ (Compared to the final value) |

#### Electrical isolation

|                      |                         |
|----------------------|-------------------------|
| Test voltage         | 2.5 kV AC (50 Hz, 60 s) |
| Overvoltage category | II                      |
| Pollution degree     | 2                       |

#### Electrical isolation Input/output/power supply IEC/EN 61010-1

|                          |                      |
|--------------------------|----------------------|
| Standards/regulations    | IEC/EN 61010-1       |
| Rated insulation voltage | 300 V <sub>rms</sub> |
| Insulation               | Safe isolation       |

#### Electrical isolation Input/output/power supply IEC/EN 60079-7

|                          |                |
|--------------------------|----------------|
| Standards/regulations    | IEC/EN 60079-7 |
| Rated insulation voltage | 250 V AC/DC    |

#### Supply

|                              |                                     |
|------------------------------|-------------------------------------|
| Nominal supply voltage range | 12 V DC ... 24 V DC -20 % ... +25 % |
| Supply voltage range         | 9.6 V DC ... 30 V DC                |
| Power dissipation            | 500 mW (at 24 V DC / 20 mA)         |
| Power consumption            | $\leq 700 \text{ mW}$               |

## Input data

# MACX MCR-UI-UI-NC - Input signal conditioner



2811446

<https://www.phoenixcontact.com/us/products/2811446>

Signal: Voltage/current

|                      |  |
|----------------------|--|
| Number of inputs     | 1  |
| Voltage input signal | 0 mV ... 50 mV                               |
|                      | 0 mV ... 60 mV                               |
|                      | 0 mV ... 75 mV                               |
|                      | 0 mV ... 100 mV                              |
|                      | 0 mV ... 120 mV                              |
|                      | 0 mV ... 150 mV                              |
|                      | 0 mV ... 200 mV                              |
|                      | 0 mV ... 300 mV                              |
|                      | 0 mV ... 500 mV                              |
|                      | 0 V ... 1 V                                  |
|                      | 0 V ... 1.5 V                                |
|                      | 0 V ... 2 V                                  |
|                      | 0 V ... 3 V                                  |
|                      | 0 V ... 5 V                                  |
|                      | 0 V ... 10 V (Configurable via DIP switches) |
|                      | 0 V ... 15 V                                 |
|                      | 0 V ... 20 V                                 |
|                      | 0 V ... 30 V                                 |
|                      | 0 V ... 50 V                                 |
|                      | 0 V ... 100 V                                |
|                      | -50 mV ... 50 mV                             |
|                      | -60 mV ... 60 mV                             |
|                      | -75 mV ... 75 mV                             |
|                      | -100 mV ... 100 mV                           |
|                      | -120 mV ... 120 mV                           |
|                      | -150 mV ... 150 mV                           |
|                      | -200 mV ... 200 mV                           |
|                      | -300 mV ... 300 mV                           |
|                      | -500 mV ... 500 mV                           |
|                      | -1 V ... 1 V                                 |
|                      | -1.5 V ... 1.5 V                             |
|                      | -2 V ... 2 V                                 |
|                      | -3 V ... 3 V                                 |
|                      | -5 V ... 5 V                                 |
|                      | -10 V ... 10 V                               |
|                      | -15 V ... 15 V                               |
|                      | -20 V ... 20 V                               |
|                      | -30 V ... 30 V                               |
|                      | -50 V ... 50 V                               |
|                      | -100 V ... 100 V                             |
| 1 V ... 5 V          |  |

# MACX MCR-UI-UI-NC - Input signal conditioner



2811446

<https://www.phoenixcontact.com/us/products/2811446>

|                                   |   |
|-----------------------------------|---|
|                                   | 2 V ... 10 V                                  |
| Min. voltage input signal         | ± 50 mV                                       |
| Max. voltage input signal         | ± 100 V                                       |
| Current input signal              | 0 mA ... 1 mA (Configurable via DIP switches) |
|                                   | 0 mA ... 1.5 mA                               |
|                                   | 0 mA ... 2 mA                                 |
|                                   | 0 mA ... 3 mA                                 |
|                                   | 0 mA ... 5 mA                                 |
|                                   | 0 mA ... 10 mA                                |
|                                   | 0 mA ... 15 mA                                |
|                                   | 0 mA ... 20 mA                                |
|                                   | 0 mA ... 30 mA                                |
|                                   | 0 mA ... 50 mA                                |
|                                   | 0 mA ... 100 mA                               |
|                                   | -1 mA ... 1 mA                                |
|                                   | -1.5 mA ... 1.5 mA                            |
|                                   | -2 mA ... 2 mA                                |
|                                   | -3 mA ... 3 mA                                |
|                                   | -5 mA ... 5 mA                                |
|                                   | -10 mA ... 10 mA                              |
|                                   | -15 mA ... 15 mA                              |
|                                   | -20 mA ... 20 mA                              |
|                                   | -30 mA ... 30 mA                              |
|                                   | -50 mA ... 50 mA                              |
|                                   | -100 mA ... 100 mA                            |
|                                   | 1 mA ... 5 mA                                 |
|                                   | 2 mA ... 10 mA                                |
|                                   | 4 mA ... 20 mA                                |
| Minimum current input signal      | ± 1 mA  |
| Max. current input signal         | ± 100 mA                                      |
| Input resistance of voltage input | approx. 1 MΩ (±1 V DC ... ±100 V DC)          |
| Input resistance current input    | approx. 10 Ω (±10 mA DC ... ±100 mA DC)       |

## Output data

Signal: Voltage/current

|                           |  |
|---------------------------|--|
| Number of outputs         | 1  |
| Configurable/programmable | Yes, can be switched                         |
| Voltage output signal     | 0 V ... 10 V (Configurable via DIP switches) |
|                           | 0 V ... 5 V                                  |
|                           | 2 V ... 10 V                                 |
|                           | 1 V ... 5 V                                  |
|                           | -10 V ... 10 V                               |
|                           | -5 V ... 5 V                                 |

# MACX MCR-UI-UI-NC - Input signal conditioner



2811446

<https://www.phoenixcontact.com/us/products/2811446>

|                                 |   |
|---------------------------------|---|
|                                 | 0 V ... 2.5 V   |
|                                 | 0.5 V ... 2.5 V   |
|                                 | -2.5 V ... 2.5 V  |
| Output signal voltage inverse   | 0 V ... 2.5 V   |
|                                 | 0 V ... 5 V   |
|                                 | 0 V ... 10 V  |
| Current output signal           | 0 mA ... 5 mA   |
|                                 | 0 mA ... 10 mA  |
|                                 | 0 mA ... 20 mA (Configurable via DIP switches)          |
|                                 | 1 mA ... 5 mA   |
|                                 | 2 mA ... 10 mA  |
|                                 | 4 mA ... 20 mA  |
|                                 | -5 mA ... 5 mA  |
|                                 | -10 mA ... 10 mA  |
|                                 | -20 mA ... 20 mA  |
| Output signal current inverse   | 0 mA ... 5 mA   |
|                                 | 0 mA ... 10 mA  |
|                                 | 0 mA ... 20 mA  |
| Load/output load voltage output | $\geq 1 \text{ k}\Omega$ (10 V)                         |
| Load/output load current output | $\leq 600 \Omega$ (20 mA; active)                       |
|                                 | passive: $\leq (U_B - 2 \text{ V}) / I_{\text{outmax}}$ |
| Ripple                          | $< 10 \text{ mV}_{\text{rms}}$                          |

## Connection data

|                                  |   |
|----------------------------------|---|
| Connection method                | Screw connection                            |
| Stripping length                 | 7 mm  |
| Screw thread                     | M3  |
| Conductor cross-section rigid    | 0.2 mm <sup>2</sup> ... 2.5 mm <sup>2</sup> |
| Conductor cross-section flexible | 0.2 mm <sup>2</sup> ... 2.5 mm <sup>2</sup> |
| Conductor cross-section AWG      | 24 ... 14                                   |
| Tightening torque                | 0.5 Nm ... 0.6 Nm                           |

## Test socket

|               |      |
|---------------|------|
| Max. diameter | 2 mm |
|---------------|------|

## Ex data

|                       |        |
|-----------------------|--------|
| Ex installation (EPL) | Gc     |
|                       | Div. 2 |


## Dimensions

# MACX MCR-UI-UI-NC - Input signal conditioner



2811446

<https://www.phoenixcontact.com/us/products/2811446>

|                     |  |
|---------------------|--|
| Dimensional drawing |  |
| Width               | 12.5 mm  |
| Height              | 112.5 mm   |
| Depth               | 113.7 mm   |
| Depth NS 35/7,5     | 114.5 mm (Snapped onto DIN rail NS 35/7,5 in accordance with EN 60715)             |

## Material specifications

|                  |                 |
|------------------|-----------------|
| Color            | gray (RAL 7042) |
| Housing material | PA 6.6-FR       |

## Characteristics

Safety data: IEC 61508 - High demand

|                              |   |
|------------------------------|---|
| Safety Integrity Level (SIL) | 2 |
|------------------------------|---|

Safety data: IEC 61508 - High demand

|                              |   |
|------------------------------|---|
| Safety Integrity Level (SIL) | 2 |
|------------------------------|---|

Safety data: IEC 61508 - Low demand

|                              |   |
|------------------------------|---|
| Safety Integrity Level (SIL) | 2 |
|------------------------------|---|

Safety data: IEC 61508 - Low demand

|                              |   |
|------------------------------|---|
| Safety Integrity Level (SIL) | 2 |
|------------------------------|---|

## Environmental and real-life conditions

Ambient conditions

|   |                           |
|---|---------------------------|
| Degree of protection                    | IP20 (not assessed by UL) |
| Ambient temperature (operation)         | -20 °C ... 70 °C          |
| Ambient temperature (storage/transport) | -40 °C ... 85 °C          |

Altitude range ( $\leq 2000$  m)

|                                 |   |
|---------------------------------|---|
| Altitude                        | $\leq 2000$ m (The technical data refers to altitudes $\leq 2000$ m above mean sea level. For altitudes $>2000$ m above mean sea level, refer to the data sheet.) |
| Ambient temperature (operation) | -20 °C ... 70 °C  |

Altitude range ( $\leq 3000$  m)

|                                 |                       |
|---------------------------------|-----------------------|
| Height range                    | $> 2000$ m ... 3000 m |
| Ambient temperature (operation) | -20 °C ... 60 °C      |
| Rated insulation voltage        | 190 V                 |

# MACX MCR-UI-UI-NC - Input signal conditioner



2811446

<https://www.phoenixcontact.com/us/products/2811446>

## Altitude range ( $\leq 4000$ m)

|                                 |                     |
|---------------------------------|---------------------|
| Height range                    | > 3000 m ... 4000 m |
| Ambient temperature (operation) | -20 °C ... 55 °C    |
| Rated insulation voltage        | 63 V                |

## Altitude range ( $\leq 5000$ m)

|                                 |                     |
|---------------------------------|---------------------|
| Height range                    | > 4000 m ... 5000 m |
| Ambient temperature (operation) | -20 °C ... 45 °C    |
| Rated insulation voltage        | 63 V                |

## Approvals

### CE

|             |              |
|-------------|--------------|
| Certificate | CE-compliant |
|-------------|--------------|

### ATEX

|                |                          |
|----------------|--------------------------|
| Identification | Ⓜ II 3 G Ex ec IIC T4 Gc |
| Certificate    | BVS 10 ATEX E 059 X      |

### UKCA Ex (UKEX)

|                |                          |
|----------------|--------------------------|
| Identification | Ⓜ II 3 G Ex nA IIC T4 Gc |
| Certificate    | PxCIF21UKEX2811284X      |

### IECEX

|                |                    |
|----------------|--------------------|
| Identification | Ex ec IIC T4 Gc    |
| Certificate    | IECEX BVS 10.0044X |

### CCC / China-Ex

|                |                  |
|----------------|------------------|
| Identification | Ex ec IIC T4 Gc  |
| Certificate    | 2021122304114077 |

### UL, USA/Canada

|                |                                       |
|----------------|---------------------------------------|
| Identification | UL 61010 Listed                       |
|                | Class I, Div. 2, Groups A, B, C, D T6 |
|                | Class I, Zone 2, Group IIC            |

### Shipbuilding approval

|             |                   |
|-------------|-------------------|
| Certificate | DNV GL TAA000020C |
|-------------|-------------------|

### Safety Integrity Level (SIL, IEC 61508)

|                |   |
|----------------|---|
| Identification | 2 |
|----------------|---|

### INMETRO

|                |                 |
|----------------|-----------------|
| Identification | Ex ec IIC T4 Gc |
| Certificate    | DNV 21.0063 X   |

### Shipbuilding data

|             |   |
|-------------|---|
| Temperature | B |
| Humidity    | B |

# MACX MCR-UI-UI-NC - Input signal conditioner



2811446

<https://www.phoenixcontact.com/us/products/2811446>

|           |   |
|-----------|---|
| Vibration | A   |
| EMC       | A   |
| Enclosure | Required protection according to the Rules shall be provided upon installation on board |

## EMC data

|                               |  |
|-------------------------------|--|
| Electromagnetic compatibility | Conformance with EMC directive                                       |
| Noise immunity                | EN 61000-6-2   |
| Note                          | When being exposed to interference, there may be minimal deviations. |

## Noise emission

|                       |              |
|-----------------------|--------------|
| Standards/regulations | EN 61000-6-4 |
|-----------------------|--------------|

## Electromagnetic HF field

|  |                          |
|--|--------------------------|
| Designation  | Electromagnetic RF field |
| Standards/regulations                                  | EN 61000-4-3             |
| Typical deviation from the measuring range final value | 1 %                      |

## Fast transients (burst)

|  |                         |
|--|-------------------------|
| Designation  | Fast transients (burst) |
| Standards/regulations                                  | EN 61000-4-4            |
| Typical deviation from the measuring range final value | 1 %                     |

## Conducted interference

|  |                         |
|--|-------------------------|
| Designation  | Conducted interferences |
| Standards/regulations                                  | EN 61000-4-6            |
| Typical deviation from the measuring range final value | 1 %                     |

## Standards and regulations

### GB Standard

|                       |             |
|-----------------------|-------------|
| Standards/regulations | GB/T 3836.1 |
|                       | GB/T 3836.3 |

## Mounting

|                   |                   |
|-------------------|-------------------|
| Mounting type     | DIN rail mounting |
| Mounting position | any               |

# MACX MCR-UI-UI-NC - Input signal conditioner

2811446

<https://www.phoenixcontact.com/us/products/2811446>



## Drawings

Dimensional drawing




# MACX MCR-UI-UI-NC - Input signal conditioner



2811446

<https://www.phoenixcontact.com/us/products/2811446>

Block diagram



# MACX MCR-UI-UI-NC - Input signal conditioner



2811446

<https://www.phoenixcontact.com/us/products/2811446>

## Approvals

To download certificates, visit the product detail page: <https://www.phoenixcontact.com/us/products/2811446>

### DNV

Approval ID: TAA000020C



### UL Listed

Approval ID: E330267



### cUL Listed

Approval ID: E330267

### Functional Safety

Approval ID: BVS Pb 01/10



### EAC Ex

Approval ID: TP012 103.01 00078



### IECEX

Approval ID: IECEX BVS 10.0044X



### CCC

Approval ID: 2021122304114077



### cUL Listed

Approval ID: E199827



### UL Listed

Approval ID: FILE E 199827



### ATEX

Approval ID: BVS 10 ATEX E059 X

### INMETRO

Approval ID: DNV 21.0063X

# MACX MCR-UI-UI-NC - Input signal conditioner



2811446

<https://www.phoenixcontact.com/us/products/2811446>

## Classifications

### ECLASS

|             |          |
|-------------|----------|
| ECLASS-13.0 | 27210120 |
| ECLASS-15.0 | 27210120 |

### ETIM

|           |          |
|-----------|----------|
| ETIM 10.0 | EC002653 |
|-----------|----------|

### UNSPSC

|             |          |
|-------------|----------|
| UNSPSC 21.0 | 39121000 |
|-------------|----------|

2811446

<https://www.phoenixcontact.com/us/products/2811446>

## Environmental product compliance

### EU RoHS

|   |                    |
|---|--------------------|
| Fulfills EU RoHS substance requirements | Yes                |
| Exemption                               | 6(c), 7(a), 7(c)-I |

### China RoHS

|  |   |
|--|---|
| Environment friendly use period (EFUP) | EFUP-50   |
|  | An article-related China RoHS declaration table can be found in the download area for the respective article under "Manufacturer declaration". For all articles with EFUP-E, no China RoHS declaration table issued and required. |

### EU REACH SVHC

|                                     |  |
|-------------------------------------|--|
| REACH candidate substance (CAS No.) | Lead(CAS: 7439-92-1)   |
|                                     | 2,2',6,6'-tetrabromo-4,4'-isopropylidenediphenol(CAS: 79-94-7) |
| SCIP                                | ff23c732-d8ee-457c-9118-b5b9a55ba528                           |

Phoenix Contact 2026 © - all rights reserved  
<https://www.phoenixcontact.com>

Phoenix Contact USA  
586 Fulling Mill Road  
Middletown, PA 17057, United States  
(+717) 944-1300  
[info@phoenixcon.com](mailto:info@phoenixcon.com)