

IB IL TEMP 4/8 RTD-PAC - Temperature module



2863915

<https://www.phoenixcontact.com/us/products/2863915>

Please be informed that the data shown in this PDF document is generated from our online catalog. Please find the complete data in the user documentation. Our general terms of use for downloads are valid.



Inline analog input terminal, complete with accessories (connector and marking field), 8 channels, RTD (resistance temperature detector), 2-, 3-conductor connection technology

Product description

The terminal is designed for use within an Inline station. This terminal provides an 8-channel input module for resistance temperature detectors.

Your advantages

- Pt, Ni, Cu, KTY sensor types according to DIN and SAMA
- 8 inputs for resistive temperature sensors and linear resistors up to 20 k Ω
- Connection of sensors in 2- and 3-conductor technology
- Communication either via process data or parameter channel (PCP)
- The channels are parameterized independently of one another via the bus system
- Robust inputs ideal for use in harsh industrial environments with electromagnetic interference
- Measured values can be represented in three different formats
- Temperature and resistance measurement in the millisecond range
- Diagnostic and status indicators

Commercial data

Item number	2863915
Packing unit	1 pc
Minimum order quantity	1 pc
Sales key	DR01
Product key	DRI143
GTIN	4017918955410
Weight per piece (including packing)	252 g
Weight per piece (excluding packing)	190 g
Customs tariff number	85389099
Country of origin	DE

IB IL TEMP 4/8 RTD-PAC - Temperature module




2863915

<https://www.phoenixcontact.com/us/products/2863915>

Technical data

Dimensions

Dimensional drawing	
Width	48.8 mm
Height	136.8 mm
Depth	71.5 mm

Notes

Note on application

Note on application	Only for industrial use
---------------------	-------------------------

Material specifications

Color (Housing)	green (RAL 6021)
-----------------	------------------

Interfaces

Inline local bus

Connection method	Inline data jumper
Transmission speed	500 kbps
Transmission physics	Copper

System properties

Programming data (LocalbusSlave)

Length code (hex)	05
ID code (dec.)	223
Length code (dec)	05
Process data channel	80 bit
Input address area	10 Byte
Output address area	10 Byte
Parameter channel (PCP)	2 Byte
Register length (bus)	96 bit

Fieldbus data telegram (PROFIBUS)

Required parameter data	31 Byte
Required configuration data	5 Byte

Input data

IB IL TEMP 4/8 RTD-PAC - Temperature module



2863915

<https://www.phoenixcontact.com/us/products/2863915>

Analog:

Input name	Analog RTD inputs
Description of the input	Input for resistive temperature sensors
Number of inputs	8
Connection method	Spring-cage connection
Connection technology	2, 3-conductor
A/D conversion time	max. 10 μ s
Sensor types (RTD) that can be used	Pt, Ni, KTY, Cu sensors, linear resistors
Tolerance, relative	typ. 0.06 % (Pt 100 with 3-wire connection) max. 0.25 % (Pt 100 with 3-wire connection) see tables for tolerance values
Tolerance, absolute	typ. \pm 0.5 K (Pt 100 with 3-wire connection) see tables for tolerance values
Data formats	IB IL, IB ST, S7 compatible
Measuring principle	Successive approximation
Measured value representation	16 bits (15 bits + sign bit)
Linear resistance measuring range	0 Ω ... 400 Ω 0 Ω ... 20 k Ω
Process data update	6 ms (Up to 230 ms possible depending on operating mode)

Product properties

Product type	I/O component
Product family	Inline
Type	modular
Scope of supply	including Inline connectors and marking fields
Operating mode	Process data mode with 5 words/1 word PCP

Insulation characteristics

Overvoltage category	II (IEC 60664-1, EN 60664-1)
Pollution degree	2 (IEC 60664-1, EN 60664-1)

Electrical properties

Maximum power dissipation for nominal condition	1.4 W
---	-------

Potentials: Communications power (U_L)

Supply voltage	7.5 V DC (via voltage jumper)
Current draw	max. 100 mA typ. 75 mA

Potentials: Supply of analog modules (U_{ANA})

Supply voltage	24 V DC (via voltage jumper)
Supply voltage range	19.2 V DC ... 30 V DC (including all tolerances, including ripple)
Current draw	max. 55 mA typ. 28 mA

IB IL TEMP 4/8 RTD-PAC - Temperature module



2863915

<https://www.phoenixcontact.com/us/products/2863915>

Electrical isolation/isolation of the voltage ranges

Test voltage: 7.5 V supply (bus logic)/±15.5 V, ±5 V analog supply (analog I/O)	500 V AC, 50 Hz, 1 min
Test voltage: 7.5 V supply (bus logic)/functional ground	500 V AC, 50 Hz, 1 min
Test voltage: ±15.5 V, ±5 V analog supply (analog I/O)/functional ground	500 V AC, 50 Hz, 1 min

Connection data

Connection technology

Connection name	Inline connector
-----------------	------------------

Inline connector

Connection method	Spring-cage connection
Conductor cross-section, rigid	0.08 mm ² ... 1.5 mm ²
Conductor cross-section, flexible	0.08 mm ² ... 1.5 mm ²
Conductor cross-section AWG	28 ... 16
Stripping length	8 mm

Environmental and real-life conditions

Ambient conditions

Ambient temperature (operation)	-25 °C ... 55 °C
Degree of protection	IP20
Air pressure (operation)	70 kPa ... 106 kPa (up to 3000 m above sea level)
Air pressure (storage/transport)	70 kPa ... 106 kPa (up to 3000 m above sea level)
Ambient temperature (storage/transport)	-25 °C ... 85 °C
Permissible humidity (operation)	10 % ... 95 % (non-condensing)
Permissible humidity (storage/transport)	10 % ... 95 % (non-condensing)

Mechanical test

Vibration resistance in accordance with EN 60068-2-6/IEC 60068-2-6	5g
Shock in accordance with EN 60068-2-27/IEC 60068-2-27	25g

Standards and regulations

Protection class	III (IEC 61140, EN 61140, VDE 0140-1)
------------------	---------------------------------------

Mounting

Mounting type	DIN rail mounting
---------------	-------------------

IB IL TEMP 4/8 RTD-PAC - Temperature module



2863915


<https://www.phoenixcontact.com/us/products/2863915>

Drawings

Dimensional drawing



Connection diagram



IB IL TEMP 4/8 RTD-PAC - Temperature module



2863915

<https://www.phoenixcontact.com/us/products/2863915>

Approvals

To download certificates, visit the product detail page: <https://www.phoenixcontact.com/us/products/2863915>



DNV GL

Approval ID: TAA00000BN



LR

Approval ID: LR23398855TA



BV

Approval ID: 21595/C1 BV

BSH

Approval ID: 658a



RINA

Approval ID: ELE121121XG

ABS

Approval ID: 22-2226444-PDA



cULus Listed

Approval ID: E140324

IB IL TEMP 4/8 RTD-PAC - Temperature module



2863915

<https://www.phoenixcontact.com/us/products/2863915>

Classifications

ECLASS

ECLASS-13.0	27242601
ECLASS-15.0	27242601

ETIM

ETIM 10.0	EC001596
-----------	----------

UNSPSC

UNSPSC 21.0	32151600
-------------	----------

2863915

<https://www.phoenixcontact.com/us/products/2863915>

Environmental product compliance

EU RoHS

Fulfills EU RoHS substance requirements	Yes
Exemption	7(a), 7(c)-I

China RoHS

Environment friendly use period (EFUP)	EFUP-50
	An article-related China RoHS declaration table can be found in the download area for the respective article under "Manufacturer declaration". For all articles with EFUP-E, no China RoHS declaration table issued and required.

EU REACH SVHC

REACH candidate substance (CAS No.)	Lead(CAS: 7439-92-1)
SCIP	dae4fed0-e9ce-45d3-91ec-9dd18731cb15

EF3.1 Climate Change

CO2e kg	18.977 kg CO2e
---------	----------------

Phoenix Contact 2026 © - all rights reserved
<https://www.phoenixcontact.com>

Phoenix Contact USA
586 Fulling Mill Road
Middletown, PA 17057, United States
(+717) 944-1300
info@phoenixcon.com