

# MINI MCR-SL-UI-UI-NC - Input signal conditioner



2864150

<https://www.phoenixcontact.com/us/products/2864150>

Please be informed that the data shown in this PDF document is generated from our online catalog. Please find the complete data in the user documentation. Our general terms of use for downloads are valid.



3-way signal conditioner for the electrical isolation of analog signals, I/O can be configured via DIP switches, with screw connection, standard configuration

## Your advantages

- Power supply possible via the foot element (TBUS)
- Up to 36 signal combinations can be configured using DIP switches
- Low power consumption
- Highly-compact isolating amplifier for electrical isolation, conversion, amplification, and filtering of standard analog signals
- 3-way isolation

## Commercial data

|                                      |               |
|--------------------------------------|---------------|
| Item number                          | 2864150       |
| Packing unit                         | 1 pc          |
| Minimum order quantity               | 1 pc          |
| Sales key                            | C403          |
| Product key                          | DK1131        |
| GTIN                                 | 4017918956615 |
| Weight per piece (including packing) | 87.7 g        |
| Weight per piece (excluding packing) | 77 g          |
| Customs tariff number                | 85437090      |
| Country of origin                    | DE            |

# MINI MCR-SL-UI-UI-NC - Input signal conditioner



2864150

<https://www.phoenixcontact.com/us/products/2864150>

## Technical data

### Notes

#### Utilization restriction

|          |   |
|----------|---|
| EMC note | EMC: class A product, see manufacturer's declaration in the download area |
|----------|---|

### Product properties

|                 |                          |
|-----------------|--------------------------|
| Product type    | Input signal conditioner |
| Product family  | MINI Analog              |
| No. of channels | 1                        |
| Configuration   | DIP switches             |

### System properties

#### Functionality

|               |              |
|---------------|--------------|
| Configuration | DIP switches |
|---------------|--------------|

### Electrical properties

|   |  |
|---|--|
| Electrical isolation                            | 3-way isolation  |
| Electrical isolation between input and output   | yes  |
| Limit frequency (3 dB)                          | ~ 100 Hz   |
| Maximum power dissipation for nominal condition | 58 mW<br>184.3 mW  |
| Protective circuit                              | Transient protection                                     |
| Step response (10-90%)                          | ~ 3.2 ms   |
| Maximum temperature coefficient                 | < 0.01 %/K   |
| Temperature coefficient, typical                | < 0.002 %/K  |
| Maximum transmission error                      | ≤ 0.1 % (of final value)<br>< 0.4 % (Without adjustment) |

#### Electrical isolation

|                      |    |
|----------------------|----|
| Overvoltage category | II |
| Pollution degree     | 2  |

#### Electrical isolation Input/output/power supply IEC/EN 61010

|                          |                         |
|--------------------------|-------------------------|
| Standards/regulations    | IEC/EN 61010            |
| Rated insulation voltage | 50 V AC/DC              |
| Test voltage             | 1.5 kV AC (50 Hz, 60 s) |
| Insulation               | Basic insulation        |

#### Supply

|                        |         |
|------------------------|---------|
| Nominal supply voltage | 24 V DC |
|------------------------|---------|

# MINI MCR-SL-UI-UI-NC - Input signal conditioner



2864150

<https://www.phoenixcontact.com/us/products/2864150>

|                              |   |
|------------------------------|---|
| Supply voltage range         | 19.2 V DC ... 30 V DC (The DIN rail connector (ME 6,2 TBUS-2 1,5/5-ST-3,81 GN, item no. 2869728) can be used to bridge the supply voltage. It can be snapped onto a 35 mm DIN rail in accordance with EN 60715) |
| Max. current consumption     | < 19 mA (Current output, at 24 V DC incl. load)   |
|                              | < 9 mA (Voltage output, at 24 V DC incl. load)  |
| Power consumption (I output) | < 450 mW (Current output)   |
| Power consumption (U output) | < 200 mW (Voltage output)   |

## Input data

Signal: Voltage/current

|                                   |                   |
|-----------------------------------|-------------------|
| Number of inputs                  | 1                 |
| Configurable/programmable         | Yes, unconfigured |
| Voltage input signal              | 0 V ... 10 V      |
|                                   | 0 V ... 5 V       |
|                                   | 1 V ... 5 V       |
|                                   | 2 V ... 10 V      |
| Max. voltage input signal         | 30 V              |
| Current input signal              | 0 mA ... 20 mA    |
|                                   | 4 mA ... 20 mA    |
| Max. current input signal         | 50 mA             |
| Input resistance of voltage input | ~ 100 kΩ          |
| Input resistance current input    | ~ 50 Ω            |

## Output data

Signal: Voltage/current

|                                 |                                  |
|---------------------------------|----------------------------------|
| Number of outputs               | 1                                |
| Configurable/programmable       | Yes, unconfigured                |
| Voltage output signal           | 0 V ... 10 V                     |
|                                 | 0 V ... 5 V                      |
|                                 | 1 V ... 5 V                      |
|                                 | 2 V ... 10 V                     |
| Max. voltage output signal      | approx. 12.5 V                   |
| Open-circuit voltage            | approx. 12.5 V                   |
| Current output signal           | 0 mA ... 20 mA                   |
|                                 | 4 mA ... 20 mA                   |
| Max. current output signal      | 28 mA                            |
| Short-circuit current           | approx. 22 mA                    |
| Load/output load voltage output | ≥ 10 kΩ                          |
| Load/output load current output | < 500 Ω (at 20 mA)               |
| Ripple                          | < 20 mV <sub>PP</sub> (at 500 Ω) |
|                                 | < 20 mV <sub>PP</sub> (at 10 kΩ) |

## Connection data

# MINI MCR-SL-UI-UI-NC - Input signal conditioner



2864150

<https://www.phoenixcontact.com/us/products/2864150>

|                                  |   |
|----------------------------------|---|
| Connection method                | Screw connection                            |
| Stripping length                 | 12 mm                                       |
| Screw thread                     | M3  |
| Conductor cross-section rigid    | 0.2 mm <sup>2</sup> ... 2.5 mm <sup>2</sup> |
| Conductor cross-section flexible | 0.2 mm <sup>2</sup> ... 2.5 mm <sup>2</sup> |
| Conductor cross-section AWG      | 26 ... 12                                   |

## Dimensions

|                     |          |
|---------------------|----------|
| Dimensional drawing |          |
| Width               | 6.2 mm   |
| Height              | 93.1 mm  |
| Depth               | 101.2 mm |

## Material specifications

|  |                  |
|--|------------------|
| Color  | green (RAL 6021) |
| Housing material                                       | PBT              |
| Fire protection for rail vehicles (DIN EN 45545-2) R22 | HL 1 - HL 2      |
| Fire protection for rail vehicles (DIN EN 45545-2) R23 | HL 1 - HL 2      |
| Fire protection for rail vehicles (DIN EN 45545-2) R24 | HL 1 - HL 2      |

## Environmental and real-life conditions

### Ambient conditions

|   |                               |
|---|-------------------------------|
| Degree of protection                    | IP20                          |
| Ambient temperature (operation)         | -20 °C ... 65 °C              |
| Ambient temperature (storage/transport) | -40 °C ... 85 °C              |
| Altitude                                | ≤ 2000 m                      |
| Permissible humidity (operation)        | 5 % ... 95 % (non-condensing) |

## Approvals

### CE

|             |              |
|-------------|--------------|
| Certificate | CE-compliant |
|-------------|--------------|

### UL, USA/Canada

|                |                                       |
|----------------|---------------------------------------|
| Identification | UL 508 Recognized                     |
|                | Class I, Div. 2, Groups A, B, C, D T5 |

## EMC data

|                               |                                |
|-------------------------------|--------------------------------|
| Electromagnetic compatibility | Conformance with EMC directive |
|-------------------------------|--------------------------------|

# MINI MCR-SL-UI-UI-NC - Input signal conditioner



2864150

<https://www.phoenixcontact.com/us/products/2864150>

|                |  |
|----------------|--|
| Noise immunity | EN 61000-6-2   |
| Note           | When being exposed to interference, there may be minimal deviations. |

## Noise emission

|                       |              |
|-----------------------|--------------|
| Standards/regulations | EN 61000-6-4 |
|-----------------------|--------------|

## Electrostatic discharge

|                       |              |
|-----------------------|--------------|
| Standards/regulations | EN 61000-4-2 |
|-----------------------|--------------|

## Electrostatic discharge

|          |   |
|----------|---|
| Comments | Safety measures must be taken to prevent electrostatic discharge. |
|----------|---|

## Electromagnetic HF field

|  |                          |
|--|--------------------------|
| Designation  | Electromagnetic RF field |
| Standards/regulations                                  | EN 61000-4-3             |
| Typical deviation from the measuring range final value | 5 %                      |

## Fast transients (burst)

|  |                         |
|--|-------------------------|
| Designation  | Fast transients (burst) |
| Standards/regulations                                  | EN 61000-4-4            |
| Typical deviation from the measuring range final value | 5 %                     |

## Surge current load (surge)

|                       |              |
|-----------------------|--------------|
| Standards/regulations | EN 61000-4-5 |
|-----------------------|--------------|

## Surge current load (surge)

|          |             |
|----------|-------------|
| Comments | Criterion B |
|----------|-------------|

## Conducted interference

|  |                         |
|--|-------------------------|
| Designation  | Conducted interferences |
| Standards/regulations                                  | EN 61000-4-6            |
| Typical deviation from the measuring range final value | 5 %                     |

## Standards and regulations

|                      |                 |
|----------------------|-----------------|
| Electrical isolation | 3-way isolation |
|----------------------|-----------------|

## Mounting

|                   |   |
|-------------------|---|
| Mounting type     | DIN rail mounting   |
| Assembly note     | The DIN rail connector can be used for bridging the supply voltage. It can be snapped onto a 35 mm EN 60715 DIN rail. |
| Mounting position | any   |

# MINI MCR-SL-UI-UI-NC - Input signal conditioner




2864150


<https://www.phoenixcontact.com/us/products/2864150>

## Drawings

Dimensional drawing



Application drawing




# MINI MCR-SL-UI-UI-NC - Input signal conditioner



2864150

<https://www.phoenixcontact.com/us/products/2864150>

Block diagram



# MINI MCR-SL-UI-UI-NC - Input signal conditioner



2864150

<https://www.phoenixcontact.com/us/products/2864150>

## Approvals

To download certificates, visit the product detail page: <https://www.phoenixcontact.com/us/products/2864150>



**cUL Recognized**  
Approval ID: E238705



**UL Recognized**  
Approval ID: E238705

**DNV**

Approval ID: TAA000020N



**cUL Listed**  
Approval ID: E199827



**UL Listed**  
Approval ID: E199827

# MINI MCR-SL-UI-UI-NC - Input signal conditioner



2864150

<https://www.phoenixcontact.com/us/products/2864150>

## Classifications

### ECLASS

|             |          |
|-------------|----------|
| ECLASS-13.0 | 27210120 |
| ECLASS-15.0 | 27210120 |

### ETIM

|           |          |
|-----------|----------|
| ETIM 10.0 | EC002653 |
|-----------|----------|

### UNSPSC

|             |          |
|-------------|----------|
| UNSPSC 21.0 | 39121000 |
|-------------|----------|

# MINI MCR-SL-UI-UI-NC - Input signal conditioner



2864150

<https://www.phoenixcontact.com/us/products/2864150>

## Environmental product compliance

### EU RoHS

|   |                    |
|---|--------------------|
| Fulfills EU RoHS substance requirements | Yes                |
| Exemption                               | 6(c), 7(a), 7(c)-I |

### China RoHS

|  |   |
|--|---|
| Environment friendly use period (EFUP) | EFUP-50   |
|  | An article-related China RoHS declaration table can be found in the download area for the respective article under "Manufacturer declaration". For all articles with EFUP-E, no China RoHS declaration table issued and required. |

### EU REACH SVHC

|                                     |  |
|-------------------------------------|--|
| REACH candidate substance (CAS No.) | Lead(CAS: 7439-92-1)   |
|                                     | 2,2',6,6'-tetrabromo-4,4'-isopropylidenediphenol(CAS: 79-94-7) |
| SCIP                                | 1a98fd1f-71dd-4573-b9dc-118019669a52                           |

### EF3.1 Climate Change

|         |              |
|---------|--------------|
| CO2e kg | 2.18 kg CO2e |
|---------|--------------|

Phoenix Contact 2026 © - all rights reserved  
<https://www.phoenixcontact.com>

Phoenix Contact USA  
586 Fulling Mill Road  
Middletown, PA 17057, United States  
(+717) 944-1300  
[info@phoenixcon.com](mailto:info@phoenixcon.com)