

MINI MCR-SL-PT100-UI-NC - Temperature measuring transducer



2864273

<https://www.phoenixcontact.com/us/products/2864273>

Please be informed that the data shown in this PDF document is generated from our online catalog. Please find the complete data in the user documentation. Our general terms of use for downloads are valid.



MCR temperature transducer for Pt 100 temperature sensors, configured via DIP switches, with screw connection, not preconfigured

Product description

The narrow, 6.2 mm wide MINI MCR-SL-PT100-UI... is a configurable, 3-way isolated temperature transducer. It is suitable for connecting Pt 100 resistance thermometers in accordance with IEC 60751 in 2-, 3-, and 4-conductor connection technology.

Electrically isolated 0 ... 20 mA, 4 ... 20 mA, 0 ... 10 V, 0 ... 5 V, 1 ... 5 V, 10 ... 0 V, 20 ... 0 mA, or 20 ... 4 mA standard analog signals are available on the output side.

The DIP switches, which can be accessed on the side of the housing, are used to configure the following parameters:

- Connection technology
- Temperature range to be measured
- Output signal
- Type of error evaluation

Power (19.2 V DC to 30 V DC) can either be supplied via the connection terminal blocks of the modules or in conjunction with the DIN rail connector.

Your advantages

- Power supply possible via the foot element (TBUS)
- For 2-, 3-, 4-conductor Pt 100 sensors in accordance with IEC 60751
- Error indication via diagnostic LED and analog signal
- Input and output signals can be configured via DIP switches
- Highly-compact temperature transducer for electrical isolation, conversion, amplification, and filtering of
- 3-way isolation
- Pt 100 signals to create standard signals
- Temperature measuring range of -150°C to +850°C

Commercial data

| | |
|--------------------------------------|---------------|
| Item number | 2864273 |
| Packing unit | 1 pc |
| Minimum order quantity | 1 pc |
| Sales key | C403 |
| Product key | DK1135 |
| GTIN | 4017918956561 |
| Weight per piece (including packing) | 88.85 g |
| Weight per piece (excluding packing) | 99.2 g |

MINI MCR-SL-PT100-UI-NC - Temperature measuring transducer



2864273

<https://www.phoenixcontact.com/us/products/2864273>

| | |
|-----------------------|----------|
| Customs tariff number | 85437090 |
| Country of origin | DE |

MINI MCR-SL-PT100-UI-NC - Temperature measuring transducer



2864273

<https://www.phoenixcontact.com/us/products/2864273>

Technical data

Notes

Utilization restriction

| | |
|----------|---|
| EMC note | EMC: class A product, see manufacturer's declaration in the download area |
|----------|---|

Product properties

| | |
|-----------------|-------------------------|
| Product type | Temperature transmitter |
| Product family | MINI Analog |
| No. of channels | 1 |
| Configuration | DIP switches |

System properties

Functionality

| | |
|---------------|--------------|
| Configuration | DIP switches |
|---------------|--------------|

Electrical properties

| | |
|---|--|
| Electrical isolation | 3-way isolation |
| Electrical isolation between input and output | yes |
| Maximum power dissipation for nominal condition | 235.5 mW |
| Protective circuit | Transient protection |
| Step response (0–99%) | < 160 ms |
| Maximum temperature coefficient | < 0.02 %/K |
| Transmission error in the set measuring range | $((100 \text{ K} / \text{set measurement range [K]}) + 0.1)\%$ |
| Transmission error in the full measuring range | $\leq 0,2 \%$ |

Electrical isolation

| | |
|----------------------|----|
| Overvoltage category | II |
| Pollution degree | 2 |

Electrical isolation Input/output/power supply IEC/EN 61010

| | |
|--------------------------|-------------------------|
| Standards/regulations | IEC/EN 61010 |
| Rated insulation voltage | 50 V AC/DC |
| Test voltage | 1.5 kV AC (50 Hz, 60 s) |
| Insulation | Basic insulation |

Supply

| | |
|--------------------------|---|
| Nominal supply voltage | 24 V DC |
| Supply voltage range | 19.2 V DC ... 30 V DC (The DIN rail connector (ME 6,2 TBUS-2 1,5/5-ST-3,81 GN, item no. 2869728) can be used to bridge the supply voltage. It can be snapped onto a 35 mm DIN rail in accordance with EN 60715) |
| Max. current consumption | < 21 mA (at 24 V DC) |

MINI MCR-SL-PT100-UI-NC - Temperature measuring transducer



2864273

<https://www.phoenixcontact.com/us/products/2864273>

| | |
|-------------------|----------|
| Power consumption | < 500 mW |
|-------------------|----------|

Input data

Signal




| | |
|------------------|---|
| Number of inputs | 1 |
|------------------|---|

Measurement

| | |
|---|-----------------------------------|
| Configurable/programmable | Yes |
| Sensor types (RTD) that can be used | Pt 100 (IEC 60751/EN 60751) |
| Temperature measuring range | min. 50 K |
| Temperature measuring range: Pt 100 | -150 °C ... 850 °C (configurable) |
| Sensor input current | 1 mA (constant) |
| Max. permissible overall conductor resistance | 10 Ω (Per cable) |
| Connection technology | 2-, 3-, 4-conductor |

Output data

Signal: Voltage/current

| | |
|---------------------------------|--|
| Number of outputs | 1 |
| Configurable/programmable | Yes, unconfigured |
| Voltage output signal | 0 V ... 5 V 1 V ... 5 V 0 V ... 10 V 10 V ... 0 V |
| Max. voltage output signal | ≈  V |
| Open-circuit voltage | ≈  V |
| Current output signal | 0 mA ... 20 mA 4 mA ... 20 mA 20 mA ... 0 mA 20 mA ... 4 mA |
| Max. current output signal | 23 mA |
| Short-circuit current | ≈  mA |
| Load/output load voltage output | ≥ 10 kΩ |
| Load/output load current output | < 500 Ω (at 20 mA) |
| Ripple | < 20 mV _{PP} (at 10 kΩ) < 20 mV _{PP} (at 500 Ω) |

Connection data

| | |
|----------------------------------|---|
| Connection method | Screw connection |
| Stripping length | 12 mm |
| Screw thread | M3 |
| Conductor cross-section rigid | 0.2 mm ² ... 2.5 mm ² |
| Conductor cross-section flexible | 0.2 mm ² ... 2.5 mm ² |

MINI MCR-SL-PT100-UI-NC - Temperature measuring transducer




2864273

<https://www.phoenixcontact.com/us/products/2864273>

| | |
|-----------------------------|-----------|
| Conductor cross-section AWG | 26 ... 12 |
|-----------------------------|-----------|

Dimensions

| | |
|---------------------|--|
| Dimensional drawing |  |
| Width | 6.2 mm |
| Height | 93.1 mm |
| Depth | 101.2 mm |

Material specifications

| | |
|--|------------------|
| Color | green (RAL 6021) |
| Housing material | PBT |
| Fire protection for rail vehicles (DIN EN 45545-2) R22 | HL 1 - HL 2 |
| Fire protection for rail vehicles (DIN EN 45545-2) R23 | HL 1 - HL 2 |
| Fire protection for rail vehicles (DIN EN 45545-2) R24 | HL 1 - HL 2 |

Environmental and real-life conditions

Ambient conditions

| | |
|---|-------------------------------|
| Degree of protection | IP20 |
| Ambient temperature (operation) | -20 °C ... 65 °C |
| Ambient temperature (storage/transport) | -40 °C ... 85 °C |
| Altitude | ≤ 2000 m |
| Permissible humidity (operation) | 5 % ... 95 % (non-condensing) |

Approvals

CE

| | |
|-------------|--------------|
| Certificate | CE-compliant |
|-------------|--------------|

UL, USA/Canada

| | |
|----------------|---------------------------------------|
| Identification | UL 508 Recognized |
| | Class I, Div. 2, Groups A, B, C, D T5 |

EMC data

| | |
|-------------------------------|--|
| Electromagnetic compatibility | Conformance with EMC directive |
| Noise immunity | EN 61000-6-2 |
| Note | When being exposed to interference, there may be minimal deviations. |

Noise emission

MINI MCR-SL-PT100-UI-NC - Temperature measuring transducer



2864273

<https://www.phoenixcontact.com/us/products/2864273>

| | |
|-----------------------|--------------|
| Standards/regulations | EN 61000-6-4 |
|-----------------------|--------------|

Electrostatic discharge

| | |
|-----------------------|--------------|
| Standards/regulations | EN 61000-4-2 |
|-----------------------|--------------|

Electrostatic discharge

| | |
|----------|---|
| Comments | Safety measures must be taken to prevent electrostatic discharge. |
|----------|---|

Electromagnetic HF field

| | |
|--|--------------------------|
| Designation | Electromagnetic RF field |
| Standards/regulations | EN 61000-4-3 |
| Typical deviation from the measuring range final value | 10 % |

Fast transients (burst)

| | |
|--|-------------------------|
| Designation | Fast transients (burst) |
| Standards/regulations | EN 61000-4-4 |
| Typical deviation from the measuring range final value | 10 % |

Surge current load (surge)

| | |
|-----------------------|--------------|
| Standards/regulations | EN 61000-4-5 |
|-----------------------|--------------|

Surge current load (surge)

| | |
|----------|-------------|
| Comments | Criterion B |
|----------|-------------|

Conducted interference

| | |
|--|-------------------------|
| Designation | Conducted interferences |
| Standards/regulations | EN 61000-4-6 |
| Typical deviation from the measuring range final value | 10 % |

Standards and regulations

| | |
|----------------------|-----------------|
| Electrical isolation | 3-way isolation |
|----------------------|-----------------|

Mounting


| | |
|-------------------|---|
| Mounting type | DIN rail mounting |
| Assembly note | The DIN rail connector can be used for bridging the supply voltage. It can be snapped onto a 35 mm EN 60715 DIN rail. |
| Mounting position | any |

MINI MCR-SL-PT100-UI-NC - Temperature measuring transducer

2864273

<https://www.phoenixcontact.com/us/products/2864273>

Drawings




MINI MCR-SL-PT100-UI-NC - Temperature measuring transducer



2864273

<https://www.phoenixcontact.com/us/products/2864273>

Block diagram



MINI MCR-SL-PT100-UI-NC - Temperature measuring transducer



2864273

<https://www.phoenixcontact.com/us/products/2864273>

Approvals

To download certificates, visit the product detail page: <https://www.phoenixcontact.com/us/products/2864273>



cUL Recognized
Approval ID: E238705



UL Recognized
Approval ID: E238705



cUL Listed
Approval ID: E199827



UL Listed
Approval ID: E199827

MINI MCR-SL-PT100-UI-NC - Temperature measuring transducer



2864273

<https://www.phoenixcontact.com/us/products/2864273>

Classifications

ECLASS

| | |
|-------------|----------|
| ECLASS-15.0 | 27210129 |
| ECLASS-13.0 | 27210129 |

ETIM

| | |
|-----------|----------|
| ETIM 10.0 | EC002919 |
|-----------|----------|

UNSPSC

| | |
|-------------|----------|
| UNSPSC 21.0 | 41112100 |
|-------------|----------|

MINI MCR-SL-PT100-UI-NC - Temperature measuring transducer



2864273

<https://www.phoenixcontact.com/us/products/2864273>

Environmental product compliance

EU RoHS

| | |
|---|--------------|
| Fulfills EU RoHS substance requirements | Yes |
| Exemption | 7(a), 7(c)-I |

China RoHS

| | |
|--|---|
| Environment friendly use period (EFUP) | EFUP-50 |
| | An article-related China RoHS declaration table can be found in the download area for the respective article under "Manufacturer declaration". For all articles with EFUP-E, no China RoHS declaration table issued and required. |

EU REACH SVHC

| | |
|-------------------------------------|--------------------------------------|
| REACH candidate substance (CAS No.) | Lead(CAS: 7439-92-1) |
| SCIP | 6a31acdc-1425-418f-9b19-c945668e11e5 |

EF3.1 Climate Change

| | |
|---------|---------------|
| CO2e kg | 5.595 kg CO2e |
|---------|---------------|

Phoenix Contact 2026 © - all rights reserved
<https://www.phoenixcontact.com>

Phoenix Contact USA
586 Fulling Mill Road
Middletown, PA 17057, United States
(+717) 944-1300
info@phoenixcon.com