

MCR-FL-HT-TS-I-EX - Head-mounted transducer



2864545

<https://www.phoenixcontact.com/us/products/2864545>

Please be informed that the data shown in this PDF document is generated from our online catalog. Please find the complete data in the user documentation. Our general terms of use for downloads are valid.



Measurement and control temperature transducer, for resistance thermometers, thermocouples, resistance-type sensors, and voltage sensors. For Pt 100 resistance temperature detectors. Replacement part: 2908742 FA MCR-HT-TS-I-OLP-PT.

Your advantages

- Input for resistance thermometers, thermocouples, and linear mV signals, Ex ia IIC
- Configuration via software
- Can be installed in zone 1
- 1-channel
- Loop-powered
- Output: 4 mA ... 20 mA/20 mA ... 4 mA
- HART-compatible
- 2-way electrical isolation

Commercial data

Item number	2864545
Packing unit	1 pc
Note	Made to order (non-returnable)
Sales key	C430
Product key	DK1XXX
GTIN	4017918893200
Weight per piece (including packing)	83.6 g
Weight per piece (excluding packing)	78.2 g
Customs tariff number	85437090
Country of origin	DE

Technical data

Product properties

Product type	Temperature transmitter
Application	Temperature
Configuration	With HART protocol

System properties

Functionality

Configuration	With HART protocol
---------------	--------------------

Electrical properties

Switch-on delay	6 s
Line monitoring	NE 43
Test voltage input/output	2 kV AC (50 Hz, 60 s)
Step response (10-90%)	< 2 s
Transmission error voltage sensor	±20 µV (-10 mV ... 75 mV)
Transmission error thermocouples	typ. 0.5 K (K, J, T, E, L, U), 1.0 K (N, C, D), 2.0 K (S, B, R)
Transmission error resistance-type sensor	±0.1 Ω (10 ... 400 Ω), ±1.5 Ω (10 ... 2000 Ω)
Transmission error resistance thermometer	0.2 K (Pt 100, Ni 100), 0.5 K (Pt 500, Ni 500), 0.3 K (Pt 1000, Ni 1000)

Supply

Designation	Loop-powered
Supply voltage range	12 V DC ... 30 V DC
Max. current consumption	< 3.5 mA

Input data

Signal

Number of inputs	1
Input signal	Temperature

Measurement

Configurable/programmable	Yes, programmable
Sensor types (RTD) that can be used	Pt, Ni (100, 500, 1000); min. measurement range 10 K
Sensor types that can be used (TC)	B, C, D, E, J, K, L, N, R, S, T, U; min. measurement range 50 K/500 K
Temperature measuring range: Pt 100	-200 °C ... 850 °C (freely adjustable)
Temperature measuring range: Pt 500	-200 °C ... 250 °C (freely adjustable)
Temperature measuring range: Pt 1000	-200 °C ... 250 °C (freely adjustable)
Temperature measuring range: Ni 100	-60 °C ... 250 °C (freely adjustable)
Temperature measuring range: Ni 500	-60 °C ... 150 °C (freely adjustable)
Temperature measuring range: Ni 1000	-60 °C ... 150 °C (freely adjustable)
Temperature measuring range: Thermoelement Typ B	50 °C ... 1820 °C (freely adjustable)

MCR-FL-HT-TS-I-EX - Head-mounted transducer



2864545

<https://www.phoenixcontact.com/us/products/2864545>

Temperature measuring range: Thermoelement Typ C	0 °C ... 2320 °C (freely adjustable)
Temperature measuring range: Thermoelement Typ D	0 °C ... 2495 °C (freely adjustable)
Temperature measuring range: Thermoelement Typ E	-270 °C ... 1000 °C (freely adjustable)
Temperature measuring range: Thermoelement Typ J	-210 °C ... 1200 °C (freely adjustable)
Temperature measuring range: Thermoelement Typ K	-270 °C ... 1372 °C (freely adjustable)
Temperature measuring range: Thermoelement Typ L	-200 °C ... 900 °C (freely adjustable)
Temperature measuring range: Thermoelement Typ N	-270 °C ... 1300 °C (freely adjustable)
Temperature measuring range: Thermoelement Typ R	-50 °C ... 1768 °C (freely adjustable)
Temperature measuring range: Thermoelement Typ S	-50 °C ... 1768 °C (freely adjustable)
Temperature measuring range: Thermoelement Typ T	-270 °C ... 400 °C (freely adjustable)
Temperature measuring range: Thermoelement Typ U	-200 °C ... 600 °C (freely adjustable)
Connection technology	2-, 3-, 4-conductor
Linear resistance measuring range	10 Ω ... 400 Ω (min. measurement range 10 Ω)
	10 Ω ... 2000 Ω (min. measurement range 100 Ω)
Linear mV signal range	-10 mV ... 75 mV (min. measurement range 5 mV)

Output data

Switching:

Configurable/programmable	no
---------------------------	----

Signal

Number of outputs	1
Configurable/programmable	Yes, programmable
Current output signal	4 mA ... 20 mA
	20 mA ... 4 mA
Max. current output signal	≤ 23 mA
Output current with short-circuit	≤ 3.6 mA or ≥ 21 mA (adjustable, not for thermocouples)
Output current with wire break	≤ 3.6 mA or ≥ 21 mA (adjustable)
Output current range with overrange/underrange	3.8 mA ... 20.5 mA (linear increase/decrease)
Load/output load current output	≤ 630 Ω (At U _V = 24 V; U _{supply} - 10 V / 0.023 A)

Connection data

Connection method	Screw connection
Stripping length	8 mm
Screw thread	M3
Conductor cross-section rigid	0.2 mm ² ... 1.75 mm ²
Conductor cross-section flexible	0.2 mm ² ... 1.75 mm ²
Conductor cross-section AWG	24 ... 15
Tightening torque	0.5 Nm ... 0.6 Nm

Ex data

Safety data

Max. voltage U _i	30 V
Max. current I _i	100 mA

MCR-FL-HT-TS-I-EX - Head-mounted transducer



2864545

<https://www.phoenixcontact.com/us/products/2864545>

Max. power P_i	750 mW
Max. output voltage U_o	5 V DC
Max. output current I_o	5.4 mA
Max. output power P_o	6.6 mW
Max. ambient temperature	Category 1: T4 = 60°C, T5 = 50°C, T6 = 40°C Category 2: T4 = 85°C, T5 = 70°C, T6 = 55°C
Safety-related maximum voltage U_m	250 V
IIA: Max. external inductivity L_o / Max. external capacitance C_o	100 mH / 9.9 μ F
IIB: Max. external inductivity L_o / Max. external capacitance C_o	100 mH / 9.9 μ F
IIC: Max. external inductivity L_o / Max. external capacitance C_o	100 mH / 2 μ F

Material specifications

Color	green (RAL 6021)
Flammability rating according to UL 94	V0
Housing material	PC

Environmental and real-life conditions

Ambient conditions

Degree of protection	IP00 IP66 (Installed in the connection head)
Ambient temperature (operation)	-40 °C ... 55 °C

Approvals

CE

Certificate	CE-compliant
-------------	--------------

ATEX

Identification	Ⓜ II 1 G bzw. II 2 G Ex ia IIC T6/T5/T4
----------------	---

UL, USA/Canada

Identification	cULus
----------------	-------

Safety Integrity Level (SIL, IEC 61508)

Identification	2
----------------	---

Standards and regulations

Standards

Standards/regulations	NAMUR recommendation NE 21
-----------------------	----------------------------

Mounting

Assembly note	Installation in connection head according to DIN 43729 form B
Mounting position	Connecting head in acc. with DIN 43729 form B


MCR-FL-HT-TS-I-EX - Head-mounted transducer



2864545

<https://www.phoenixcontact.com/us/products/2864545>

Drawings



Dimensional drawing



MCR-FL-HT-TS-I-EX - Head-mounted transducer

2864545

<https://www.phoenixcontact.com/us/products/2864545>



Connection diagram




MCR-FL-HT-TS-I-EX - Head-mounted transducer

2864545

<https://www.phoenixcontact.com/us/products/2864545>

Connection diagram




MCR-FL-HT-TS-I-EX - Head-mounted transducer



2864545

<https://www.phoenixcontact.com/us/products/2864545>

Block diagram



Block diagram MCR-FL-HT-TS-I-EX

MCR-FL-HT-TS-I-EX - Head-mounted transducer



2864545

<https://www.phoenixcontact.com/us/products/2864545>

Classifications

ETIM

ETIM 9.0

EC002919

MCR-FL-HT-TS-I-EX - Head-mounted transducer



2864545

<https://www.phoenixcontact.com/us/products/2864545>

Environmental product compliance

EU RoHS

Fulfills EU RoHS substance requirements	Yes, No exemptions
---	--------------------

China RoHS

Environment friendly use period (EFUP)	EFUP-E
	No hazardous substances above the limits

EU REACH SVHC

REACH candidate substance (CAS No.)	No substance above 0.1 wt%
-------------------------------------	----------------------------

Phoenix Contact 2026 © - all rights reserved
<https://www.phoenixcontact.com>

Phoenix Contact USA
586 Fulling Mill Road
Middletown, PA 17057, United States
(+717) 944-1300
info@phoenixcon.com