

# UM-MSTB/8-A-IN/SC013 - Active module



2900765

<https://www.phoenixcontact.com/us/products/2900765>

Please be informed that the data shown in this PDF document is generated from our online catalog. Please find the complete data in the user documentation. Our general terms of use for downloads are valid.



Interface module for 8 analog inputs; can be set using jumpers for each channel if active or passive sensors are connected; active current limitation for each channel in case of a short-circuit, pluggable screw terminal blocks

## Commercial data

Item number	2900765
Packing unit	1 pc
Minimum order quantity	1 pc
Product key	DK2A88
GTIN	4046356530149
Weight per piece (including packing)	367 g
Weight per piece (excluding packing)	367 g
Country of origin	DE

## Technical data

### Notes

Notes on operation	For proper use, the specifications of the installation directive (see Downloads) must be observed. For applications or use with third-party products, the specifications, and the safety and warning instructions of the respective third-party manufacturer must also be met.
--------------------	--

### Product properties

Product type	Relay Module
Insulation characteristics: Air clearances and creepage distances	
Overvoltage category	II
Pollution degree	2

### Electrical properties

Air clearances and creepage distances	
Rated insulation voltage	50 V
Rated surge voltage	0.5 kV (Basic insulation)

### Input data

Nominal input voltage $U_N$	24 V DC
Input voltage range in reference to $U_N$	0.8 ... 1.1
Typical input current at $U_N$	260 mA

### Connection data

COMBICON MSTB	
Connection method	Screw connection
PCB connection	
Connection method	Screw connection

### Signaling

Status display present	no
------------------------	----

### Dimensions

Width	111 mm
Height	126 mm
Depth	78 mm

### Material specifications

Color	green (RAL 6021)
Housing insulation material	PVC

2900765

<https://www.phoenixcontact.com/us/products/2900765>

## Environmental and real-life conditions

### Ambient conditions

Ambient temperature (operation)	-20 °C ... 50 °C
Ambient temperature (storage/transport)	-20 °C ... 50 °C

## Standards and regulations

### Air clearances and creepage distances

Standards/regulations	EN 50178
-----------------------	----------

## Mounting

Mounting type	DIN rail mounting
Mounting position	any

2900765

<https://www.phoenixcontact.com/us/products/2900765>

## Environmental product compliance

### China RoHS

Environment friendly use period (EFUP)	EFUP-50
	An article-related China RoHS declaration table can be found in the download area for the respective article under "Manufacturer declaration". For all articles with EFUP-E, no China RoHS declaration table issued and required.

### EU REACH SVHC

REACH candidate substance (CAS No.)	No substance above 0.1 wt%
-------------------------------------	----------------------------

Phoenix Contact 2026 © - all rights reserved  
<https://www.phoenixcontact.com>

Phoenix Contact USA  
586 Fulling Mill Road  
Middletown, PA 17057, United States  
(+717) 944-1300  
[info@phoenixcon.com](mailto:info@phoenixcon.com)