

TTC-6-MOV-C-60DC-UT-I - Surge protection device



2906839

<https://www.phoenixcontact.com/us/products/2906839>

Please be informed that the data shown in this PDF document is generated from our online catalog. Please find the complete data in the user documentation. Our general terms of use for downloads are valid.



Medium surge protection with integrated status indicator for one signal wire with grounded reference potential. Can be used in safety-related circuits up to SIL 3.

Your advantages

- Space-saving and cost-saving with a narrow overall width of just 6 mm
- Continuous monitoring of protective devices, plus mechanical status indicator with optional remote signaling
- Finding the right product for all possible requirements in MCR applications is easy, thanks to the complete range of products with customized features

Commercial data

| | |
|--------------------------------------|---------------|
| Item number | 2906839 |
| Packing unit | 1 pc |
| Minimum order quantity | 1 pc |
| Sales key | CL23 |
| Product key | CL2264 |
| GTIN | 4055626136950 |
| Weight per piece (including packing) | 30.5 g |
| Weight per piece (excluding packing) | 25.26 g |
| Customs tariff number | 85363010 |
| Country of origin | DE |

TTC-6-MOV-C-60DC-UT-I - Surge protection device



2906839

<https://www.phoenixcontact.com/us/products/2906839>

Technical data

Product properties

| | |
|--------------------------------|-------------------------------------|
| Product type | Surge protection for MCR technology |
| Product family | TERMITRAB complete |
| IEC test classification | C1 |
| | C2 |
| | C3 |
| Type | DIN rail module, one-piece |
| Surge protection fault message | optical |

Insulation characteristics

| | |
|----------------------|-----|
| Overvoltage category | III |
| Pollution degree | 2 |


Electrical properties

| | |
|-----------------------|---------|
| Nominal voltage U_N | 60 V DC |
|-----------------------|---------|

Connection data

| | |
|----------------------------------|---|
| Connection method | Screw connection |
| Screw thread | M3 |
| Tightening torque | 0.5 Nm ... 0.6 Nm |
| Conductor cross-section flexible | 0.2 mm ² ... 2.5 mm ² |
| Conductor cross-section rigid | 0.2 mm ² ... 4 mm ² |
| Conductor cross-section AWG | 24 ... 12 |

Dimensions

| | |
|---------------------|--|
| Dimensional drawing |  |
| Width | 6.2 mm |
| Height | 92 mm |
| Depth | 69.5 mm (incl. DIN rail 7.5 mm) |

Material specifications

| | |
|--|-----------------|
| Color | gray (RAL 7042) |
| Flammability rating according to UL 94 | V-0 |
| Insulating material | PBT |
| Housing material | PBT |

Mechanical properties

Mechanical data

TTC-6-MOV-C-60DC-UT-I - Surge protection device



2906839

<https://www.phoenixcontact.com/us/products/2906839>

| | |
|-----------------|-----|
| Open side panel | Yes |
|-----------------|-----|

Protective circuit

| | |
|--|---|
| Direction of action | Line-Earth Ground |
| Nominal voltage U_N | 60 V DC |
| Maximum continuous operating voltage U_C | 75 V DC 53 V AC |
| Rated current | 10 A (60 °C) |
| Operating effective current I_C at U_C | $\leq 100 \mu\text{A}$ |
| Protective conductor current I_{PE} | $\leq 100 \mu\text{A}$ |
| Nominal discharge current I_n (8/20) μs (line-ground) | 2 kA |
| Voltage protection level U_p (line-earth) | $\leq 200 \text{ V}$ (C1 - 600 A) $\leq 270 \text{ V}$ (C2 - 4 kV) $\leq 190 \text{ V}$ (C3 - 25 A) $\leq 200 \text{ V}$ (C3 - 35 A) |
| Response time t_A (line-earth) | $\leq 25 \text{ ns}$ |
| Input attenuation aE, asym. | typ. 0.3 dB ($\leq 200 \text{ kHz} / 150 \Omega$) |
| Cut-off frequency f_g (3 dB), asym. (PE) in 150 Ω system | typ. 650 kHz |
| Capacity (Core-Earth) | 5 nF |
| Resistance per path | $\leq 100 \text{ m}\Omega$ |
| Surge protection fault message | optical |
| Impulse durability (line-earth) | C1 - 600 A C2 - 2 kA C3 - 35 A |

Environmental and real-life conditions

Ambient conditions

| | |
|---|------------------------------|
| Degree of protection | IP20 (with end cover) |
| Ambient temperature (operation) | -40 °C ... 85 °C |
| Ambient temperature (storage/transport) | -40 °C ... 85 °C |
| Altitude | $\leq 4000 \text{ m}$ (amsl) |
| Permissible humidity (operation) | 5 % ... 95 % |

Standards and regulations

| | |
|--------------------------|---|
| Standards/specifications | IEC 61643-21 |
| Note | 2000 + corrigendum 2001 + A1:2008, modified + A2:2012 |

EN 61643-21

| | |
|--------------------------|--------------------------|
| Standards/specifications | EN 61643-21 |
| Note | 2001 + A1:2009 + A2:2013 |

Mounting

| | |
|---------------|-----------------|
| Mounting type | DIN rail: 35 mm |
|---------------|-----------------|

TTC-6-MOV-C-60DC-UT-I - Surge protection device



2906839

<https://www.phoenixcontact.com/us/products/2906839>

Drawings

Dimensional drawing



Schematic diagram

| TTC-6-MOV | | | | | | | | | |
|--|--------------------------|---------------------------|--------------------------|-------|--------------------------|----------------------------|------|--------------------------|-------|
| Category | 1oo1 architecture, HFT=0 | | | | 1oo2 architecture, HFT=1 | | | | |
| | PFD _{AVG} | PFH | Used budget of SIL 2 SIF | | PFD _{AVG} | PFH | CCF | Used budget of SIL 3 SIF | |
| | | | PFD _{AVG} | PFH | | | | PFD _{AVG} | PFH |
| | 1.57x10 ⁻⁵ | 2.80x10 ⁻⁹ 1/h | 0.2 % | 0.3 % | 7.87x10 ⁻⁷ | 1.40x10 ⁻¹⁰ 1/h | 5 % | 0.1 % | 0.1 % |
| | | | | | 1.57x10 ⁻⁶ | 2.80x10 ⁻¹⁰ 1/h | 10 % | 0.2 % | 0.3 % |
| Calculation based on exida report, Phoenix Contact 16/06-072 R024 V2R0 exida Profile 1, FMEDA Analysis 2, T _{proof} : 1 year, MT: 10 years, MTTR: 24 hours, PTC: 99% Used standards IEC/EN 61508, edition 2010 (device specific) IEC/EN 61511, edition 2016 + COR1:2016 + A1:2017 (system specific) | | | | | | | | | |

Functional safety scenarios

TTC-6-MOV-C-60DC-UT-I - Surge protection device



2906839

<https://www.phoenixcontact.com/us/products/2906839>

Diagram



Circuit diagram



TTC-6-MOV-C-60DC-UT-I - Surge protection device



2906839

<https://www.phoenixcontact.com/us/products/2906839>

Classifications

ECLASS

ECLASS-13.0

27171501

ETIM

ETIM 9.0

EC000943

UNSPSC

UNSPSC 21.0

39121600

TTC-6-MOV-C-60DC-UT-I - Surge protection device



2906839

<https://www.phoenixcontact.com/us/products/2906839>

Environmental product compliance

EU RoHS

| | |
|---|--------------------|
| Fulfills EU RoHS substance requirements | Yes, No exemptions |
|---|--------------------|

China RoHS

| | |
|--|--|
| Environment friendly use period (EFUP) | EFUP-E |
| | No hazardous substances above the limits |

EU REACH SVHC

| | |
|-------------------------------------|----------------------------|
| REACH candidate substance (CAS No.) | No substance above 0.1 wt% |
|-------------------------------------|----------------------------|

EF3.1 Climate Change

| | |
|---------|---------------|
| CO2e kg | 0.175 kg CO2e |
|---------|---------------|

Phoenix Contact 2026 © - all rights reserved
<https://www.phoenixcontact.com>

Phoenix Contact USA
586 Fulling Mill Road
Middletown, PA 17057, United States
(+717) 944-1300
info@phoenixcon.com