# TTC-6-TVSD-C-60DC-PT-I - Surge protection device

2906850

https://www.phoenixcontact.com/us/products/2906850

Please be informed that the data shown in this PDF document is generated from our online catalog. Please find the complete data in the user documentation. Our general terms of use for downloads are valid.






Fine surge protection with integrated status indicator for one signal wire with grounded reference potential. Can be used in safety-related circuits up to SIL 3.

## Your advantages

- Space-saving and cost-saving with a narrow overall width of just 6 mm
- Continuous monitoring of protective devices, plus mechanical status indicator with optional remote signaling
- Finding the right product for all possible requirements in MCR applications is easy, thanks to the complete range of products with customized features

## Commercial data

| | |
|---|---|
| Item number | 2906850 |
| Packing unit | 1 pc |
| Minimum order quantity | 1 pc |
| Note | Made to order (non-returnable) |
| Sales key | CL23 |
| Product key | CL2265 |
| GTIN | 4055626137063 |
| Weight per piece (including packing) | 27.7 g |
| Weight per piece (excluding packing) | 27 g |
| Customs tariff number | 85363010 |
| Country of origin | DE |

# Technical data

## Product properties

| | |
|---|---|
| Product type | Surge protection for MCR technology |
| Product family | TERMITRAB complete |
| IEC test classification | C3 |
| Type | DIN rail module, one-piece |
| Surge protection fault message | optical |

### Insulation characteristics

| | |
|---|---|
| Overvoltage category | III |
| Pollution degree | 2 |


## Electrical properties

| | |
|---|---|
| Nominal voltage $U_N$ | 60 V DC |

## Connection data

| | |
|---|---|
| Connection method | Push-in connection |
| Conductor cross-section flexible | 0.2 mm² ... 2.5 mm² |
| Conductor cross-section rigid | 0.2 mm² ... 4 mm² |
| Conductor cross-section AWG | 24 ... 12 |

## Dimensions

| | |
|---|---|
| Dimensional drawing |   |
| Width | 6.2 mm |
| Height | 92 mm |
| Depth | 69.5 mm (incl. DIN rail 7.5 mm) |

## Material specifications

| | |
|---|---|
| Color | gray (RAL 7042) |
| Flammability rating according to UL 94 | V-0 |
| Insulating material | PBT |
| Housing material | PBT |

## Mechanical properties

### Mechanical data

| | |
|---|---|
| Open side panel | Yes |

## Protective circuit

| | |
|---|---|
| Direction of action | Line-Earth Ground |

| | |
|---|---|
| Nominal voltage $U_N$ | 60 V DC |
| Maximum continuous operating voltage $U_C$ | 75 V DC |
| | 53 V AC |
| Rated current | 10 A (60 °C) |
| Operating effective current $I_C$ at $U_C$ | ≤ 5 µA |
| Protective conductor current $I_{PE}$ | ≤ 5 µA |
| Nominal discharge current $I_n$ (8/20) µs (line-ground) | 60 A |
| Voltage protection level $U_p$ (line-earth) | ≤ 110 V (C3 - 12 A) |
| Response time $t_A$ (line-earth) | ≤ 1 ns |
| Input attenuation aE, asym. | typ. 0.3 dB (≤ 1.2 MHz / 150 Ω) |
| Cut-off frequency fg (3 dB), asym. (PE) in 150 Ω system | typ. 4 MHz |
| Capacity (Core-Earth) | 0.6 nF |
| Resistance per path | ≤ 100 mΩ |
| Surge protection fault message | optical |
| Impulse durability (line-earth) | C3 - 12 A |

## Environmental and real-life conditions

Ambient conditions

| | |
|---|---|
| Degree of protection | IP20 (with end cover) |
| Ambient temperature (operation) | -40 °C ... 85 °C |
| Ambient temperature (storage/transport) | -40 °C ... 85 °C |
| Altitude | ≤ 4000 m (amsl) |
| Permissible humidity (operation) | 5 % ... 95 % |

## Standards and regulations

| | |
|---|---|
| Standards/specifications | IEC 61643-21 |
| Note | 2000 + corrigendum 2001 + A1:2008, modified + A2:2012 |

EN 61643-21


| | |
|---|---|
| Standards/specifications | EN 61643-21 |
| Note | 2001 + A1:2009 + A2:2013 |

## Mounting

| | |
|---|---|
| Mounting type | DIN rail: 35 mm |

## Drawings

Dimensional drawing





Schematic diagram


| TTC-6-TVSD | | | | | | | | | |
|---|---|---|---|---|---|---|---|---|---|
| Category | 1oo1 architecture, HFT=0 | | | | 1oo2 architecture, HFT=1 | | | | |
| | $PFD_{AVG}$ | PFH | Used budget of SIL 2 SIF | | $PFD_{AVG}$ | PFH | CCF | Used budget of SIL 3 SIF | |
| | | | $PFD_{AVG}$ | PFH | | | | $PFD_{AVG}$ | PFH |
| | $5.62_{x10^{-7}}$ | $1.00_{x10^{-10}}$ 1/h | 0.0 % | 0.0 % | $2.81_{x10^{-8}}$ | $5.00_{x10^{-12}}$ 1/h | 5 % | 0.0 % | 0.0 % |
| | | | | | $5.62_{x10^{-8}}$ | $1.00_{x10^{-11}}$ 1/h | 10 % | 0.0 % | 0.0 % |
| | Calculation based on exida report, Phoenix Contact 16/06-072 R024 V2R0<br>exida Profile 1, FMEDA Analysis 2, $T_{proof}$: 1 year, MT: 10 years, MTTR: 24 hours, PTC: 99%<br>Used standards<br>IEC/EN 61508, edition 2010 (device specific)<br>IEC/EN 61511, edition 2016 + COR1:2016 + A1:2017 (system specific) | | | | | | | | |

Functional safety scenarios

Diagram




Circuit diagram



## Classifications

### ECLASS

| | |
|---|---|
| ECLASS-13.0 | 27171501 |

### ETIM

| | |
|---|---|
| ETIM 9.0 | EC000943 |

### UNSPSC

| | |
|---|---|
| UNSPSC 21.0 | 39121600 |

## Environmental product compliance

EU RoHS

| | |
|---|---|
| Fulfills EU RoHS substance requirements | Yes |
| Exemption | 7(a), 7(c)-I |

China RoHS

| | |
|---|---|
| Environment friendly use period (EFUP) | EFUP-50 |
| | An article-related China RoHS declaration table can be found in the download area for the respective article under "Manufacturer declaration". For all articles with EFUP-E, no China RoHS declaration table issued and required. |

EU REACH SVHC

| | |
|---|---|
| REACH candidate substance (CAS No.) | Lead(CAS: 7439-92-1) |
| SCIP | 55adbf8c-6157-4f4e-9aa1-7c10d8d4875f |

Phoenix Contact 2026 © - all rights reserved
https://www.phoenixcontact.com

Phoenix Contact USA
586 Fulling Mill Road
Middletown, PA 17057, United States
(+717) 944-1300
info@phoenixcon.com