EMD 12-REL/KSR-G 24/21 - Relay module

2946560

https://www.phoenixcontact.com/us/products/2946560

Please be informed that the data shown in this PDF document is generated from our online catalog. Please find the complete data in the user documentation. Our general terms of use for downloads are valid.

Commercial data

Item number	2946560
Packing unit	10 pc
Minimum order quantity	1 pc
Sales key	C460
Product key	DK61C2
GTIN	4017918082307
Weight per piece (including packing)	51.99 g
Weight per piece (excluding packing)	50.24 g
Customs tariff number	85364190
Country of origin	DE

Technical data

Product properties

Product type	Relay Module

Data management status

Date of last data management	12.09.2025

Electrical properties

Maximum power dissipation for nominal condition	0.5 W

Input data

Coil side

Nominal input voltage U_N	24 V DC
Input voltage range	19.2 V DC ... 26.4 V DC (20 °C)
Drive and function	monostable
Drive (polarity)	polarized

Output data

Switching

Contact switching type	1 changeover contact
Type of switch contact	Single contact
Contact material	AgNi
Limiting continuous current	6 A

Connection data

Connection method	Screw connection

Mounting

Mounting type	DIN rail mounting

Classifications

ECLASS

ECLASS-13.0	27371601
ECLASS-15.0	27371601

ETIM

ETIM 10.0	EC001437

UNSPSC

UNSPSC 21.0	39122300

Environmental product compliance

EU RoHS

Fulfills EU RoHS substance requirements	Yes
Exemption	6(c)

China RoHS

Environment friendly use period (EFUP)	EFUP-50
	An article-related China RoHS declaration table can be found in the download area for the respective article under "Manufacturer declaration". For all articles with EFUP-E, no China RoHS declaration table issued and required.

EU REACH SVHC

REACH candidate substance (CAS No.)	Lead(CAS: 7439-92-1)
SCIP	69b0c652-2be6-48e3-9cf4-a9605f2ef9b1

Phoenix Contact 2026 © - all rights reserved
https://www.phoenixcontact.com

Phoenix Contact USA
586 Fulling Mill Road
Middletown, PA 17057, United States
(+717) 944-1300
info@phoenixcon.com