

UMKS- F48M-VR - Termination board



2970167

<https://www.phoenixcontact.com/us/products/2970167>

Please be informed that the data shown in this PDF document is generated from our online catalog. Please find the complete data in the user documentation. Our general terms of use for downloads are valid.



VARIOFACE module, for IEC 603/DIN 41612 connector, type F, 48-pos., z, b, d components mounted, with male connector, cable housing with latch interlock

Commercial data

Item number	2970167
Packing unit	1 pc
Minimum order quantity	1 pc
Note	Made to order (non-returnable)
Sales key	C422
Product key	DK2187
GTIN	4017918087678
Weight per piece (including packing)	277 g
Weight per piece (excluding packing)	277 g
Customs tariff number	85369010
Country of origin	DE

UMKS- F48M-VR - Termination board



2970167

<https://www.phoenixcontact.com/us/products/2970167>

Technical data

Product properties

Product type	Interface module
Product family	VARIOFACE
Number of positions	48

Insulation characteristics

Insulation	Functional insulation
Overvoltage category	II
Pollution degree	2

Electrical properties

Operating voltage (AC/DC)	250 V AC/DC
Current (per branch)	≤ 4 A
Rated insulation voltage	260 V
Rated surge voltage	2.5 kV

Connection data

Field level

Connection in acc. with standard	IEC / EN
Connection method	Screw connection
Stripping length	8 mm
Screw thread	M3
Conductor cross-section rigid	0.2 mm ² ... 4 mm ²
Conductor cross-section flexible	0.2 mm ² ... 2.5 mm ²
Conductor cross-section AWG	24 ... 12

Controller level

Connection method	IEC 603/DIN 41612 connection
Number of connections	1
Number of positions	48

Signaling

Status display present	no
------------------------	----

Dimensions

Item dimensions

Width	112.3 mm
Height	77 mm
Depth	70.87 mm

Material specifications

Color	green (RAL 6021)
-------	------------------

UMKS- F48M-VR - Termination board



2970167

<https://www.phoenixcontact.com/us/products/2970167>

Housing insulation material	Polyamide PA non-reinforced
-----------------------------	-----------------------------

Environmental and real-life conditions

Ambient conditions

Degree of protection	IP00
Ambient temperature (operation)	-20 °C ... 45 °C
Ambient temperature (storage/transport)	-20 °C ... 70 °C

Standards and regulations

Standards/regulations	EN 60664-1
-----------------------	------------

Mounting

Mounting type	DIN rail mounting
Mounting position	any

Notes

Notes on operation	Basic insulation is maintained against adjacent modules (in the DIN rail direction).
Notes on operation	Ensure that the supply voltage of the device has a common reference potential.
Notes on operation	For proper use, the specifications of the installation directive (see Downloads) must be observed. For applications or use with third-party products, the specifications, and the safety and warning instructions of the respective third-party manufacturer must also be met.

UMKS- F48M-VR - Termination board



2970167

<https://www.phoenixcontact.com/us/products/2970167>

Approvals

To download certificates, visit the product detail page: <https://www.phoenixcontact.com/us/products/2970167>



EAC

Approval ID: RU*DE.*09.B.00387/20

UMKS- F48M-VR - Termination board



2970167

<https://www.phoenixcontact.com/us/products/2970167>

Classifications

ECLASS

ECLASS-13.0	27141152
ECLASS-15.0	27141152

ETIM

ETIM 10.0	EC002780
-----------	----------

UNSPSC

UNSPSC 21.0	39121400
-------------	----------

UMKS- F48M-VR - Termination board



2970167

<https://www.phoenixcontact.com/us/products/2970167>

Environmental product compliance

EU RoHS

Fulfills EU RoHS substance requirements	Yes
Exemption	6(c)

China RoHS

Environment friendly use period (EFUP)	EFUP-50
	An article-related China RoHS declaration table can be found in the download area for the respective article under "Manufacturer declaration". For all articles with EFUP-E, no China RoHS declaration table issued and required.

EU REACH SVHC

REACH candidate substance (CAS No.)	Lead(CAS: 7439-92-1)
SCIP	df86aad1-6aff-4c82-806a-5b9c82b7ec5e

Phoenix Contact 2026 © - all rights reserved

<https://www.phoenixcontact.com>

Phoenix Contact USA
586 Fulling Mill Road
Middletown, PA 17057, United States
(+717) 944-1300
info@phoenixcon.com