

# UWV 16-POT - Panel feed-through terminal block



3073542

<https://www.phoenixcontact.com/us/products/3073542>

Please be informed that the data shown in this PDF document is generated from our online catalog. Please find the complete data in the user documentation. Our general terms of use for downloads are valid.



16 mm<sup>2</sup>



SCREW



BOX



Panel feed-through terminal block, connection method: Screw connection with tension sleeve, Cable lug connection, number of positions: 1, load current: 76 A, cross section: 6 mm<sup>2</sup> - 25 mm<sup>2</sup>, connection direction of the conductor to plug-in direction: -90 °, width: 12.1 mm, color: gray

## Your advantages

- Well-known connection principle allows worldwide use
- Low temperature rise, thanks to maximum contact force
- Tool-free snap-in principle enables easy mounting on the device panel
- Automatic panel thickness compensation enables universal use
- Reliable seal even with low-viscosity molding compounds

## Commercial data

|                                      |               |
|--------------------------------------|---------------|
| Item number                          | 3073542       |
| Packing unit                         | 50 pc         |
| Minimum order quantity               | 50 pc         |
| Sales key                            | AA28          |
| Product key                          | AA1DDD        |
| GTIN                                 | 4046356344784 |
| Weight per piece (including packing) | 30.114 g      |
| Weight per piece (excluding packing) | 23.9 g        |
| Customs tariff number                | 85369010      |
| Country of origin                    | CN            |

# UWV 16-POT - Panel feed-through terminal block



3073542

<https://www.phoenixcontact.com/us/products/3073542>

## Technical data

### Product properties

|                       |                                   |
|-----------------------|-----------------------------------|
| Product type          | Panel feed-through terminal block |
| Product family        | UWV 16-POT                        |
| Number of positions   | 1                                 |
| Pitch                 | 12.1 mm                           |
| Number of connections | 2                                 |
| Number of rows        | 1                                 |
| Number of potentials  | 1                                 |

### Insulation characteristics

|                      |     |
|----------------------|-----|
| Overvoltage category | III |
| Degree of pollution  | 3   |

### Electrical properties

#### Properties

|                             |       |
|-----------------------------|-------|
| Nominal current $I_N$       | 76 A  |
| Nominal voltage $U_N$       | 500 V |
| Rated voltage (III/3)       | 500 V |
| Rated surge voltage (III/3) | 6 kV  |

### Connection data

#### Connection technology

|                       |                    |
|-----------------------|--------------------|
| Connector system      | UW 16 / PW 16      |
| Nominal cross section | 16 mm <sup>2</sup> |

#### Conductor connection exterior

|   |  |
|---|--|
| Connection method   | Screw connection with tension sleeve       |
| Connection direction of the conductor to plug-in direction                                | -90 °                                      |
| Conductor cross-section rigid   | 6 mm <sup>2</sup> ... 25 mm <sup>2</sup>   |
| Conductor cross-section flexible  | 6 mm <sup>2</sup> ... 16 mm <sup>2</sup>   |
| Conductor cross-section, flexible, with ferrule, without plastic sleeve                   | 6 mm <sup>2</sup> ... 16 mm <sup>2</sup>   |
| Conductor cross-section, flexible, with ferrule, with plastic sleeve                      | 6 mm <sup>2</sup> ... 16 mm <sup>2</sup>   |
| 2 conductors with same cross section, rigid   | 2.5 mm <sup>2</sup> ... 10 mm <sup>2</sup> |
| 2 conductors with same cross section, flexible  | 2.5 mm <sup>2</sup> ... 6 mm <sup>2</sup>  |
| 2 conductors with same cross section, flexible, with ferrule without plastic sleeve       | 4 mm <sup>2</sup> ... 6 mm <sup>2</sup>    |
| 2 conductors with the same cross section, flexible, with TWIN ferrule with plastic sleeve | 4 mm <sup>2</sup> ... 6 mm <sup>2</sup>    |
| Internal cylindrical gage   | B7   |
| Stripping length  | 16 mm                                      |
| Tightening torque   | 2.5 Nm ... 3 Nm                            |

# UWV 16-POT - Panel feed-through terminal block



3073542

<https://www.phoenixcontact.com/us/products/3073542>

## Conductor connection interior

|  |                      |
|--|----------------------|
| Connection method  | Cable lug connection |
| Connection direction of the conductor to plug-in direction | 0 °                  |

## Mounting

|                 |             |
|-----------------|-------------|
| Panel thickness | 1 mm...6 mm |
|-----------------|-------------|

## Material specifications

### Material data - contact

|                         |  |
|-------------------------|--|
| Note                    | WEEE/RoHS-compliant, free of whiskers according to IEC 60068-2-82/JEDEC JESD 201 |
| Contact material        | Cu alloy   |
| Surface characteristics | tin-plated   |

### Material data - housing

|   |             |
|---|-------------|
| Color (Housing)   | gray (7042) |
| Insulating material   | PA          |
| Insulating material group   | I           |
| CTI according to IEC 60112  | 600         |
| Flammability rating according to UL 94                            | V0          |
| Glow wire flammability index GWFI according to EN 60695-2-12      | 850         |
| Glow wire ignition temperature GWIT according to EN 60695-2-13    | 775         |
| Temperature for the ball pressure test according to EN 60695-10-2 | 125 °C      |

## Notes

### Safety note

|             |  |
|-------------|--|
| Safety note | <ul style="list-style-type: none"><li>• Only electrically qualified personnel may install and operate the product.<br/>To recognize and prevent danger, the qualified personnel must be familiar with the basics of electrical engineering.</li><li>• Observe the technical data provided here and refer to the documents listed under "Downloads". The download area contains important information, such as installation notes, technical drawings, and 3D data.</li><li>• The cable entry funnel is not safe to touch. Never connect or disconnect the terminal when it is energized. Take appropriate steps to ensure touch protection.</li><li>• To maintain the nominal voltage, align the cable lugs straight and centered, and cast the terminals on the inside.</li></ul> |
|-------------|--|


## Dimensions

# UWV 16-POT - Panel feed-through terminal block



3073542

<https://www.phoenixcontact.com/us/products/3073542>

|                     |  |
|---------------------|--|
| Dimensional drawing |  |
| Pitch               | 12.1 mm  |
| Width [w]           | 12.1 mm  |

## External dimensions

|             |         |
|-------------|---------|
| Width [w]   | 12.1 mm |
| Height [h1] | 43.1 mm |
| Length [l1] | 39.1 mm |

## Internal dimensions

|             |         |
|-------------|---------|
| Width [w]   | 12.1 mm |
| Height [h2] | 26 mm   |
| Length [l2] | 23.6 mm |

## Mechanical tests

### Test for conductor damage and slackening

|               |                       |
|---------------|-----------------------|
| Specification | IEC 60947-7-1:2009-04 |
| Result        | Test passed           |

### Pull-out test

|   |   |
|---|---|
| Specification   | IEC 60947-7-1:2009-04                   |
| Conductor cross-section/conductor type/tractive force setpoint/actual value | 6 mm <sup>2</sup> / solid / > 80 N      |
|   | 6 mm <sup>2</sup> / flexible / > 80 N   |
|   | 25 mm <sup>2</sup> / stranded / > 135 N |
|   | 16 mm <sup>2</sup> / flexible / > 100 N |

## Electrical tests

### Temperature-rise test

|                                   |                                |
|-----------------------------------|--------------------------------|
| Specification                     | IEC 60947-7-1:2009-04          |
| Requirement temperature-rise test | Increase in temperature ≤ 45 K |

### Short-time withstand current

|               |                       |
|---------------|-----------------------|
| Specification | IEC 60947-7-1:2009-04 |
|---------------|-----------------------|

### Air clearances and creepage distances | 1. Insulation coordination

|  |                       |
|--|-----------------------|
| Application                            | without spacer plate  |
| Specification                          | IEC 60947-7-1:2009-04 |
| Insulating material group              | I                     |
| Comparative tracking index (IEC 60112) | CTI 600               |
| Rated insulation voltage (III/3)       | 500 V                 |

# UWV 16-POT - Panel feed-through terminal block



3073542

<https://www.phoenixcontact.com/us/products/3073542>

|  |        |
|--|--------|
| Rated surge voltage (III/3)                            | 6 kV   |
| minimum clearance value - non-homogenous field (III/3) | 5.5 mm |
| minimum creepage distance (III/3)                      | 6.3 mm |

## Air clearances and creepage distances | 2. Insulation coordination

|  |                       |
|--|-----------------------|
| Application  | with spacer plate     |
| Specification  | IEC 60947-7-1:2009-04 |
| Insulating material group                              | I                     |
| Comparative tracking index (IEC 60112)                 | CTI 600               |
| Rated insulation voltage (III/3)                       | 800 V                 |
| Rated surge voltage (III/3)                            | 8 kV                  |
| minimum clearance value - non-homogenous field (III/3) | 8 mm                  |
| minimum creepage distance (III/3)                      | 10 mm                 |

## Environmental and real-life conditions

### Vibration test

|                        |                             |
|------------------------|-----------------------------|
| Specification          | IEC 60068-2-6:2007-12       |
| Frequency              | 10 - 150 - 10 Hz            |
| Sweep speed            | 1 octave/min                |
| Amplitude              | 0.35 mm (10 Hz ... 60.1 Hz) |
| Acceleration           | 5g (60.1 Hz ... 150 Hz)     |
| Test duration per axis | 2.5 h                       |
| Test directions        | X-, Y- and Z-axis           |

### Shocks

|                 |                                   |
|-----------------|-----------------------------------|
| Specification   | IEC 60068-2-27:2008-02            |
| Pulse shape     | Semi-sinusoidal                   |
| Acceleration    | 30g                               |
| Shock duration  | 18 ms                             |
| Test directions | X-, Y- and Z-axis (pos. and neg.) |

### Glow-wire test

|                  |                        |
|------------------|------------------------|
| Specification    | IEC 60695-2-11:2014-02 |
| Temperature      | 960 °C                 |
| Time of exposure | 30 s                   |

### Ambient conditions

|   |   |
|---|---|
| Ambient temperature (storage/transport) | -40 °C ... 70 °C  |
| Relative humidity (storage/transport)   | 30 % ... 70 %   |
| Ambient temperature (assembly)          | -5 °C ... 100 °C  |
| Ambient temperature (operation)         | -40 °C ... 105 °C (Depending on the current carrying capacity/derating curve) |

### Ambient conditions

|                                 |   |
|---------------------------------|---|
| Ambient temperature (operation) | -40 °C ... 105 °C (Depending on the current carrying capacity/derating curve) |
|---------------------------------|---|

# UWV 16-POT - Panel feed-through terminal block



3073542

<https://www.phoenixcontact.com/us/products/3073542>

|   |                  |
|---|------------------|
| Ambient temperature (storage/transport) | -40 °C ... 70 °C |
| Relative humidity (storage/transport)   | 30 % ... 70 %    |
| Ambient temperature (assembly)          | -5 °C ... 100 °C |

## Packaging specifications

|                   |                     |
|-------------------|---------------------|
| Type of packaging | packed in cardboard |
|-------------------|---------------------|


# UWV 16-POT - Panel feed-through terminal block

3073542

<https://www.phoenixcontact.com/us/products/3073542>

## Drawings


Dimensional drawing



\* Only when using the UW...-F flange plate

\*\* Dimensions when using the DP-UW... spacer plate

Dimensional drawing




# UWV 16-POT - Panel feed-through terminal block



3073542

<https://www.phoenixcontact.com/us/products/3073542>

Diagram



Type: UWV 16-POT

# UWV 16-POT - Panel feed-through terminal block



3073542

<https://www.phoenixcontact.com/us/products/3073542>

## Approvals

To download certificates, visit the product detail page: <https://www.phoenixcontact.com/us/products/3073542>

|  <b>CSA</b><br>Approval ID: 13631 |                       |                       |                   |                             |
|--|-----------------------|-----------------------|-------------------|-----------------------------|
|  | Nominal voltage $U_N$ | Nominal current $I_N$ | Cross section AWG | Cross section $\text{mm}^2$ |
| B  | 600 V                 | 80 A                  | 10 - 4            | -                           |
| C  | 600 V                 | 80 A                  | 10 - 4            | -                           |

|  <b>cULus Recognized</b><br>Approval ID: E60425-20100423 |                       |                       |                   |                             |
|---|-----------------------|-----------------------|-------------------|-----------------------------|
|   | Nominal voltage $U_N$ | Nominal current $I_N$ | Cross section AWG | Cross section $\text{mm}^2$ |
| B   | 600 V                 | 85 A                  | 10 - 4            | -                           |
| C   | 600 V                 | 85 A                  | 10 - 4            | -                           |

# UWV 16-POT - Panel feed-through terminal block



3073542

<https://www.phoenixcontact.com/us/products/3073542>

## Classifications

### ECLASS

|             |          |
|-------------|----------|
| ECLASS-13.0 | 27141134 |
| ECLASS-15.0 | 27141134 |

### ETIM

|           |          |
|-----------|----------|
| ETIM 10.0 | EC001283 |
|-----------|----------|

### UNSPSC

|             |          |
|-------------|----------|
| UNSPSC 21.0 | 39121400 |
|-------------|----------|

# UWV 16-POT - Panel feed-through terminal block



3073542

<https://www.phoenixcontact.com/us/products/3073542>

## Environmental product compliance

### EU RoHS

|   |                    |
|---|--------------------|
| Fulfills EU RoHS substance requirements | Yes, No exemptions |
|---|--------------------|

### China RoHS

|  |  |
|--|--|
| Environment friendly use period (EFUP) | EFUP-E                                   |
|  | No hazardous substances above the limits |

### EU REACH SVHC

|                                     |                            |
|-------------------------------------|----------------------------|
| REACH candidate substance (CAS No.) | No substance above 0.1 wt% |
|-------------------------------------|----------------------------|

Phoenix Contact 2026 © - all rights reserved  
<https://www.phoenixcontact.com>

Phoenix Contact USA  
586 Fulling Mill Road  
Middletown, PA 17057, United States  
(+717) 944-1300  
[info@phoenixcon.com](mailto:info@phoenixcon.com)