

PTPOWER 50 P BU - High-current terminal block



3260066

<https://www.phoenixcontact.com/us/products/3260066>

Please be informed that the data shown in this PDF document is generated from our online catalog. Please find the complete data in the user documentation. Our general terms of use for downloads are valid.



High-current terminal block, with test socket, nom. voltage: 1000 V, nominal current: 150 A, number of connections: 2, number of positions: 1, connection method: PowerTurn connection, 1 level, cross section: 10 mm² - 70 mm², mounting type: NS 35/15, color: blue

Your advantages

- Quick and easy connection is now also possible for large conductors with the high-current terminal block
- In addition to using the existing test pick-off, pick-off terminal blocks can be connected, each of which can also accommodate two test cables
- The compact design enables wiring in a confined space
- The Push-in connection terminal blocks are characterized by the system features of the CLIPLINE complete system and by easy and tool-free wiring of conductors with ferrules or solid conductors

Commercial data

| | |
|--------------------------------------|---------------|
| Item number | 3260066 |
| Packing unit | 10 pc |
| Minimum order quantity | 10 pc |
| Sales key | BE22 |
| Product key | BE2211 |
| GTIN | 4046356998031 |
| Weight per piece (including packing) | 162.8 g |
| Weight per piece (excluding packing) | 155.76 g |
| Customs tariff number | 85369010 |
| Country of origin | TR |

PTPOWER 50 P BU - High-current terminal block



3260066

<https://www.phoenixcontact.com/us/products/3260066>

Technical data

Product properties

| | |
|-----------------------|-----------------------------|
| Product type | High current terminal block |
| Number of positions | 1 |
| Number of connections | 2 |
| Number of rows | 1 |
| Potentials | 1 |

Insulation characteristics

| | |
|----------------------|-----|
| Overvoltage category | III |
| Degree of pollution | 3 |

Electrical properties

| | |
|---|--------|
| Rated surge voltage | 8 kV |
| Maximum power dissipation for nominal condition | 4.73 W |

Connection data

| | |
|---------------------------------|--------------------|
| Number of connections per level | 2 |
| Nominal cross section | 50 mm ² |
| Rated cross section AWG | 2/0 |

1 level

| | |
|--|---|
| Connection method | PowerTurn connection |
| Stripping length | 30 mm ... 32 mm |
| Internal cylindrical gage | A10 |
| Connection in acc. with standard | IEC 60947-7-1 |
| Conductor cross-section rigid | 10 mm ² ... 70 mm ² |
| Cross section AWG | 6 ... 2/0 (converted acc. to IEC) |
| Conductor cross-section flexible | 10 mm ² ... 70 mm ² |
| Conductor cross-section, flexible [AWG] | 6 ... 2/0 (converted acc. to IEC) |
| Conductor cross-section flexible (ferrule without plastic sleeve) | 10 mm ² ... 50 mm ² |
| Flexible conductor cross-section (ferrule with plastic sleeve) | 10 mm ² ... 50 mm ² |
| Cross-section with insertion bridge, rigid | 10 mm ² ... 50 mm ² |
| Cross-section with insertion bridge, flexible | 10 mm ² ... 50 mm ² |
| Cross-section with insertion bridge, flexible, with ferrule without plastic sleeve | 10 mm ² (50 mm ²) |
| Cross-section with insertion bridge, flexible, with ferrule with plastic sleeve | 10 mm ² ... 50 mm ² |
| Nominal current | 150 A |
| Maximum load current | 150 A (with 50 mm ² conductor cross-section) |
| Nominal voltage | 1000 V |

1 level Connection cross sections directly pluggable

| | |
|-------------------------------|---|
| Conductor cross-section rigid | 10 mm ² ... 70 mm ² |
|-------------------------------|---|

PTPOWER 50 P BU - High-current terminal block



3260066

<https://www.phoenixcontact.com/us/products/3260066>

| | |
|---|---|
| Conductor cross-section, rigid [AWG] | 8 ... 2/0 (converted acc. to IEC) |
| Conductor cross-section flexible (ferrule without plastic sleeve) | 10 mm ² ... 50 mm ² |
| Flexible conductor cross-section (ferrule with plastic sleeve) | 10 mm ² ... 50 mm ² |

Ex data

Rated data (ATEX/IECEx)

| | |
|-----------------------------------|--|
| Identification | ⊕ II 2 GD Ex eb IIC Gb |
| Operating temperature range | -60 °C ... 110 °C |
| Ex-certified accessories | 1206612 SZF 3-1,0X5,5 1201662 E/AL-NS 35 |
| List of bridges | / EB 2-20/PT / 3260067 / EB 3-20/PT / 3260068 |
| Bridge data | 131 A (50 mm ²) |
| Ex temperature increase | 40 K (147 A / 50 mm ²) |
| at bridging with insertion bridge | 1100 V |
| Rated insulation voltage | 1000 V |
| output | (Permanent) |

Ex level General

| | |
|----------------------|---------|
| Rated voltage | 1100 V |
| Rated current | 134 A |
| Maximum load current | 134 A |
| Contact resistance | 0.16 mΩ |

Ex connection data General

| | |
|--|---|
| Ferrule length | 30 mm ... 32 mm |
| Stripping length | 30 mm |
| Nominal cross section | 50 mm ² |
| Rated cross section AWG | 1/0 |
| Connection capacity rigid | 10 mm ² ... 70 mm ² |
| Connection capacity AWG | 8 ... 2/0 |
| Conductor cross-section flexible, with ferrule without plastic sleeve min. | 16 mm ² |
| Conductor cross-section flexible, with ferrule without plastic sleeve max. | 50 mm ² |

Dimensions

| | |
|-------------------|--------|
| Width | 20 mm |
| Height | 101 mm |
| Depth on NS 35/15 | 105 mm |

Material specifications

| | |
|--|-----------------|
| Color | blue (RAL 5015) |
| Flammability rating according to UL 94 | V0 |
| Insulating material group | I |

PTPOWER 50 P BU - High-current terminal block



3260066

<https://www.phoenixcontact.com/us/products/3260066>

| | |
|---|-------------|
| Insulating material | PA |
| Static insulating material application in cold | -60 °C |
| Temperature index of insulation material (DIN EN 60216-1 (VDE 0304-21)) | 125 °C |
| Relative insulation material temperature index (Elec., UL 746 B) | 130 °C |
| Fire protection for rail vehicles (DIN EN 45545-2) R22 | HL 1 - HL 3 |
| Fire protection for rail vehicles (DIN EN 45545-2) R23 | HL 1 - HL 3 |
| Fire protection for rail vehicles (DIN EN 45545-2) R24 | HL 1 - HL 3 |
| Fire protection for rail vehicles (DIN EN 45545-2) R26 | HL 1 - HL 3 |
| Calorimetric heat release NFPA 130 (ASTM E 1354) | 27,5 MJ/kg |
| Surface flammability NFPA 130 (ASTM E 162) | passed |
| Specific optical density of smoke NFPA 130 (ASTM E 662) | passed |
| Smoke gas toxicity NFPA 130 (SMP 800C) | passed |

Mechanical properties

Mechanical data

| | |
|-----------------|----|
| Open side panel | No |
|-----------------|----|

Environmental and real-life conditions

Ambient conditions

| | |
|--|--|
| Ambient temperature (operation) | -60 °C ... 110 °C (Operating temperature range incl. self-heating; for max. short-term operating temperature, see RTI Elec.) |
| Ambient temperature (storage/transport) | -25 °C ... 60 °C (for a short time, not exceeding 24 h, -60 °C to +70 °C) |
| Ambient temperature (assembly) | -5 °C ... 70 °C |
| Ambient temperature (actuation) | -5 °C ... 70 °C |
| Permissible humidity (operation) | 20 % ... 90 % |
| Permissible humidity (storage/transport) | 30 % ... 70 % |

Standards and regulations

| | |
|----------------------------------|---------------|
| Connection in acc. with standard | IEC 60947-7-1 |
|----------------------------------|---------------|

Mounting

| | |
|---------------|----------|
| Mounting type | NS 35/15 |
|---------------|----------|

PTPOWER 50 P BU - High-current terminal block


3260066

<https://www.phoenixcontact.com/us/products/3260066>

Drawings

Schematic diagram

PTPOWER



| | | |
|----------------|--|-------|
| AGK 10-PTPOWER | 0,5 mm ² ... 16 mm ² | 18 mm |
| PTPOWER 35 | 2,5 mm ² ... 35 mm ² | 25 mm |
| PTPOWER 50 | 10 mm ² ... 50 mm ² | 32 mm |
| PTPOWER 95 | 25 mm ² ... 95 mm ² | 40 mm |
| PTPOWER 185 | 95 mm ² ... 185 mm ² | 40 mm |



PTPOWER 50 P BU - High-current terminal block



3260066

<https://www.phoenixcontact.com/us/products/3260066>

Circuit diagram



PTPOWER 50 P BU - High-current terminal block




3260066

<https://www.phoenixcontact.com/us/products/3260066>


Approvals

To download certificates, visit the product detail page: <https://www.phoenixcontact.com/us/products/3260066>


|  cUL Recognized Approval ID: E60425 | | | | |
|--|-----------------------|-----------------------|-------------------|----------------------|
| | Nominal voltage U_N | Nominal current I_N | Cross section AWG | Cross section mm^2 |
| C | 1000 V | 140 A | 8 - 1/0 | - |


|  UL Recognized Approval ID: E60425 | | | | |
|---|-----------------------|-----------------------|-------------------|----------------------|
| | Nominal voltage U_N | Nominal current I_N | Cross section AWG | Cross section mm^2 |
| E | 1000 V | 140 A | 8 - 1/0 | - |


| DNV Approval ID: TAE00000Z9 | | | | |
|---------------------------------------|--|--|--|--|
|---------------------------------------|--|--|--|--|

|  CSA Approval ID: 13631 | | | | |
|--|-----------------------|-----------------------|-------------------|----------------------|
| | Nominal voltage U_N | Nominal current I_N | Cross section AWG | Cross section mm^2 |
| B | 600 V | 140 A | 8 - 1/0 | - |
| C | 1000 V | 140 A | 8 - 1/0 | - |

|  CCC Approval ID: 2020322313000630 | | | | |
|---|--|--|--|--|
|---|--|--|--|--|

|  UKCA-EX Approval ID: CML 22UKEX1227U | | | | |
|--|--|--|--|--|
|--|--|--|--|--|

|  IECEX Approval ID: IECEXSEV14.0013U | | | | |
|---|--|--|--|--|
|---|--|--|--|--|

|  ATEX Approval ID: SEV14ATEX0156U | | | | |
|--|-----------------------|-----------------------|-------------------|----------------------|
| | Nominal voltage U_N | Nominal current I_N | Cross section AWG | Cross section mm^2 |
| keine | | | | |


PPOWER 50 P BU - High-current terminal block



3260066

<https://www.phoenixcontact.com/us/products/3260066>

| | | | | |
|-----------------------------|--------|-------|---|---------|
| Only rigid conductors | 1100 V | 134 A | - | 10 - 70 |
| multi-stranded with ferrule | 1100 V | 134 A | - | 16 - 50 |

|  IECEX Approval ID: IECExSEV14.0013U | | | | |
|---|-----------------------|-----------------------|-------------------|----------------------|
| | Nominal voltage U_N | Nominal current I_N | Cross section AWG | Cross section mm^2 |
| keine | | | | |
| | 1100 V | 134 A | - | - |
| Only rigid conductors | 1100 V | 134 A | - | - |
| multi-stranded with ferrule | 1100 V | 134 A | - | - |

|  EAC Ex Approval ID: KZ 7500525010101950 | | | | |
|--|--|--|--|--|
| | | | | |

PTPOWER 50 P BU - High-current terminal block



3260066

<https://www.phoenixcontact.com/us/products/3260066>

Classifications

ECLASS

| | |
|-------------|----------|
| ECLASS-13.0 | 27250101 |
| ECLASS-15.0 | 27250101 |

ETIM

| | |
|-----------|----------|
| ETIM 10.0 | EC000897 |
|-----------|----------|

UNSPSC

| | |
|-------------|----------|
| UNSPSC 21.0 | 39121400 |
|-------------|----------|

PTPOWER 50 P BU - High-current terminal block



3260066

<https://www.phoenixcontact.com/us/products/3260066>

Environmental product compliance

EU RoHS

| | |
|---|--------------------|
| Fulfills EU RoHS substance requirements | Yes, No exemptions |
|---|--------------------|

China RoHS

| | |
|--|--|
| Environment friendly use period (EFUP) | EFUP-E |
| | No hazardous substances above the limits |

EU REACH SVHC

| | |
|-------------------------------------|----------------------------|
| REACH candidate substance (CAS No.) | No substance above 0.1 wt% |
|-------------------------------------|----------------------------|

Phoenix Contact 2026 © - all rights reserved
<https://www.phoenixcontact.com>

Phoenix Contact USA
586 Fulling Mill Road
Middletown, PA 17057, United States
(+717) 944-1300
info@phoenixcon.com