

FLK 26-LONG LATCH - Termination board



5601732

<https://www.phoenixcontact.com/us/products/5601732>

Please be informed that the data shown in this PDF document is generated from our online catalog. Please find the complete data in the user documentation. Our general terms of use for downloads are valid.



VARIOFACE module, with screw connection and flat-ribbon cable connector, for mounting on NS 32 or NS 35/7.5, with pin strip and short and long locking latches for socket strips, 26-pos.

The figure shows a 40-position version

Commercial data

Item number	5601732
Packing unit	1 pc
Note	Made to order (non-returnable)
Sales key	NULL
Product key	DK2BZZ
GTIN	4046356685962
Weight per piece (including packing)	123.7 g
Weight per piece (excluding packing)	112.8 g
Customs tariff number	85369080
Country of origin	DE

FLK 26-LONG LATCH - Termination board



5601732

<https://www.phoenixcontact.com/us/products/5601732>

Technical data

Product properties

Product type	Interface module
Number of positions	26

Electrical properties

Nominal voltage U_N	< 50 V AC
	60 V DC
Max. current carrying capacity per branch	1 A

Connection data

Field level

Connection in acc. with standard	IEC / EN
Connection method	Screw connection
Stripping length	8 mm
Screw thread	M3
Conductor cross-section rigid	0.2 mm ² ... 4 mm ²
Conductor cross-section flexible	0.2 mm ² ... 2.5 mm ²
Conductor cross-section AWG	24 ... 12

Controller level

Connection method	IDC/FLK pin strip
Pitch	2.54 mm

Dimensions

Item dimensions

Width	78.8 mm
Height	77 mm
Depth	58.5 mm

Material specifications

Housing insulation material	Polyamide 6 green
-----------------------------	-------------------

Environmental and real-life conditions

Ambient conditions

Ambient temperature (operation)	-20 °C ... 50 °C
Ambient temperature (storage/transport)	-20 °C ... 70 °C

Mounting

Mounting position	any
-------------------	-----

Notes

FLK 26-LONG LATCH - Termination board



5601732

<https://www.phoenixcontact.com/us/products/5601732>

Notes on operation

For proper use, the specifications of the installation directive (see Downloads) must be observed. For applications or use with third-party products, the specifications, and the safety and warning instructions of the respective third-party manufacturer must also be met.

FLK 26-LONG LATCH - Termination board



5601732

<https://www.phoenixcontact.com/us/products/5601732>

Environmental product compliance

EU REACH SVHC

REACH candidate substance (CAS No.)	No substance above 0.1 wt%
-------------------------------------	----------------------------

Phoenix Contact 2026 © - all rights reserved

<https://www.phoenixcontact.com>

Phoenix Contact USA
586 Fulling Mill Road
Middletown, PA 17057, United States
(+717) 944-1300
info@phoenixcon.com