


# SK 2,8 REEL P5,2 WH CUS - Marker card



8199986

<https://www.phoenixcontact.com/us/products/8199986>

Please be informed that the data shown in this PDF document is generated from our online catalog. Please find the complete data in the user documentation. Our general terms of use for downloads are valid.



Marker card, Roll, can be ordered: by card, white (RAL 9010), labeled according to customer specifications, mounting type: adhesive, for terminal block width: 5.2 mm, Number of individual labels: 14

## Your advantages

- Labeling service: Phoenix Contact can custom-label all SK ... markers in accordance with your requirements
- Ideal for labeling COMBICON connectors
- The SK labeling range offers self-adhesive marker strips for labeling products that do not have a marker groove

## Commercial data

Item number	8199986
Packing unit	1 pc
Minimum order quantity	1 pc
Note	Made to order (non-returnable)
Product key	BG8113
GTIN	4055626460642
Weight per piece (including packing)	0.51 g
Weight per piece (excluding packing)	0.51 g
Country of origin	PL

# SK 2,8 REEL P5,2 WH CUS - Marker card



8199986

<https://www.phoenixcontact.com/us/products/8199986>

## Technical data

### Notes

Order information:	Marking up to max. 25-pos.
--------------------	----------------------------

### Product properties

Product type	Terminal marker
Pitch	5.2 mm

### Marking

Number of individual labels	14
Number of individual labels per row	1
Number of marker strips	14
Slot type	Label
Identification technology	Thermal transfer

### Dimensions

Width	50.00 mm
Height	2.80 mm
Depth	0.07 mm
Pitch	5.2 mm

### Material specifications

Color	white (RAL 9010)
Material	Polyester
Base element material	Polyester
Components	free from silicone and halogen

### Environmental and real-life conditions

#### Ambient conditions

Ambient temperature (operation)	-40 °C ... 150 °C
Recommended ambient temperature (storage/transport)	23 °C
Recommended humidity (storage/transport)	50 % (Storage in a dry and dark place in the original packaging is recommended)

#### UV resistance

Specification	DIN EN ISO 4892-2:2021-11 (following)
---------------	---------------------------------------

#### Wipe resistance of inscriptions

Specification	DIN EN 61010-1 (VDE 0411-01):2020-03
	DIN EN 62208 (VDE 0660-511):2012-06 (in parts)

### Standards and regulations

Wipe resistance	DIN EN 61010-1 (VDE 0411-1)
-----------------	-----------------------------

# SK 2,8 REEL P5,2 WH CUS - Marker card



8199986

<https://www.phoenixcontact.com/us/products/8199986>

## Mounting

Mounting type

adhesive

# SK 2,8 REEL P5,2 WH CUS - Marker card

8199986

<https://www.phoenixcontact.com/us/products/8199986>

## Drawings

Schematic diagram



- ① Horizontal
- ② Vertical

# SK 2,8 REEL P5,2 WH CUS - Marker card



8199986

<https://www.phoenixcontact.com/us/products/8199986>

## Classifications

### ECLASS

ECLASS-13.0	27281101
ECLASS-15.0	27281101

### ETIM

ETIM 10.0	EC000761
-----------	----------

### UNSPSC

UNSPSC 21.0	39131500
-------------	----------

# SK 2,8 REEL P5,2 WH CUS - Marker card



8199986

<https://www.phoenixcontact.com/us/products/8199986>

## Environmental product compliance

### EU RoHS

Fulfills EU RoHS substance requirements	Yes, No exemptions
---	--------------------

### EU REACH SVHC

REACH candidate substance (CAS No.)	No substance above 0.1 wt%
-------------------------------------	----------------------------

Phoenix Contact 2026 © - all rights reserved

<https://www.phoenixcontact.com>

Phoenix Contact USA  
586 Fulling Mill Road  
Middletown, PA 17057, United States  
(+717) 944-1300  
[info@phoenixcon.com](mailto:info@phoenixcon.com)